TECHNICAL SPECIFICATION FOR DOC LEVELLER

1.	**Application**	a) To facilitate quick and safe loading / unloading of Goods by Forklift truck from inside the truck / container (viz. Finished lubes, Additive drums or Bags, Packaging materials on pallets or bags);
2.	**Quantity**	FP warehouse – 5nos Additive W/house – 3nos Packaging warehouse – 3nos Drum plant – 4nos Total – 15nos.
3.	**Design standard**	Conforming to European standard – EN-1398
4.	**Capacity**	Uniformly distributed load - 15MT Design Point load – 6MT
5.	**Model (VTC)**	**
6.	**Deck length**	3000mm
7.	**Deck Width**	2200mm
8.	**Frame height**	550mm – VTC
9.	**Lip Extension**	410mm – VTC
10.	**Bumpers**	Super Bumpers - to be included; Approx. size- 150mm width x 400mm height x 130mm depth including steel support;
11.	**Overall length (including Lip)**	3410mm (VTC)
12.	**Working height**	Maximum positive excursion - (+) 600mm Maximum negative excursion- (-) 300mm
13.	**Gradient**	Max. Upto 12.5% (upto 7 deg)
14.	**Powerpack**	Platform shall be safely and reliably controlled by a electro-hydraulic drive system of suitable rating with suitable safety features for safe operation & maintenance. Push-button to activate the dock leveler into operation; Electro-hydraulic power pack – to consist of all major components viz. Motor, High pressure Gear / Vane pump, Oil filters, Oil reservoir, solenoid valve, relief valve etc. all components of reputed make. Vendors to confirm the makes. Vendor to also confirm the location & space required for the Drive unit suitable for easy maintenance;

15.	**Operator & Control unit**	Electrohydraulic operator 400V, 50Hz, IP-55. Membrane push button with Press and Hold actuation and Emergency Stop integrated in IP-65 enclosure.
16.	**Platform**	Heavy duty, non-skid or anti-slip, chequered platform reinforced for maximum strength & rigidity;
17.	**Painting**	As per Manufacturer's standard; Structural members shall be preferably galvanized and then epoxy painted;
18.	**Safety features**	(a) Safety stop valve integrated in the lift cylinder; Lift cylinder to be of reputed make and with polyurethane seal of reputed make; (b) Maximum pressure valve © Maintenance crutch with positive engagement (d) Rubber bumpers to protect the dock levellers