Opening doors
to business and life

ASSA ABLOY Entrance Systems

ASSA ABLOY
NIHVA
NIHVA Technologies Pvt. Ltd.

The global leader in
door opening solutions

Project	**Rajasthan Hangar**
Location	
Application	**Civil Aviation**
Our ref.no.	**219-028**
Calculated	**28-1-2019 15:07**
Notes	**Price based on 2 doors**

System summary

Calc by	Henk v.d. Heijden
Version	V 2-1-2019 10:10:28 4598
Revision	
Identical doors	2
Total weight	10253 kg
Shipping weight	11975 kg
Shipping volume	76,64 m³
Overall clear width	42000 mm
Environment	Megadoor Standard
Nominal current	25,0 A
Total power	11,5 kW
Hoist peak current	35,9 A
Voltage/Frequency	400 V 50 Hz
Control panel base	A1 Door Cabinet, 500x600x250
Control panel	A10x Door/Mullion Cabinet, 500x600x250 (9A nom.)
Control panel	A10x Door Cabinet, 500x600x250 (9A nom.)
Control panel	A10x Door/Mullion Cabinet, 500x600x250 (9A nom.)

Options selected

Make level door	
Back-up power switch	
Audible and visual alarm	
Beam clamps	

Door 1 options selected

No installation equipment	1 no.
Metal trim both sides	
Floor/site-built door leaf	
Colored clamp strip on inside	
Colored clamp strip on outside	

Door 1

CW	13706 mm
CH	7658 mm
Depth	290 mm
Differential pressure	1 kPa (20,9 psf)
Leaf height	8962 mm
Total height	9432 mm
Total width	13946 mm
Number of splices	1
Guide shoe load	9,9 kN
Leaf fabric outside	Standard fabric, Colour TBC
Leaf fabric inside	Standard fabric, Colour TBC
Hoist	1 * SK 973.1Z-100LA/4
Open time	41 sec
Moving weight	1686 kg
Total weight	2665 kg
Bottom seal	EPDM Grey 644 mm

Mullion 12

Mullion	VKR400x200x6,3 355
Clear under mullion	7000 mm
Building deflection down	61 mm
Building deflection up	61 mm
Mullion swing time	45 sec
Mullion floor pit lenght	1700 mm
Mullion hoist load	675 kg
Mullion weight	1172 kg

Door 2 options selected

Metal trim both sides
Floor/site-built door leaf
Colored clamp strip on inside
Colored clamp strip on outside

Door 2

CW	13706 mm
CH	7658 mm
Depth	290 mm
Differential pressure	1 kPa (20,9 psf)
Leaf height	8962 mm
Total height	9432 mm
Total width	13946 mm
Number of splices	1
Guide shoe load	9,9 kN
Leaf fabric outside	Standard fabric, Colour TBC
Leaf fabric inside	Standard fabric, Colour TBC
Hoist	1 * SK 973.1Z-100LA/4
Open time	41 sec
Moving weight	1686 kg
Total weight	2582 kg
Bottom seal	EPDM Grey 644 mm

Mullion 23

Mullion	VKR400x200x6,3 355
Clear under mullion	7000 mm
Building deflection down	61 mm
Building deflection up	61 mm
Mullion swing time	45 sec
Mullion floor pit lenght	1700 mm
Mullion hoist load	675 kg
Mullion weight	1172 kg

Door 3 options selected

Metal trim both sides
Colored clamp strip on inside
Colored clamp strip on outside

Door 3

CW	13706 mm
CH	7658 mm
Depth	290 mm
Differential pressure	1 kPa (20,9 psf)
Leaf height	8962 mm
Total height	9432 mm
Total width	13946 mm
Number of splices	1
Guide shoe load	9,9 kN
Leaf fabric outside	Standard fabric, Colour TBC
Leaf fabric inside	Standard fabric, Colour TBC
Hoist	1 * SK 973.1Z-100LA/4
Open time	41 sec
Moving weight	1686 kg
Total weight	2663 kg
Bottom seal	EPDM Grey 644 mm