ASSA ABLOY

AUFTRAGSBESTÄTIGUNG/ ORDER CONFIRMATION

ASSA ABLOY Entrance Systems - Am Mondschein 25 - D-59557 Lippstadt

NIHVA Technologies PVT LTD 27 8/1 Coromant Housing Society 411044 Pune, Nigdi Pradhikar India	**Auftrags-Nr./Order No** 30901979 **Datum/Date** 2022-12-29 **Referenz/Reference** Kathale **Verkäufer/Salesman**

Kunden-Nr./Customer No.	**Innendienst/Internal department**	**Versandart/Way of delivery**
1059669	Olga Ziebart +49.2941.766. x 746	Sea
Ihre Ust-ID Nr./Your TAX No	**Ihre Bestell-Nr./Your Order**	**Versandbedingungen/Terms of delivery**
	NVA-601	FCA / Pilzen incl.standard versand / Forwarder (W)

Lieferadresse/Delivery address **Nr. Lieferadresse/Delivery address No.**	**Zahlungsbedingungen/Terms of payment**
NIHVA Technologies PVT LT1059669 27 8/1 Coromant Housing Society 411044 Pune, Nigdi Pradhikar India	Due Net 90

Pos. **item**	**Produkt** **Product**	**Beschreibung** **Description**	**Versanddatum** **Ship date**	**Anzahl** **QTY**	**Einheit** **Unit**	**Preis/Einh.** **Price/Unit**	**Preis** **Price**
10	**AD_RP300**	**ASSA ABLOY RP300**	**2023-01-24**	**1.000**	**ST**	**3,850.00**	**3,850.00**

Serien-Nr. 2620013104

Door type	High-speed roller door RapidProtect 300
Daylight width	2.500 mm
Daylight height	2.400 mm
Door control system	MCC (7110)
MCC(7110) type	Standard, wth combibox mp plas
Max. Opening Speed	2,3 m/s
Max. Closing Speed	1,7 m/s
Control box position	Mounted next to the drive unit
Control system position	Right
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Pre running photocell at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Grey, similar to RAL 7001
Silicone free	Silicone free
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: CZ 682 534 558
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Sven J. Lars Ynner
Marina Lindholm

Pos.	Produkt	Beschreibung	Versanddatum	Anzahl	Einheit	Preis/Einh.	Preis
item	Product	Description	Ship date	QTY	Unit	Price/Unit	Price

MCC display type	Prepared for display
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Motor cable length	1.000 mm
Mains connection cable length	3.000 mm
Combibox cable length	3.000 mm
Interface card	Interface card mounted in plastic MCC combi box
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
MP Switch Window	Side element with cutout and transparent cover for visual inspection of the limit switch
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Warranty	1 Year
Dimension packing 1 LxWxH	3000X480X400
Dimension packing 2 LxWxH	800X600X370

20 AD_RP300 ASSA ABLOY RP300 2023-01-24 1.000 ST 3,850.00 3,850.00

Serien-Nr. 2620013105

Door type	High-speed roller door RapidProtect 300
Daylight width	2.500 mm
Daylight height	2.400 mm
Door control system	MCC (7110)
MCC(7110) type	Standard, wth combibox mp plas
Max. Opening Speed	2,3 m/s
Max. Closing Speed	1,7 m/s
Control box position	Mounted next to the drive unit
Control system position	Right
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Pre running photocell at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Grey, similar to RAL 7001
Silicone free	Silicone free
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
MCC display type	Prepared for display
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Motor cable length	1.000 mm
Mains connection cable length	3.000 mm
Combibox cable length	3.000 mm
Interface card	Interface card mounted in plastic MCC combi box

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: CZ 682 534 558
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Sven J. Lars Ynner
Marina Lindholm

Pos. item	Produkt Product	Beschreibung Description	Versanddatum Ship date	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
MP Switch Window	Side element with cutout and transparent cover for visual inspection of the limit switch
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Warranty	1 Year
Dimension packing 1 LxWxH	3000X480X400
Dimension packing 2 LxWxH	800X600X370

30 AD_RP300 ASSA ABLOY RP300 2023-02-17 1.000 ST 3,850.00 3,850.00

Serien-Nr. 2620013106

Door type	High-speed roller door RapidProtect 300
Daylight width	2.500 mm
Daylight height	2.400 mm
Door control system	MCC (7110)
MCC(7110) type	Standard, wth combibox mp plas
Max. Opening Speed	2,3 m/s
Max. Closing Speed	1,7 m/s
Control box position	Mounted next to the drive unit
Control system position	Right
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Pre running photocell at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Grey, similar to RAL 7001
Silicone free	Silicone free
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
MCC display type	Prepared for display
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Motor cable length	1.000 mm
Mains connection cable length	3.000 mm
Combibox cable length	3.000 mm
Interface card	Interface card mounted in plastic MCC combi box
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
MP Switch Window	Side element with cutout and transparent cover for visual inspection of the limit switch
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: CZ 682 534 558
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Sven J. Lars Ynner
Marina Lindholm

Pos. item	Produkt Product	Beschreibung Description	Versanddatum Ship date	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

CE - Sign	Yes
Warranty	1 Year
Dimension packing 1 LxWxH	3000X480X400
Dimension packing 2 LxWxH	800X600X370

40 AD_RP300 ASSA ABLOY RP300 2023-02-17 1.000 ST 3,850.00 3,850.00

Serien-Nr. 2620013107

Door type	High-speed roller door RapidProtect 300
Daylight width	2.500 mm
Daylight height	2.400 mm
Door control system	MCC (7110)
MCC(7110) type	Standard, wth combibox mp plas
Max. Opening Speed	2,3 m/s
Max. Closing Speed	1,7 m/s
Control box position	Mounted next to the drive unit
Control system position	Right
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Pre running photocell at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Grey, similar to RAL 7001
Silicone free	Silicone free
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
MCC display type	Prepared for display
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Motor cable length	1.000 mm
Mains connection cable length	3.000 mm
Combibox cable length	3.000 mm
Interface card	Interface card mounted in plastic MCC combi box
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
MP Switch Window	Side element with cutout and transparent cover for visual inspection of the limit switch
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Warranty	1 Year
Dimension packing 1 LxWxH	3000X480X400
Dimension packing 2 LxWxH	800X600X370

50 AD_RP300 ASSA ABLOY RP300 2023-02-16 1.000 ST 3,850.00 3,850.00

Serien-Nr. 2620013108

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: CZ 682 534 558
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Sven J. Lars Ynner
Marina Lindholm

Pos. item	Produkt Product	Beschreibung Description	Versanddatum Ship date	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

Door type	High-speed roller door RapidProtect 300
Daylight width	2.500 mm
Daylight height	2.400 mm
Door control system	MCC (7110)
MCC(7110) type	Standard, wth combibox mp plas
Max. Opening Speed	2,3 m/s
Max. Closing Speed	1,7 m/s
Control box position	Mounted next to the drive unit
Control system position	Right
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Pre running photocell at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Grey, similar to RAL 7001
Silicone free	Silicone free
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
MCC display type	Prepared for display
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Motor cable length	1.000 mm
Mains connection cable length	3.000 mm
Combibox cable length	3.000 mm
Interface card	Interface card mounted in plastic MCC combi box
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
MP Switch Window	Side element with cutout and transparent cover for visual inspection of the limit switch
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Warranty	1 Year
Dimension packing 1 LxWxH	3000X480X400
Dimension packing 2 LxWxH	800X600X370

60 AD_RP300 ASSA ABLOY RP300 2023-02-16 1.000 ST 3,850.00 3,850.00

Serien-Nr. 2620013109

Door type	High-speed roller door RapidProtect 300
Daylight width	2.500 mm
Daylight height	2.400 mm
Door control system	MCC (7110)
MCC(7110) type	Standard, wth combibox mp plas
Max. Opening Speed	2,3 m/s
Max. Closing Speed	1,7 m/s
Control box position	Mounted next to the drive unit

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: CZ 682 534 558
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Sven J. Lars Ynner
Marina Lindholm

Pos.	Produkt	Beschreibung	Versanddatum	Anzahl	Einheit	Preis/Einh.	Preis
item	Product	Description	Ship date	QTY	Unit	Price/Unit	Price

Control system position	Right
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Pre running photocell at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Grey, similar to RAL 7001
Silicone free	Silicone free
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
MCC display type	Prepared for display
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Motor cable length	1.000 mm
Mains connection cable length	3.000 mm
Combibox cable length	3.000 mm
Interface card	Interface card mounted in plastic MCC combi box
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
MP Switch Window	Side element with cutout and transparent cover for visual inspection of the limit switch
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Warranty	1 Year
Dimension packing 1 LxWxH	3000X480X400
Dimension packing 2 LxWxH	800X600X370

70 AD_RP300 ASSA ABLOY RP300 2023-02-16 1.000 ST 3,850.00 3,850.00

Serien-Nr. 2620013110

Door type	High-speed roller door RapidProtect 300
Daylight width	2.500 mm
Daylight height	2.400 mm
Door control system	MCC (7110)
MCC(7110) type	Standard, wth combibox mp plas
Max. Opening Speed	2,3 m/s
Max. Closing Speed	1,7 m/s
Control box position	Mounted next to the drive unit
Control system position	Right
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Pre running photocell at the bottom profile
Photocell	With photocell

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: CZ 682 534 558
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Sven J. Lars Ynner
Marina Lindholm

Pos.	Produkt	Beschreibung	Versanddatum	Anzahl	Einheit	Preis/Einh.	Preis
item	Product	Description	Ship date	QTY	Unit	Price/Unit	Price

Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Grey, similar to RAL 7001
Silicone free	Silicone free
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
MCC display type	Prepared for display
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Motor cable length	1.000 mm
Mains connection cable length	3.000 mm
Combibox cable length	3.000 mm
Interface card	Interface card mounted in plastic MCC combi box
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
MP Switch Window	Side element with cutout and transparent cover for visual inspection of the limit switch
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Warranty	1 Year
Dimension packing 1 LxWxH	3000X480X400
Dimension packing 2 LxWxH	800X600X370

80 **AD_RP300** **ASSA ABLOY RP300** **2023-02-15** **1.000** **ST** **3,850.00** **3,850.00**

Serien-Nr. 2620013111

Door type	High-speed roller door RapidProtect 300
Daylight width	2.500 mm
Daylight height	2.400 mm
Door control system	MCC (7110)
MCC(7110) type	Standard, wth combibox mp plas
Max. Opening Speed	2,3 m/s
Max. Closing Speed	1,7 m/s
Control box position	Mounted next to the drive unit
Control system position	Right
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Pre running photocell at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Grey, similar to RAL 7001
Silicone free	Silicone free
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: CZ 682 534 558
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Sven J. Lars Ynner
Marina Lindholm

Pos.	Produkt	Beschreibung	Versanddatum	Anzahl	Einheit	Preis/Einh.	Preis
item	Product	Description	Ship date	QTY	Unit	Price/Unit	Price

MCC display type	Prepared for display
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Motor cable length	1.000 mm
Mains connection cable length	3.000 mm
Combibox cable length	3.000 mm
Interface card	Interface card mounted in plastic MCC combi box
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
MP Switch Window	Side element with cutout and transparent cover for visual inspection of the limit switch
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Warranty	1 Year
Dimension packing 1 LxWxH	3000X480X400
Dimension packing 2 LxWxH	800X600X370

90 AD_RP300 ASSA ABLOY RP300 2023-02-17 1.000 ST 3,850.00 3,850.00

Serien-Nr. 2620013112

Door type	High-speed roller door RapidProtect 300
Daylight width	2.500 mm
Daylight height	2.400 mm
Door control system	MCC (7110)
MCC(7110) type	Standard, wth combibox mp plas
Max. Opening Speed	2,3 m/s
Max. Closing Speed	1,7 m/s
Control box position	Mounted next to the drive unit
Control system position	Right
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Pre running photocell at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Grey, similar to RAL 7001
Silicone free	Silicone free
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
MCC display type	Prepared for display
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Motor cable length	1.000 mm
Mains connection cable length	3.000 mm
Combibox cable length	3.000 mm
Interface card	Interface card mounted in plastic MCC combi box

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: CZ 682 534 558
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Sven J. Lars Ynner
Marina Lindholm

Pos. item	Produkt Product	Beschreibung Description	Versanddatum Ship date	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
MP Switch Window	Side element with cutout and transparent cover for visual inspection of the limit switch
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Warranty	1 Year
Dimension packing 1 LxWxH	3000X480X400
Dimension packing 2 LxWxH	800X600X370

100 AD_RP300 ASSA ABLOY RP300 2023-01-24 1.000 ST 3,850.00 3,850.00

Serien-Nr. 2620013113

Door type	High-speed roller door RapidProtect 300
Daylight width	2.500 mm
Daylight height	2.400 mm
Door control system	MCC (7110)
MCC(7110) type	Standard, wth combibox mp plas
Max. Opening Speed	2,3 m/s
Max. Closing Speed	1,7 m/s
Control box position	Mounted next to the drive unit
Control system position	Right
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Pre running photocell at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Grey, similar to RAL 7001
Silicone free	Silicone free
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
MCC display type	Prepared for display
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Motor cable length	1.000 mm
Mains connection cable length	3.000 mm
Combibox cable length	3.000 mm
Interface card	Interface card mounted in plastic MCC combi box
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
MP Switch Window	Side element with cutout and transparent cover for visual inspection of the limit switch
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: CZ 682 534 558
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Sven J. Lars Ynner
Marina Lindholm

Pos. item	Produkt Product	Beschreibung Description	Versanddatum Ship date	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

CE - Sign	Yes
Warranty	1 Year
Dimension packing 1 LxWxH	3000X480X400
Dimension packing 2 LxWxH	800X600X370

110 AD_RP300 ASSA ABLOY RP300 2023-02-21 1.000 ST 3,750.00 3,750.00

Serien-Nr. 2620013114

Door type	High-speed roller door RapidProtect 300
Daylight width	2.000 mm
Daylight height	2.400 mm
Door control system	MCC (7110)
MCC(7110) type	Standard, wth combibox mp plas
Max. Opening Speed	2,3 m/s
Max. Closing Speed	1,7 m/s
Control box position	Mounted next to the drive unit
Control system position	Right
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Pre running photocell at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Grey, similar to RAL 7001
Silicone free	Silicone free
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
MCC display type	Prepared for display
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Motor cable length	1.000 mm
Mains connection cable length	3.000 mm
Combibox cable length	3.000 mm
Interface card	Interface card mounted in plastic MCC combi box
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
MP Switch Window	Side element with cutout and transparent cover for visual inspection of the limit switch
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Warranty	1 Year
Dimension packing 1 LxWxH	2900X480X400
Dimension packing 2 LxWxH	800X600X370

120 AD_RP300 ASSA ABLOY RP300 2023-02-20 1.000 ST 3,750.00 3,750.00

Serien-Nr. 2620013115

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: CZ 682 534 558
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Sven J. Lars Ynner
Marina Lindholm

Pos.	Produkt	Beschreibung	Versanddatum	Anzahl	Einheit	Preis/Einh.	Preis
item	Product	Description	Ship date	QTY	Unit	Price/Unit	Price

Door type	High-speed roller door RapidProtect 300
Daylight width	2.000 mm
Daylight height	2.400 mm
Door control system	MCC (7110)
MCC(7110) type	Standard, wth combibox mp plas
Max. Opening Speed	2,3 m/s
Max. Closing Speed	1,7 m/s
Control box position	Mounted next to the drive unit
Control system position	Right
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Pre running photocell at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Grey, similar to RAL 7001
Silicone free	Silicone free
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
MCC display type	Prepared for display
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Motor cable length	1.000 mm
Mains connection cable length	3.000 mm
Combibox cable length	3.000 mm
Interface card	Interface card mounted in plastic MCC combi box
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
MP Switch Window	Side element with cutout and transparent cover for visual inspection of the limit switch
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Warranty	1 Year
Dimension packing 1 LxWxH	2900X480X400
Dimension packing 2 LxWxH	800X600X370

130 AD_RP300 ASSA ABLOY RP300 2023-02-20 1.000 ST 3,750.00 3,750.00

Serien-Nr. 2620013116

Door type	High-speed roller door RapidProtect 300
Daylight width	2.000 mm
Daylight height	2.400 mm
Door control system	MCC (7110)
MCC(7110) type	Standard, wth combibox mp plas
Max. Opening Speed	2,3 m/s
Max. Closing Speed	1,7 m/s
Control box position	Mounted next to the drive unit

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: CZ 682 534 558
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Sven J. Lars Ynner
Marina Lindholm

Pos.	Produkt	Beschreibung	Versanddatum	Anzahl	Einheit	Preis/Einh.	Preis
item	Product	Description	Ship date	QTY	Unit	Price/Unit	Price

Control system position	Right
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Pre running photocell at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Grey, similar to RAL 7001
Silicone free	Silicone free
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
MCC display type	Prepared for display
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Motor cable length	1.000 mm
Mains connection cable length	3.000 mm
Combibox cable length	3.000 mm
Interface card	Interface card mounted in plastic MCC combi box
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
MP Switch Window	Side element with cutout and transparent cover for visual inspection of the limit switch
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Warranty	1 Year
Dimension packing 1 LxWxH	2900X480X400
Dimension packing 2 LxWxH	800X600X370

140 AD_RP300 ASSA ABLOY RP300 2023-02-20 1.000 ST 3,750.00 3,750.00

Serien-Nr. 2620013117

Door type	High-speed roller door RapidProtect 300
Daylight width	2.000 mm
Daylight height	2.400 mm
Door control system	MCC (7110)
MCC(7110) type	Standard, wth combibox mp plas
Max. Opening Speed	2,3 m/s
Max. Closing Speed	1,7 m/s
Control box position	Mounted next to the drive unit
Control system position	Right
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Pre running photocell at the bottom profile
Photocell	With photocell

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: CZ 682 534 558
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Sven J. Lars Ynner
Marina Lindholm

Pos.	Produkt	Beschreibung	Versanddatum	Anzahl	Einheit	Preis/Einh.	Preis
item	Product	Description	Ship date	QTY	Unit	Price/Unit	Price

Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Grey, similar to RAL 7001
Silicone free	Silicone free
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
MCC display type	Prepared for display
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Motor cable length	1.000 mm
Mains connection cable length	3.000 mm
Combibox cable length	3.000 mm
Interface card	Interface card mounted in plastic MCC combi box
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
MP Switch Window	Side element with cutout and transparent cover for visual inspection of the limit switch
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Warranty	1 Year
Dimension packing 1 LxWxH	2900X480X400
Dimension packing 2 LxWxH	800X600X370

150 AD_RP300 ASSA ABLOY RP300 2023-02-20 1.000 ST 3,750.00 3,750.00

Serien-Nr. 2620013118

Door type	High-speed roller door RapidProtect 300
Daylight width	2.000 mm
Daylight height	2.400 mm
Door control system	MCC (7110)
MCC(7110) type	Standard, wth combibox mp plas
Max. Opening Speed	2,3 m/s
Max. Closing Speed	1,7 m/s
Control box position	Mounted next to the drive unit
Control system position	Right
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Pre running photocell at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Grey, similar to RAL 7001
Silicone free	Silicone free
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: CZ 682 534 558
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Sven J. Lars Ynner
Marina Lindholm

Pos.	Produkt	Beschreibung	Versanddatum	Anzahl	Einheit	Preis/Einh.	Preis
item	Product	Description	Ship date	QTY	Unit	Price/Unit	Price

MCC display type	Prepared for display
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Motor cable length	1.000 mm
Mains connection cable length	3.000 mm
Combibox cable length	3.000 mm
Interface card	Interface card mounted in plastic MCC combi box
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
MP Switch Window	Side element with cutout and transparent cover for visual inspection of the limit switch
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Warranty	1 Year
Dimension packing 1 LxWxH	2900X480X400
Dimension packing 2 LxWxH	800X600X370

160 AD_RP300 ASSA ABLOY RP300 2023-01-24 1.000 ST 3,750.00 3,750.00

Serien-Nr. 2620013119

Door type	High-speed roller door RapidProtect 300
Daylight width	2.000 mm
Daylight height	2.400 mm
Door control system	MCC (7110)
MCC(7110) type	Standard, wth combibox mp plas
Max. Opening Speed	2,3 m/s
Max. Closing Speed	1,7 m/s
Control box position	Mounted next to the drive unit
Control system position	Right
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Pre running photocell at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Grey, similar to RAL 7001
Silicone free	Silicone free
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
MCC display type	Prepared for display
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Motor cable length	1.000 mm
Mains connection cable length	3.000 mm
Combibox cable length	3.000 mm
Interface card	Interface card mounted in plastic MCC combi box

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: CZ 682 534 558
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Sven J. Lars Ynner
Marina Lindholm

Pos. item	Produkt Product	Beschreibung Description	Versanddatum Ship date	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
MP Switch Window	Side element with cutout and transparent cover for visual inspection of the limit switch
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Warranty	1 Year
Dimension packing 1 LxWxH	2900X480X400
Dimension packing 2 LxWxH	800X600X370

170 AD_RP2000 ASSA ABLOY RP2000 2023-01-23 1.000 ST 7,530.00 7,530.00

Serien-Nr. 2500002716

Door type	High speed roller door RapidProtect 2000
Daylight width	2.000 mm
Daylight height	2.400 mm
Door control system	MCC (7110)
MCC(7110) type	Standard, wth combibox mpsteel
Max. Opening Speed	2,0 m/s
Max. Closing Speed	1,2 m/s
Control box position	Mounted next to the drive unit
Motor Position	Right
Wind class	3
Side frame version	Galvanised steel
Safety contact edge	Pre running photocell at the bottom profile
Manual egress (brake release)	Pull rope on front side.
Door curtain	Door curtain made of aluminium lamellas, version laser protection
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
MCC display type	Display delivered separately, not mounted
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Motor cable length	1.000 mm
Mains connection cable length	3.000 mm
Combibox cable length	3.000 mm
Interface card	Interface card mounted in MCC combi box made of sheet steel
Safety limit switch (MP)	Schmersal on 2 sides with relay for cat. 4
Photocell	With photocell
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Warranty	1 Year
Dimension packing 1 LxWxH	2800X620X800
Dimension packing 2 LxWxH	2900X650X600

Warenwert/Value of goods 68,530.00

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: CZ 682 534 558
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Sven J. Lars Ynner
Marina Lindholm

ASSA ABLOY

Summe/Total	**EUR**	**68,530.00**

Wir danken für Ihren Auftrag Thank you for the order
Mit freundlichen Grüßen Best regards
Albany Door Systems GmbH

(Automatisch erstellt, daher ohne Unterschrift gültig
Written automatically, valid without signature)

Dem Auftrag liegen unsere allgemeinen, zur Zeit gültigen Verkaufsbedingungen zugrunde, die auch für alle weiteren Verträge Gültigkeit haben.
The order is based on our current general terms of sales, which will as well be applicable for all further contracts.

Die gesetzlichen durch die DSGVO geforderten Informationen zum Umgang mit Ihren personenbezogenen Daten erhalten Sie unter dem folgenden Link: https://goo.gl/qGzSw5

Sollten Sie keinen Zugang zum Internet haben, senden wir Ihnen gerne die Informationen postalisch zu. Bitte sprechen Sie uns ggf. unter Telefon: 02941/766-622 darauf an.

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: CZ 682 534 558
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Sven J. Lars Ynner
Marina Lindholm