NIHVA Technologies Pvt. Ltd.
187, G-Block, 1st Floor, Above Renault Showroom, Thermax chowk, MIDC, Chinchwad.
Pune – 411019

An ISO 9001:2008 Certified Company

GST Pune :

Technical Specification :

Motorized Single Leaf Sliding Gate

Sr .No.	Specification	Motorized Single Leaf Sliding Gate
1	Door type	Motorized Sliding Gate
2	Opening Direction	Horizontal - from left to right or reverse
3	Mounting Location area	Inside area
4	Design Pattern	Standard Tubular Design Pattern
5	Outer Tube	72 x 72 x 3.2mm MS SQ. TUBE
6	For Post	72 x 72 x 3.2mm MS SQ. TUBE
7	Innear Tube	38x38x3.20mm/40x40x3.2 MS SQ. TUBE
8	Gap Between Tubes	125mm
9	Bottom Rail on ground	dia 20 mm round bright bar with heavy duty support ISMB 100 X 50 Beams
10	Bottom Rollers	Heavy Duty Bottom Wheel With both side Bearings (chorme plated)
11	Guide Rollers supporter during Gate movement	Nylon Rollers with Bearings both side mounted on column for support smooth movement of gate
12	Painting	2 Coats of EPOXY polyamide based enamel finish of approved colour
13	El motor make	BFT – Italy (100% imported)
14	Emergency Operation	Manual after turn the switch
15	Operating Switch	Push Button from inside
16	Safety	Photocells, Flashing Light

Wicket Gate

Sr .No.	Specification	Wicket Gate
1	Door type	Manual Single Leaf Wicket Gate
2	Size considered	Clear opening - (W)1200 mm x (H)1800 mm
3	Mounting Location area	Inside area
4	Design Pattern	Standard Tubular Design Pattern
5	Outer Frame Tube Sizes	80 x 80 x 3.2 mm
6	Internal Vertical Tube Sizes	40 x 40 x 2 mm
7	Gap Between Tubes	100 mm C/C
8	Painting	2 Coats of EPOXY polyamide based enamel finish of approved Colour
9	Operation	Manually Opening

NIHVA Technologies Pvt. Ltd.
187, G-Block, 1st Floor, Above Renault Showroom, Thermax chowk, MIDC, Chinchwad.
Pune – 411019

An ISO 9001:2008 Certified Company

GST Pune :

Technical Specification :

Boom Barrier

Electro Mechanical Barrier with 24 V power supply for useful passage up to 8 m / 6 m and opening time 8 / 6 sec.

Impact reaction via Control unit with U-Link slot, display and receiver in head. RAL 7015 grey colour.

Sr .No.	Specification	Wicket Gate
1	Boom length:	8m (MICHELANGELO BT A 80) / 5-6m (MICHELANGELO BT A 60)
2	Power supply:	230V±10% 50/60Hz(*)
3	Power absorbed:	300W
4	Internal lubrication:	permanent grease
5	Max torque:	600 Nm
6	Opening time:	8s (8m)
7	Impact reaction:	encoder
8	Manual mechanical release:	key
9	Limit devices:	electrical incorporated and electronically adjustable
10	Type of use	continuous operation
11	Working temperature:	from -20°C to +55°C
12	Degree of protection:	IP 54
13	Operator weight (without boom):	68 Kg (MICHELANGELO BT A 80)
14	Mains/low voltage insulation:	> 2MOhm 500V
15	Dielectric strength:	mains/low voltage 3750V~ for 1 minute
16	Motor output current:	30A max (MICHELANGELO BT A 80)
17	Supply to accessories:	24V~ (180 mA max absorption)
18	Barrie-open warning light:	24V~ 3W max
19	Blinker:	24V~ 25W max