# PRODUCT SPECIFICATION
## ASSA ABLOY RR300
***Vertical rapid roll door for interior or limited exterior use***

## Standard equipment

| | |
|---|---|
| Dimensions: | |
| Daylight width (DW): | 1000 - 3500 mm<br>1000 - 4000 mm with MCC |
| Daylight height (DH): | 1000 - 3500 mm<br>1000 - 4200 mm with MCC |
| Area: | 1.0 – 16.8 $m^2$ |
| Wind class: | Class 1 according to EN 12424 |
| Resistance to water | |
| penetration: | - |
| Air permeability: | - |
| Heat transition coefficient (U- value) | - |
| Noise emission: | < 70 dB A |
| Operating temperature: | Standard +10 °C - +40 °C<br>Extended 0°C - +60 °C (see “Allowed operating temperature range for ASSA ABLOY doors”) |
| Door blade: | Clear PVC (1,4 mm) with vertical colored stripes in PVC (0,5 mm)<br>Daylight width: 700 - 1270 mm: no vertical middle stripe<br>Daylight width: 1271 - 2400 mm: 1 vertical middle stripe<br>Daylight width: 2401 - 3500 mm: 2 vertical middle stripes<br>Daylight width: >3500 mm: 3 vertical middle stripes<br>Colors for vertical and horizontal stripes (not silicon free, glossy, according to RAL):<br>Blue (RAL 5002), Red (RAL 3002)<br>(If not specified: Blue)<br>In cold positions or in positions with pressure differences should RollTex Plus be used |
| Side guides: | Galvanized sheet metal<br>Stainless Steel |
| Wind reinforcement: | Windtabs mounted at door blade sides |
| Top roll cover: | Galvanized sheet metal<br>Stainless Steel 30°<br>Stainless Steel<br>Required if DH ≤ 2500mm |
| Motor cover: | Plastic grey RAL 7040<br>Steel, powder coated 9006<br>Stainless Steel 30°<br>Required if DH ≤ 2500 mm |

**Product Development**
ASSA ABLOY Entrance Systems
Am Mondschein 25 • D-59557 Lippstadt • Germany
Tel: +49-2941-766-0 • Fax: +49-2941-766-136

**Approved 2019-06-05**

| | |
|---|---|
| Toproll: | Aluminum ∅ 115 mm with galvanized shafts<br>Aluminum ∅ 115 mm with stainless steel plates and shafts<br>Stainless steel ∅ 115 mm, complete stainless steel |
| Bottom beam: | Anodized aluminum without break-away<br>Stainless Steel without break-away<br>Electrical self-testing safety edge inside rubber profile, coily cable |
| Safety device: | Photocell in door line |
| Drive unit: | GfA gear motor 0.75 kW, with power-off brake, integrated geared limit switches.<br>Available for right and left side. |
| Control box: | ACS50 Electronic control system with mini contactors incl. main switch<br>Opening/closing speed: max. 1.0/1.0 m/s |
| Power supply: | 3/(N)/PE 230V (±10%), 50Hz, 10A fuse internal<br>3/(N)/PE 380V (-5%/+10%), 50Hz, 6.3A fuse internal<br>3/(N)/PE 400V (±10%), 50Hz, 6.3A fuse internal<br>3/(N)/PE 415V (-10%/+5%), 50Hz, 6.3A fuse internal |
| Emergency opening: | In the event of a power failure, the door can be opened manually by means of a crank |

## Optional equipment

| | |
|---|---|
| Door blade alternative 1: | RollTex Plus with/without windows. Not silicone free, optional silicone free.<br>Colours: Orange (RAL2009), Blue (RAL5002) or Grey (RAL7001) |
| Door blade alternative 2: | RollTex Original with/without windows. Not silicone free, optional silicone free.<br>Colours: Orange (RAL2009), Blue (RAL5002) or Grey (RAL7001, also paintable on request) |
| Door blade alternative 3: | Flame retardant door blade 1,9mm according to ISO 340 without vision panel or windows. Colour: Grey (RAL7045) |
| Door blade alternative 4: | NomaTex with/without windows. With/without integrated vision panel (not replaceable), observe: visible width are DW-290 mm but never more than 3110 mm. Height of vision panel max.750 mm. Min. dimension from vision panel/Window level to bottom >=310 mm.<br>Not silicone free, optional silicone free<br>Colors: |

| | | |
|---|---|---|
| E8/2 V1/V2 H Orange | RAL2009 | Antistatic, R < $3x10^8$ Ω |
| E8/2 V1/V2 H Blue | RAL5005 | Antistatic, R < $3x10^8$ Ω |
| E8/2 V1/V1 Grey* | RAL 7038 | Antistatic, R < $3x10^8$ Ω |
| E8/2 V1/V1 Yellow* | RAL1023 | |
| E8/2 V1/V1 Red | RAL 3000 | |

H= Smooth surface front side (top roll side)
*Conform to requirements of FD (U.S. Food and Drug Administration) concerning the extraction behavior

**Product Development**
ASSA ABLOY Entrance Systems
Am Mondschein 25 • D-59557 Lippstadt • Germany
Tel: +49-2941-766-0 • Fax: +49-2941-766-136

| | |
|---|---|
| Door blade alternative 5: | Top 1.3 with/without vision panel, height of vision panel max. 560 mm.<br>Min. dimension from vision panel to bottom >=510 mm<br>Colors: Blue (RAL5010), Grey (RAL7035), Red (RAL3002)<br>DW ≤ 3500 mm, DH ≤ 3500 mm |
| Door blade alternative 6: | Clear PVC (1.4 mm) with vertical colored stripes in PVC (0.5 mm) (not silicon free, glossy, according to RAL):<br>Beige (RAL 1014), Yellow (RAL 1021), Orange (RAL 2011),<br>Green (RAL 6018), White (RAL 9016), Grey (RAL 7035) |
| Door blade alternative 7: | Clear PVC (1.4 mm) with vertical colored stripes in PVC (0.5 mm) (silicon free, matt, according to RAL):<br>Blue (RAL 5010), Red (RAL 3002), Yellow (RAL 1021), Orange (RAL 2011),<br>White (RAL 9010), Grey (RAL 7037), Black (RAL 9005) |
| Windows:<br>(only for Rolltex and Nomatex) | vertical 500 x 700 mm (by DH>=1100 mm):<br>Daylight width: 800 - 1700 mm: max. 1 window<br>Daylight width: 1701 - 2400 mm: max. 2 windows<br>Daylight width: 2401 - 3100 mm: max. 3 windows<br>Daylight width: >3100 mm: max. 4 windows<br>horizontal 700 x 500 mm:<br>Daylight width: 1000 - 2100 mm: max. 1 window<br>Daylight width: 2101 - 3000 mm: max. 2 windows<br>Daylight width: >3000 mm: max. 3 windows<br>Window frame color in black or yellow<br>Min. dimension from Window level to bottom >=310 mm |
| Side frames: | Available without bottom plates |
| LED traffic light strip: | Mounting on external anodized aluminum bracket, 2 or 4 stripes selectable |
| Bottom beam: | Elongated sealing lip; extended by 50, 100 or 150 mm (not for FlexEdge) |
| Bottom beam:<br>Alternative 1 | Break-away system for bottom beam with electrical safety edge<br>Door stops automatically when hit, manual reset<br>can be used with any of the door blade alternatives<br>DW ≥ 1300 mm, DH ≥ 1000 mm<br>Not available in combination without control. |
| Bottom beam:<br>Alternative 2 | FlexEdge – soft bottom profile without aluminum extrusion and without coiled cord (wireless system); only for interior use without wind load<br>Break-away system for bottom beam with electrical safety edge<br>Door stops automatically when hit, manual reset<br>can be used with any of the door blade alternatives<br>DW ≥ 1300 mm, DH ≥ 1000 mm<br>Can be used with all control systems, not available for doors “without control” |
| Control box: | MCC Frequency converter control system incl. display<br>Opening/closing speed: max. 2.0 / 1.0 m/s<br>Display at side frame only possible if DH ≥ 2330 mm |

**Product Development**
ASSA ABLOY Entrance Systems
Am Mondschein 25 • D-59557 Lippstadt • Germany
Tel: +49-2941-766-0 • Fax: +49-2941-766-136

| | |
|---|---|
| Power supply MCC: | 3/(N)/PE 380V (±10%), 50/60Hz<br>3/(N)/PE 400V (±10%), 50/60Hz<br>3/(N)/PE 415V (±10%), 50/60Hz<br>3/(N)/PE 440V (±10%), 50/60Hz<br>3/(N)/PE 460V (±10%), 50/60Hz<br>3/(N)/PE 480V (-10%/+5%), 50/60Hz |
| Power supply MCC: | with transformer:<br>3/(N)/PE 220V (±10%), 50/60Hz<br>3/(N)/PE 230V (±10%), 50/60Hz<br>3/(N)/PE 500V (±10%), 50/60Hz |
| Power supply: MCC | single phase mains power supply<br>1/N/PE 220V, 50/60Hz (±10%)<br>1/N/PE 230V, 50/60Hz (±10%)<br>opening and closing speed is reduced about 25 % |
| Power supply ACS50: | with transformer:<br>3/(N)/PE 440V (±10%), 50Hz, 6.3A fuse internal<br>3/(N)/PE 480V (±10%), 50Hz, 6.3A fuse internal<br>3/(N)/PE 500V (±10%), 50Hz, 6.3A fuse internal |
| Without control system: | Specification drive and cable same as ACS50, Crash system is not available. You will get only a declaration of incorporation instead of a CE-Declaration. |
| Top roll sealing: | With sealing added to distance profile to cover space between the top roll and the wall. |
| Heater at drive unit: | 380V-480V, 50W at 400V, controlled heater, no neutral wire needed. |
| Hand chain operator: | KNH Hand chain operator. Easy, manually emergency opening by power failure. Combination with Motor cover is not possible. |

## Legend:

| | | |
|---|---|---|
| 2008-03-17 | | Added legend<br><br>Added motor cover steel powder coated RAL9006<br>Plastic cover grey: RAL 7040 added<br>If display is at side frame the minimum value for daylight height is 2330 (was 2180 before). |
| 2008-11-04 | | Added Door blade alternative clear PVC with colored stripes in PVC (silicon free) |
| 2010-02-24 | stf | Resistance to water penetration, air permeability, heat transition coefficient added |
| 2010-09-21 | pc | RollTex Original Grey - paintable on request added. Min. Door height for vertical Window, min. dimensions from vision panel/Window level to bottom added. Lengths of elongated sealing lip added. Power supply: MCC without internal Fuse. |

**Product Development**
ASSA ABLOY Entrance Systems
Am Mondschein 25 • D-59557 Lippstadt • Germany
Tel: +49-2941-766-0 • Fax: +49-2941-766-136

| | | |
|---|---|---|
| 2011-01-31 | wue | Added details of control box ACS25, removed Aluminum side guide, removed Aluminum top roll cover. |
| 2011-05-10 | wue | Added option heater at drive unit. |
| 2012-12-04 | stf | max. size changed to 4000 x 4200 mm, limitations for control system and curtains |
| 2012-05-07 | siw | FlexEdge bottom profile as an option added |
| 2012-06-27 | stf | ASSA ABLOY Logo integrated |
| | wue | Added option without bottom plates |
| 2013-02-13 | stf | single phase mains power supply, LED traffic light strip and operating temperature added |
| 2014-03-22 | pc | Option Hand chain operator added. |
| 2014-03-22 | ruf | MCS added, new drives added. |
| 2014-10-17 | ruf | Add limitation of the FlexEdge. |
| 2014-12-08 | Cic | Remove limitation MCS with FlexEdge. |
| 2015-01-07 | Cic | Limitation of dimension with MCS-R and MCS-FC added. MCC voltage 460V added. |
| 2015-07-31 | wue | Curtains RollTex Plus, RollTex Original and Nomatex: Added „Not silicone free, optional silicone free“. |
| 2015-11-05 | wue | Changed name from MCS-R to MCS-R1 and from MCS-FC to MCS-F1. Deleted additional limit for maximum door size for MCS-F1. Changed max. opening-/closing speed MCS-F1 (was MCS-FC). |
| 2016-03-14 | wue | Added Bottom beam Alternative 3. |
| 2016-11-25 | wue | Changed opening speed MCS-F1 from 1,7m/s to 1,5m/s. |
| 2017-11-22 | wue | Remove Door blade alternative Top 0,8 with/without vision panel. |
| 2018-10-26 | pc | Albany in ASSA ABLOY, RR 300I/S in ASSA ABLOY RR300 changed. Without control system: You will get only a declaration of incorporation instead of a CE-Declaration; added. |
| 2019-06-05 | wue | Remove control systems MCS-R1 and MCS-F1,<br>Door blade alternative 4: Remove NA= Non anti-static.<br>Add Antistatic, R < $3x10^8$ Ω for Orange, Blue and Grey.<br>Remove bottom beam Alternative 3: Low Aluminum bottom profile (mini) |

**Product Development**
ASSA ABLOY Entrance Systems
Am Mondschein 25 • D-59557 Lippstadt • Germany
Tel: +49-2941-766-0 • Fax: +49-2941-766-136

**Approved 2019-06-05**