# Albany M Safety

ALBANY
ASSA ABLOY

## Enhance the safety of your high-speed door with a modern safety contact edge





## Albany safety contact edge as a closing edge safety device

Key benefit

Safety

The safety contact edge plays a decisive role in ensuring the safety of a door. It is needed as a closing edge safety device on the main bottom edge.

A poorly functioning and outdated contact strip contains a high risk potential.

People who are hit by apoorly secured moving door blade can suffer serious injury.

With the use of a modern safety contact edge, the consequences of a collision can be considerably reduced.

This is achieved by means of improved sensitivity of the contact element and a higher rubber profile with additional damping properties. These factors play a significant role in the reduction of closing forces.

On older doors we also recommend a retrofit to a modern control system, to comply with the requirements of current safety regulations.

Please get in touch with us for more information.
service.de.albany@assaabloy.com
(here should be the local mail address)

# Product kit for Albany M Safety



## Article number and product description

| Articl no. | Name | Typ | Resistor |
|---|---|---|---|
| D4421RG036 | Rubberprofile with integrated contact strip | RR290 / RR300Plus / RR320 / RR330 / RR390/ RR600 mit SRD / Clean / RP2000 / L / SL / EL-3 | 8,2 kOhm |
| D4421RG037 | Rubberprofile with extended sealing lip and integrated contact strip | | |
| D4421RG043 | Rubberprofile with integrated contact strip | RR3000 / RR350/E | 8,2 kOhm |
| D4421RG044 | Rubberprofile with extended sealing lip and integrated contact strip | | |
| D4421RG048 | Rubberprofile with integrated contact strip | RR330 ACS70 | 8,2 kOhm |
| D8550RG066 | Rubberprofile with integrated contact strip (through) | RR400/E/X2 | 8,2 kOhm |
| D8550RG067 | Rubberprofile with integrated contact strip (end) | RR400/E/X2 | 8,2 kOhm |
| D8550RG068 | Rubberprofile with integrated contact strip (Rebuilding kit from Mayser/Bircher to new edge) | RR420 / 660 / 910 | 8,2 kOhm |
| D8550RG073 | Rubberprofile with integrated contact strip (w.end pieces) | RR300 / Mini / 355 / 392 / 450 / 600 ohne SRD / Food / DiviRoll | 8,2 kOhm |
| D8550RG074 | Rubberprofile with extended sealing lip and integrated contact strip (w. end pieces) | | |

© ASSA ABLOY Entrance Systems AB. All rights reserved.
Technische Änderungen vorbehalten
64 100 351/13/12 EN

ASSA ABLOY Entrance Systems
High Performance Door Solutions
(here should be the local address)

Am Mondschein 25
Tel.: +49 (0) 29 41 / 766-0
Fax.: +49 (0) 29 41 / 766-294
verkauf.de.albany@assaabloy.com
www.assaabloyentrance.com

ASSA ABLOY

ASSA ABLOY, the global leader in door opening solutions