Product:

Dock Levelers

Supply and Installation of NIHVA Make electro Hydraulic Dock leveller of Various Capacity in KG i.e :6000Kg to 5000 kg , For Standard 9000Kg

Platform Width : 2000mm

Platform Length : 2500mm

Lip Width : 2000mm

Lip Length : 400mm

Working Length (Including Lip): 2400mm

Shut Height : 485mm

Working Range UP/Down : (+) 300mm / (-) 150mm

Loading Platform Height from Road : 1250mm

Dock Operation Mode : AC Power Pack Hydraulically Operated

Lip Operation Mode : Hydraulically Operated

Operation Control : Through Panel

Power Pack : Hydraulic

Pump Design Flow (LPM) : 2.5lpm

Pump Type : Gear

Volume of Oil Receiver (Liter): 7

Safety Valve Set Pressure (Kg/Sq. Cm): 120

No. Of Deck Cylinder : 1no / 2nos (optional) **No. Of Lip Cylinder :** 1no

Drive Type : Direct by electric Motor

Motor Ratings HP / Make : 1HP/Crompton

Power Supply : 3 Phase

Maximum Gradient : 1:10

Clear Pit Dimensions (W x L x D) MM: 2030 X 2530 X 485

Service Weight in Kg (Approx.): 900

Colour : Golden Yellow

91 8551091333 ☎ +91 20 66304033

Email: marketing@nihva.com