1. Specification of Telescopic belt conveyor:

Particulars	Description
Material To Be Handle	Boxes/Plastic Jar/Tin Jar
Weight Of The Box/Bags	30 Kg. maximum
Size of Box/Bags	Variable
Temperature	Ambient
Type	Collapsible Boom type hinged Telescopic Belt Conveyor
Design Capacity	50 Kg per meter
Size Of Belt	500 mm Width
Height	1010 mm
Type Of Belt	Oil resistance food grade belt (Forbo make)
Belt Speed	33 m/min (Variable)
Belt direction	Bidirectional
Length Of Conveyor	FIXED : 4000 mm TELESCOPIC : 8200 mm TOTAL : 12200 mm HEIGHT : 1010 mm approx.
Motor Rating	5.0 HP for Belt & 2.0 HP for Boom (to be worked during detailed engineering)
VFD	Suitable for motor rating
Motor make	SEW with encoder
Drive make	Allen Bradely / Siemens
MOC (FRAME):	MS Powder Coated
Rated Voltage	430 V, 50 Hz
Quantity required	12 sets
Delivery	11 weeks from date of order confirmation
Freight	Will be in ATS Account

2. Features of telescopic belt conveyor:

Sl No	Particular's	Description
1	All Pinch points & Moving parts covered.	Yes
2	PLC Considered (SIMATIC S7-1200, CPU 1214C)	Yes
3	Fixed wired pendant.	Yes
4	Emergency Switch.	Yes
5	Telescopic Boom Lockable and Hold to Run Operation.	Yes
6	Anti-Pin Bar Mechanism (if it touches the operator, Telescopic stops there, then starts after resetting from main panel).	Yes
7	All Booms are Covered from Below	Yes
8	Mounting base including castor PU coated wheels	Yes
9	Sensors in the front boom to stop if an operator comes too close to the system.	Yes
10	Belt Damage Protection System.	Yes
11	Brushes at openings from where telescopic booms come out.	Yes
12	Tower Lamp with Hooter to indicate start of conveyor Belt & Boom.	Yes
13	Variable Speed Belt @ 33mtr/min & Variable Boom Speed @ 10 mtr/min.	Yes
14	Sensor to stop conveyors at Loading & Unloading end if operator is not there to pick the product	Yes
15	Hydraulics for tilting mechanism.	Yes

ATS Conveyors India