WORK ORDER

Client:			
Address:			

PO Number:	RBPL/SEM/PO/202207/021	**W. O. No-**	SO/22-23/031
PO Dated :	28-07-2022	**W. O. Date**	30-07-2022
PO Received Date:	30-07-2022	**Sales Co ordinator**	Pradeep Shinde
Ref. Quotation:	SQT.22.23_0042 R2	**Front Sales Person**	YK

Contact Details		**Billing Address:**	**Dispatch Address:**
Contact Person:			
Email ID of contact Person:			
Mobile No:			

A **Technical Terms:**

Sr. No	Description of Goods	Technical Details	UOM	Qty.	Supply Rate	Installation Rate	Total Amount	Dwg. Approval Status
1	NIHVA Make High Speed Door W 6000 mm X H 6000 mm	Sheet 2	Nos	3		Included	-	Pending
2	GI 1 mm - Motorized Single Skin Rolling Shutter - Indirect Drive W 7000 mm X H 7000 mm	Sheet 2	Nos	2		Included	-	Pending
3	GI 1 mm - Motorized Single Skin Rolling Shutter - Indirect Drive W 6000 mm X H 7000 mm	Sheet 2	Nos	2		Included	-	Pending
4	GI 1 mm - Motorized Single Skin Rolling Shutter - Indirect Drive W 5500 mm X H 7000 mm	Sheet 2	No	1		Included	-	Pending
5	GI 1 mm - Motorized Single Skin Rolling Shutter - Indirect Drive W 6000 mm X H 6000 mm	Sheet 2	No	1		Included	-	Pending
6	GI 1 mm Single skin Motorised rolling shutter - Indirect drive Motor with Partly Perforation (1650 mm area) W 4000 mm X H 5000 mm	Sheet 2	No	3		Included	-	Pending
6	GI 1 mm Single skin Motorised rolling shutter - Indirect drive Motor with Partly Perforation (2350 mm area) W 4500 mm X H 7000 mm	Sheet 2	No	1		Included	-	Pending
						Total		-

Non standard items/extra requirement, if any:

B **Commerical Terms:**

1	**Payment Terms:**	20% Advance along with PO , 70% before dispatch & Balance 10% after installations .		
2A	**Delivery Date as per PO:**	7-8 weeks for High Speed Door & 3-4 weeks for Rolling shutter	**2B. Required Delivery Date:**	
3A	**Transportation Scope:**	Extra at actual	**3B. Transportation Charges:**	
4	**P&F Charges:**	NIL		
5A	**Loading Scope:**	NIHVA Scope	**5B. Loading Charges:**	
6A	**Unloading Scope:**	CLIENT Scope	**6B. Unloading Charges:**	
7A	**Lifting Equipments Scope:**	CLIENT Scope	**7B. Available Lifting Equipments:**	
8	**Warranty:**	12 months from the date of supply.		
9A	**Height arrangement Scope:**	CLIENT Scope	**9B. Available Equipments for working at Site:**	
10	**Electricity Supply:**	CLIENT Scope		
11	**GST:**	18% extra		
12A	**Installation Scope:**	NIHVA Scope	**12B. Installation required date:**	
13	**Mode of import:**	NA		
14	**HSS:**	NA		
15	**Documentation Required:**	Standard Handover Documents		
16A	**Total site visits required:**		**16B. Site visit charges:**	

Certified that the above work order finalised in presence of:

GM	AGM	SALES		Operation	PROJECT	DESIGN	Date & Time

GI - Motorized Single Skin Rolling Shutter - Indirect Drive

Sr .No.	Specification	GI Motorized Single Skin Rolling Shutter - Indirect Drive
1	**Description:**	Motorised Rolling Shutter with GI Slats with thickness of 1 mm.
2	**Mounting Location area**	Inside area / Outside area
3	**Mounting Surface**	Side Brackets: Optional = On Concrete /Steel & Side
4	**Curtain Panel**	The panel made of 1.0mm thick GI.
5	**Curtain panel size**	75mm wide
6	**Curtain Profile**	Curved
7	**Bottom Profile**	M. S. Plate 100 mm x 2.5 mm thick with angle stiffener
8	**Side Guide Profile**	M.S." T" Shaped profile 65 mm -150 mm x 3 mm thick.
9	**Roller Shaft**	M.S. Tubular Pipe with Flange & machined shaft at the ends Pipe Dia -100 to 300 mm as per w
10	**Side Brackets**	MS Plate 3 mm to 10 mm thick, as per the opening dimension.
11	**Hood Cover**	Made of GI Sheet Thickness 0.9 mm
12	**Surface finish**	Powder coating of Approved RAL code
13	**Drive Unit & Mounting Type**	Electric Motor - Indirect Mounting - Sprocket chain arrangement – IP54 Protection
14	**Perforation**	1/3 Height on total height of Shutter only for mentioned Sizes as bove
15	**Safety catch**	Consider safety catch for 7000 x 7000 & 6000 x 7000 mm Shutter

NIHVA MAKE - High Speed Door - (European Components)

- Safe & for continous operations
- Smooth & silent opening & closing
- Can be equipped with full vision PVC curtain
- Modular Interchaegable panels permit to replace worn & damged panels

Sr. No	Description	Specifications
1	Use	Internal Door
2	Speed	Inverter Motion system to adjust different speeds, with progressive control of acceleration &
3	Opening speed	upto 3 m/s
4	Closing speed	0.8 m/s
5	Control Panel	4 Push Button operated
6	Security Features	EN 13241-1 Standard
7	Resistance to wind load	EN12424 upto class 1
8	Curtain	Fabric 1mm thick- RAL Colour confirmed by client
9	Guide Material	Aluminum anodised
10	Hood & Motor Cover	Galvanised Steel - Included
11	Operator & Control	CE Certified German Make Motor
12	Connecting Voltage	220V , 1Ph , N
13	Open-Stop-Close Button	Standarad
14	Protection Category	IP 54
15	Power Consumption	0.75 kw Motor
16	Emergency Off Button	Standard
17	Closing Zone Monitoring	Optical Safety edge
18	Safety Device	Photocell
19	Emergency Opening	Crank Handle