RAPIDA DOOR
HIGH SPEED PVC ROLL UP DOOR

High Speed Door for interior & exterior applications



ROBUST AND OPTICAL | TECHNICAL SPECIFICATIONS

NIHVA
NIHVA TECHNOLOGIES PVT. LTD.

- Safe and for continuous operations
- Self-Supporting construction with anti-crash protection system for bottom profile
- Smooth and silent opening and closing
- Can be equipped with full vision PVC curtain
- Modular interchangeable panels permit to replace worn or damaged panels
- Advance and robust control device

Door Type			Roll-up
Use	Internal / External Door		Standard
Door Sizes	Max Width		6000 mm
	Max Height		6000 mm
Speed	Inverter Motion system to adjust different speeds, with progressive control of acceleration & deceleration during braking		
	Opening Speed up to		3,0 m/s
	Closing Speed		0,8 m/s
Security Features	EN 13241-1		Standard
Resistance to Wind Load	EN 12424		up to Class 2
	Aluminum anodized windbars		
Curtain	Fabric	0.9 - 1.5 mm	Standard
	Transparent PVC section	2.0 mm	Standard
Guide Material / Surface	Aluminum Anodized		Standard
	Painting in any RAL color		Optional
	Stainless Steel SS 316 matte finish		Optional
Shaft / Operator Cover	Straight		Optional
Operator and Control (German brand)	Connecting Voltage		220V - 1ph, N
	Open-Stop-Close Button		Standard
	Protection Category (Operator / Control)		IP 54 / IP 65
	Emergency-OFF Button		Standard
	Closing Zone Monitoring	Light Curtain	Optional
		optical safety edge	Standard
	External Route Monitoring	Photocell	Standard
	Door area Monitoring	Radar Presence Detector	Optional
		Induction Loop	Optional
	Electronic Limit Switch		Standard
Emergency Opening	Crank Handle		Standard
	Counterweight system		Optional
	Chain		Optional

Standard Curtain Colours

- Blue Similar to RAL 5010
- Yellow Similar to RAL 1018
- Orange Similar to RAL 2004
- White Similar to RAL 9010
- Red Similar to RAL 3002
- Grey Similar to RAL 7035
- Green Similar to RAL 6005
- Aluminum grey Similar to RAL 9006