Motorized Rolling Sutter

Door type	Motorized Rolling Sutter
Clear Opening	Size: (W) 3000 mm x (H) 3000 mm QTY 2 Size: (W) 3050 mm X (H) 3050 mm QTY 1 Size: (W) 3050 mm X (H) 3600 mm QTY 3 Size: (W) 1800 mm X (H) 1200 mm QTY 1 Size: (W) 2400 mm X (H) 3000 mm QTY 2
Opening Direction	Vertical - from bottom to Top
Mounting Location area	Inside area
Mounting Surface	Side Brackets: Optional = On Concrete /Steel & Side Guides: Optional = On Concrete/Steel / Masonry
Door Material	
Curtain material	GI
Curtain Panel	The panel made of 1.0mm thick CRCA steel
Curtain panel size	75mm wide
Curtain Profile	Corrugation
Slat Thickness	1. mm (As per IS 6248)
Bottom Profile	M. S. Plate 100 mm x 2.5 mm thick with angle stiffener
Side Guide Profile	M.S." U" Shaped profile 100 mm -150 mm x 3 mm thick (as per the opening width dimension)
Roller Shaft	M.S. Tubular Pipe with Flange & machined shaft at the ends Pipe Dia -100 to 300 mm as per w x h
Side Brackets	MS Plate 3 mm to 10 mm thick, as per the opening dimension
Hood Cover	Made of GI Sheet Thickness 0.9 mm with 25x25x3mm angle stiffener
Surface finish	
Painting	Powder Coating
Automation	
Drive Unit & Mounting Type	Electric Motor (Imported China make) (single phase / three phase) - Indirect Mounting - Sprocket chain arrangement
Emergency Operation	Manual Hand Driven
Operating Switch	Push Button from inside