NIHVA Technologies Pvt. Ltd.
187, G-Block, 1st Floor, Above Renault Showroom, Thermax chowk, MIDC,
Chinchwad.
Pune – 411019

An ISO 9001:2015 Certified Company

GST Pune : 27AAECN0437H1ZM

NIHVA Sales Quotation

Shubhshree Engineering & Constructions Pvt Ltd
Aurangabad

Date : 28.11.2020
Quote NO : SQT.18.19.1365R9
Kind Attn : Manish Sharma
Email Id : manishsharma@shubhshree.co.in
Contact No: 9175575106

Project, Location : Endress Hauser Flowtech Aurangabad

Subject : Quotation for Scissor Lift, Motorized Sliding Gate, Wicket Gate, Barrier Gate and Sliding Glass Door

Dear Sir,

Thank you for your opportunity and trust shown on "NIHVA" your preferred partner for innovative solutions.
This has reference to your above mentioned requirement, please find below our Solutions.

Sr. No	Description	Pages
A.	Commercial Offer	1
B.	Technical Specification	2 , 3
C.	General Conditions	4
D.	Terms & Condtions	4

A) Commercial Offer

Sr No	Description	Size		Qty	Supply Charges in INR		Installation Charges in INR	
		Clear Width (mm)	Clear Height (mm)	(Nos)	Unit Price	Total Amount	Unit Price	Total Amount
1	**NIHVA Scissor Lift - 6T point load and 15T UDL**	2000	2500	4	1,345,000	5,380,000	inclusive	
2	**Automatic Two Leaf Telescopic Gate**	6000	1800	1	493,000	493,000	inclusive	
3	**Wicket Gate**	1500	1800	1	90,000	90,000	inclusive	
4	**SS Barrier Gate**	1500	1000	1	398,000	398,000	inclusive	
5	**Glass Sliding Door**	2000	2200	1	354,000	354,000	inclusive	
	Total			**8**		**6,715,000**		**-**
	Standard Discount			5%		335,750		
	Total after Standard Discount					**6,379,250**		
6	P&F Charges			0%		-		
	Total Without Taxes					6,379,250		-
	GST Extra @ 18%			18%		1,148,265.00		-
	Total With Taxes					**7,527,515**		**-**
7	Transportation Charges					Inclusive		
8	Unloading Charges @ Site					NIHVA		

NIHVA Technologies Pvt. Ltd.
187, G-Block, 1st Floor, Above Renault Showroom, Thermax chowk, MIDC,
Chinchwad.
Pune – 411019

An ISO 9001:2015 Certified Company

GST Pune : 27AAECN0437H1ZM

B) Technical Specification

Pit Mounted Scissor Lift

Sr. No	Description	Specifications
1	Capacity	6T point load and 15T UDL
2	Platform size	(W) 2000 mm X (L) 2500 mm
3	Shut ht	1000 mm
4	Max ht	2200 mm
5	Lift ht	1200 mm
6	Power Pack Inside Pit with Buzzer	15 HP, 3 Phase - Eaton make
7	Safety Railing	Safety railing M.S SECTION 900 mm ht all side on platform & fixed
8	Manual Lip	3 Piece (240 + 1500 + 240) - 1 Side Only
9	Maintenance Stopper	2 NOS
10	Push Button Pendent	Flexible pendent with 5 mtr Cable - 1 No
11	Control Panel	Outside pit - 1 No
12	Safety Bellow	All side
13	Hydraulic Cylinder	Two numbers with Bore 150 X stroke 500 mm - Eaton make
14	Hot Dip Galvanized	IS 2629 / EN ISO 1461 / As per ASTM
15	Hose	Parker Hoses
16	Cable	Polycab cables
17	Hydraulic Oil	Grade 68 - 125 Ltr
18	Paint	Gloosy-20Ltr
19	Fabrication	3500KG

Motorised Two Leaf Telescopic Sliding Gate

Sr .No.	Specification	Motorised Two Leaf Telescopic Sliding Gate
1	**Door type**	Motorised Two Leaf Telescopic Sliding Gate
2	**Clear Opening gate dimension**	(W) 6000 mm X (H) 1800 mm
3	**Opening Direction**	Horizontal - from left to right or reverse
4	**Mounting Location area**	Inside area
5	**Design Pattern**	Standard Tubular Design Pattern
6	**Outer Frame Tube Sizes**	80 x 80 x 3.2 mm MS SQ. TUBE
7	**Internal Vertical Tube Sizes**	40 x 40 x 2 mm MS SQ. TUBE
8	**Gap Between Tubes**	100 mm C/C
9	**Bottom Rail on ground**	dia 20 mm round bright bar with heavy duty support ISMB 100 X 50 Beams
10	**Bottom Rollers**	Heavy Duty Bottom Wheel With both side Bearings
11	**Guide Rollers supporter during Gate movement**	Nylon Rollers with Bearings both side mounted on column for support smooth movement of gate
12	**Painting**	Two Coats of Primer and Two Coats of Synthetic Enamel Paint
13	**Control Panel**	2 Nos Operating Station.(Motor Panel and Security Room)
14	**Operation**	By Telescopic Mechanism
15	**Accessories**	1. Limit Switch for Cut out when Gate is fully Closed
		2. Flashing Light
		3. Photocell

Wicket Gate

Sr .No.	Specification	Telescopic Sliding Gate
1	**Door type**	Manual Single Leaf Wicket Gate
2	**Size considered**	Clear opening - (W)1200 mm x (H)1800 mm
3	**Mounting Location area**	Inside area
4	**Design Pattern**	Standard Tubular Design Pattern
5	**Outer Frame Tube Sizes**	80 x 80 x 3.2 mm
6	**Internal Vertical Tube Sizes**	40 x 40 x 2 mm
7	**Gap Between Tubes**	100 mm C/C
8	**Painting**	2 Coats of EPOXY polyamide based enamel finish of approved Colour
9	**Operation**	Manually Opening

NIHVA Technologies Pvt. Ltd.
187, G-Block, 1st Floor, Above Renault Showroom, Thermax chowk, MIDC,
Chinchwad.
Pune – 411019

An ISO 9001:2015 Certified Company

GST Pune : 27AAECN0437H1ZM

B) Technical Specification

Double Leaf SS Flap Barrier Gate

Sr .No.	Specification
1	It has zero position of self -checking, easy for users to maintain and use.
2	There is alarm notice function when illegal access.
3	Avoid bump function: When the turnstile does not receive the open signals, the baffle will lock automatically.
4	IR/mechanical dual anti-lined function: When the baffle has problem in reseeding, it will stop working automatically in certain time, and the potency is small, will make an alarm sound at the same time.
5	Resent automatically: the passenger read effectively, the system will cancel this access authority if they will not access in certain time.
6	Standard wiring connection: can connect with many kinds of card readers, and can remote control through the computer.
7	Optical beams for safety movements, Ensures rapid, efficient & safe access control
8	Easily integrated into access control system, Automatic reset of barrier flap after each valid entry, mechanical release key for emergency cases, fire trigger input facility. In the event of power failure panels can be specified to remain closed
9	The whole system works steadily, and the noise is very low. Size: 1400 x 280 x 980mm; Unlock time: 0.2s Pass rate: 35 person/min; Pass Width: ≤550mm; Input: 100V~240V; Driving Voltage: 24v; Environment: -25~70°c; Power Consumption: 35w; Input: 12v dry contact.

Sliding Glass Door

Sr.No.	Description	Specification
1	**Door type**	Bipart Sliding Glass Door
2	**Size considered**	(W)2000 mm x (H)2200 mm
3	**Main power supply**	1 ph, 230 V
4	**Operator type**	Bi part operator
5	**Operation mode**	Partial Opening/Auto/one way/closed/Open
6	**Battery**	Battery 12 V power fail open
7	**Activation**	By Radar Sensors from both sides
8	**Glass**	10mm thick toughened glass (Saint Gobain)
9	**Safety**	01 safety sensor from inside

NIHVA Technologies Pvt. Ltd.
187, G-Block, 1st Floor, Above Renault Showroom, Thermax chowk, MIDC,
Chinchwad.
Pune – 411019

An ISO 9001:2015 Certified Company

GST Pune : 27AAECN0437H1ZM

C) General Conditions

1 Installation will start after receiving of Site Readyness Photographs or written Email communication.

2 We will mobilize the Installation Team in 3 - 4 working days, after reciept of Site Readyness Confirmation

3 For any reason if we need to stop our Installation and demobilize the Team without completing the Work, then extra cost will be applicable for Remobilizing the Team.

4 If Lifting Equipements are in NIHVA Scope, then those will be used for Installation purpose only and not for any other works.

Note: Please find below List which are in Client Scope

Sr. No	Description		
1	Secured and fully covered Store area to keep the material	In Client Scope	
2	Scaffolding/Hydra/Crane/Forklift Etc - Required for Installation at Site	In NIHVA Scope	
3	Electrical Supply on the site single phase/three phase points at different places.	In Client Scope	
4	Any civil / masonry/structural work required	In Client Scope	
5	All structure support required	In Client Scope	
6	In Case of any changes in the layout as per site requirements after the shipment of material , the additional quantities and the wastage.	In Client Scope	
7	Conduits, Cables required	In Client Scope	

D) Terms & Conditions

Price : Ex Works Pune

Delivery : 6 - 7 weeks from the date of receipt of confirmed purchase order, Advance Payment & Drawing approval.

Payment : 80% Advance along with Confirmed Purchase Order & Balance before dispatch.

Validity : Validity of Offer is 15 days from the date of quotation

Warranty : 12 months from the date of supply.

Please feel free to Contact **Mr. Ravindra Kharat on 7410169333** For any further Clarification /Information in this Concern.

With Best Regards
Shailesh Bhoir
7219206333
For NIHVA Technologies Pvt Ltd