ASSA ABLOY

AUFTRAGSBESTÄTIGUNG/ ORDER CONFIRMATION

ASSA ABLOY Entrance Systems - Am Mondschein 25 - D-59557 Lippstadt

NIHVA Technologies PVT LTD 27 8/1 Coromant Housing Society 411044 Pune, Nigdi Pradhikar India	**Auftrags-Nr./Order No** 30715210 **Datum/Date** 2018-12-06 **Referenz/Reference** Mr. Marne **Verkäufer/Salesman**

Kunden-Nr./Customer No.	**Innendienst/Internal department**	**Versandart/Way of delivery**
1059669	Nadine Gundelach 02941/766-744	Air freight
Ihre Ust-ID Nr./Your TAX No	**Ihre Bestell-Nr./Your Order**	**Versandbedingungen/Terms of delivery**
	NVA-406	FCA / Hemau, Germany / Forwarder (W)

Lieferadresse/Delivery address **Nr. Lieferadresse/Delivery address No.**	**Zahlungsbedingungen/Terms of payment**
NIHVA Technologies PVT LT1059669 27 8/1 Coromant Housing Society 411044 Pune, Nigdi Pradhikar India	Due Net 90

Pos. item	Produkt Product	Beschreibung Description	Versanddatum Ship date	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price
10	**AD_RP300**	**ASSA ABLOY RP300**	**2019-01-21**	**1.000**	**ST**	**4,800.00**	**4,800.00**

Serien-Nr. 2610018196

Door type	High-speed roller door RapidProtect 300
Daylight width	4.000 mm
Daylight height	2.500 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	2,4 m/s
Max. Closing Speed	1,7 m/s
Control box position	Mounted next to the drive unit
Control system position	Right
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Pre running photocell at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Plus
Door curtain colour	Blue, similar to RAL 5002
Silicone free	Silicone free
Window type	Window 700X500 mm, type anti UV
Window Quantity	1
Height:bott.edge to bott.prof.	1.200 mm

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos.	Produkt	Beschreibung	Versanddatum	Anzahl	Einheit	Preis/Einh.	Preis
item	Product	Description	Ship date	QTY	Unit	Price/Unit	Price

Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
MCC type	Standard version
MCC display type	Display delivered separately, not mounted
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Interface cable length	3.000 mm
Mains connection cable length	3.000 mm
Dry contact	Dry contacts for signal door open / closed and door in operation
Interface card	Interface card delivered separately, installation on site in the customer control box
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	4500X480X400
Dimension packing 2 LxWxH	800X600X370

20 AD_RP300 ASSA ABLOY RP300 2019-01-21 1.000 ST 4,800.00 4,800.00

Serien-Nr. 2610018197

Door type	High-speed roller door RapidProtect 300
Daylight width	4.000 mm
Daylight height	2.500 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	2,4 m/s
Max. Closing Speed	1,7 m/s
Control box position	Mounted next to the drive unit
Control system position	Right
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Pre running photocell at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Plus
Door curtain colour	Blue, similar to RAL 5002
Silicone free	Silicone free
Window type	Window 700X500 mm, type anti UV
Window Quantity	1
Height:bott.edge to bott.prof.	1.200 mm
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
MCC type	Standard version
MCC display type	Display delivered separately, not mounted

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos. item	Produkt Product	Beschreibung Description	Versanddatum Ship date	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Interface cable length	3.000 mm
Mains connection cable length	3.000 mm
Dry contact	Dry contacts for signal door open / closed and door in operation
Interface card	Interface card delivered separately, installation on site in the customer control box
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	4500X480X400
Dimension packing 2 LxWxH	800X600X370

Warenwert/Value of goods **9,600.00**

Summe/Total **EUR** **9,600.00**

Wir danken für Ihren Auftrag Thank you for the order
Mit freundlichen Grüßen Best regards
Albany Door Systems GmbH

(Automatisch erstellt, daher ohne Unterschrift gültig
Written automatically, valid without signature)

Dem Auftrag liegen unsere allgemeinen, zur Zeit gültigen Verkaufsbedingungen zugrunde, die auch für alle weiteren Verträge Gültigkeit haben.
The order is based on our current general terms of sales, which will as well be applicable for all further contracts.

Die gesetzlichen durch die DSGVO geforderten Informationen zum Umgang mit Ihren personenbezogenen Daten erhalten Sie unter dem folgenden Link: https://goo.gl/qGzSw5

Sollten Sie keinen Zugang zum Internet haben, senden wir Ihnen gerne die Informationen postalisch zu. Bitte sprechen Sie uns ggf. unter Telefon: 02941/766-622 darauf an.

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye