Preventive Maintenance Manufacturer's Specification

ASSA ABLOY

ASSA ABLOY Entrance Systems

The global leader in door opening solutions

Enhance the durability of your High Performance Door Albany RR420

Key benefit

Safety

Cost-Savings

Just as a car's tires and oil must be changed regularly, your Albany High Performance Doors have key components that periodically need replacing. Whether it's a spring or a sprocket, changing them before they break is an integral part of Pro-Active Care.

We at ASSA ABLOY Entrance Systems believe in Pro-Active Care. Letting us replace components before they fail keeps your warranty valid and your equipment compliant with regulations. Even more importantly, it ensures the safety and functionality of your equipment, so that you can avoid accidents and losses in productivity.



Instructions for table usage:

Qualified person
The manufacturer's recommendation for exchange of components is subject to the findings of a qualified person. We strongly recommend that inspections are performed by a qualified person within the recommended service intervals (according to the user manual of the door).

Recommendations for exchange
The manufacturer's recommendations are based on a door with average size, installed under regular environmental conditions. Doors dimensioned close to maximum size of the door type or doors installed in harsh environmental conditions, need particular observation by a qualified person as the recommended intervals might be shorter.

Components specified as wear and tear related do not have a recommended exchange interval, indications for exchange or wear can be derived from the corresponding fact sheets.

Subject to technical modifications without notice. Errors and omissions excepted.

ASSA ABLOY ENTRANCE SYSTEMS
Maintenance & Modernization

Preventive Maintenance
Manufacturer's Specification

ASSA ABLOY

Albany RR420

Product group	Description	100.000 cycles	200.000 cycles	300.000 cycles	400.000 cycles	500.000 cycles	1.000.000 cycles	5 years	10 years	wear / tear related
Actuators	Photocell re / tr								●	
	Photocell Telco cpl.								●	
Brush	Brush strip (front & back)					●				
Cable chain	Cable chain, complete with cable and bracket					●				
Counterbalancing	Steel cable, w/o SRD		●							
	Cable pulley with bearings complete, w/o SRD		●							
	Spring				●					
	Steel cable, with SRD	●								
	Cable pulley with bearings complete, with SRD	●								
Curtain	Curtain									●
Top roll	Bearing					●				
Bottom profile	Rubber profile with contact strip							●		
	Rubber profile pneumatic							●		
	Rubber profile pneumatic crash							●		
	Rubber profile optical							●		
	Pneumatic pressure switch								●	
	Spiral cable			●						
Sliding/Guiding	Set of guides with wear pads					●				
	Plastic wear pad incl. Screws					●				
	Guide/Wire attachment SRD					●				
Drive unit	Drive unit 1,1 kW - frequency converter						●			
Brake	Brake - frequency converter						●			
Damper	Vibration absorber					●				

≤150.000 cycles: ±10.000 cycles; >150.000 cycles: ±20.000 cycles
≤5 years: ±6 months; >5 years: ±1 year

© ASSA ABLOY Entrance Systems AB PL.MAN/RR420/DEU.EN-1.1/1602 / 64 100 657 Technical data subject to change without notice

ASSA ABLOY ENTRANCE SYSTEMS
Maintenance & Modernization