NIHVA – Motorized Rated Rolling Shutter

Size: (W) 2400 mm x (H) 3000 mm

Description:

Motorised Rolling Shutter with Galvanised Steel Laths with thickness of 1 mm.

Mounting Location area

Inside area / Outside area

Mounting Surface

Side Brackets: Optional = On Concrete /Steel & Side

Curtain Panel
The panel made of 1.0mm thick GI steel

Curtain panel size
75mm wide

Curtain Profile
Curved

Bottom Profile
M. S. Plate 100 mm x 2.5 mm thick with angle stiffener

Side Guide Profile

M.S." U" Shaped profile 65 mm -150 mm x 3 mm thick (as per the opening width dimension)

Roller Shaft

M.S. Tubular Pipe with Flange & machined shaft at the ends Pipe Día -100 to 300 mm as per w x h

Side Brackets
MS Plate 3 mm to 10 mm thick, as per the opening dimension

Hood Cover
Made of GI Sheet Thickness 0.9 mm GI mm with 25x25x3mm angle stiffener

Surface finish

PU paint or Powder coated

Drive Unit & Mounting Type
Electric Motor - Indirect Mounting -Jielong

91 8551096333 ☎ +91 20 66304033

Email: Arjun.patil@nihva.com