Administrative Office:-
S. No. 10, Bangalow No 11, Bhagyashri Garden Society,Near Vinakar Sabhagruha, Dhanakawadi, Pune 411 043

Contact No. :- 7774051204 / 9372451112
Email:- nucleonics.equipments@gmail.com
nucsignal@gmail.com
Website:- www.nucleonicssignals.com

# NUCLEONICS

## TRAFFIC EQUIPMENTTS PVT. LTD.

AN ISO 9001 - 2008 CERTIFIED COMPANY

Manufacturers of Traffic Signals & Countdown Timers

# SPECIFICATION OF SIGNAL LAMPHEAD

1. High bright less power consumption daylight visible LED's from Taiwan.
2. LED board is of glass epoxy material having life of 15 years.
3. The clear lenses material and the sun visor is of vergin HDPEmaterial.
4. MS Body
5. The housing of lamphead is of IP 65 & IP 54 protection and LED's intensity, brightness,viewing angle is tested in government laboratory.
6. The lamphead is accompanied all mounting accessories and clamps suitable for any square or round poles.
7. Lamp head Assembly in Polycarbonate Housing with IP65 Certification
8. Highly Bright LED's (10,000 to 12,000 MCD) (190 Nos ) imported from Taiwan & tested in Government Laboratory for Intensity, Brightness & Wattage & Viewing Angle (Certificates attached).
9. LED board is of Glass Epoxy having life of 15 Years.
10. The clear lens is of Polycarbonate UV Protected and the Sunvisor is of vergin HDPE material.
11. The Lamphead as accompanied by all mounting accessories and Clamps suitable for any square or round poles.
12. The Wattage (Power consumption of LED Lamphead assembly is 4 -5 Watt's Only.

# RED LAMPHEAD

- Lamp head Size – 300mm dia
- 5 mm Round clear LED's – 190 nos.
- Intensity – 860cd
- LED forward current per group 20 MA
- 4.Viewing angle – 23 degree
- For Housing IP 65 protection / Compatible to IP 54
- Wave length 625 Nm
- For all above Govt. Laboratory test report attached.
- Ms Body –MS Look
- 3 in Led Flash
- Case type – 6
- Operating – 110 / 120 VAC

# GREEN LAMPHEAD

- Lamp head Size – 300mm dia
- 5 mm Round clear LED's – 190 nos.
- Intensity – 590 cd
- LED forward current per group 20 MA
- 4.Viewing angle – 23 degree
- For Housing IP 65 protection
- Wave length 625 Nm
- For all above Govt. Laboratory test report attached.