**Motorized 3 Leaf Telescopic Sliding Gate with vision window (each Leaf) and MS Sheet on One Side**

| Sr .No. | Specification | Telescopic Sliding Gate |
|---|---|---|
| 1 | **Door type** | Motorised Three Leaf Telescopic Sliding Gate with vision window (each Leaf) and MS Sheet on One Side |
| 2 | **Clear Opening gate dimension** | (W) 6000 mm X (H) 1800 mm |
| 3 | **Master Leaf Size** | 2670 X 1800 mm |
| 4 | **1 ST Leaf Size** | 2370 X 1800 mm |
| 5 | **2 ND Leaf Size** | 2370 X 1800 mm |
| 6 | **Opening Direction** | Horizontal - from left to right or reverse |
| 7 | **Mounting Location area** | Inside area |
| 8 | **Design Pattern** | Standard Tubular Design Pattern |
| 9 | **Outer Frame Tube Sizes** | 50 X 50 X 3 mm MS SHS |
| 10 | **Internal Vertical Tube Sizes** | 50 X 25 X 3 mm MS SHS |
| 11 | **For Post** | 50 X 50 X 3 mm MS SHS |
| 12 | **Bottom Rail on ground** | dia 20 mm round bright bar with heavy duty support ISMB 100 X 50 Beams |
| 13 | **Bottom Rollers** | Heavy Duty Bottom Wheel With both side Bearings |
| 14 | **Guide Rollers supporter during Gate movement** | Nylon Rollers with Bearings both side mounted on column for support smooth movement of gate |
| 15 | **Painting** | Powder Coating |
| 16 | **Control Panel** | 1 No Operating Station. |
| 17 | **Operation** | By Telescopic Mechanism |
| 18 | **Accessories** | 1. Limit Switch for Cut out when Gate is fully Closed |
| | | 2. Flashing Light |
| | | 3. Remote |
| | | 4. Hooter |
| | | 5. Photocell |
| 19 | **Civil work** | Client scope – client need to grout the I beam in concrete to create track for sliding gate |