


TECHNICAL SPECIFICATION :

SR.	SPECIFICATIONS	DETAILS
1	Control Panel	LED Display Servo Controller : - Working Temperature : -30°C to +85°C Water Resistant : IP65 Make IDER, manufactured under European Standards
2	Motor	Servo Motor Make IDER Make ,CE Certified
3	Manual Release	Hand Crank
4	Door Travel Speed	Opening: 0.5m /Sec & Closing: 0.5m/Sec
5	Safety Device	Safety Photocell Pair & Safety Edges
6	Accessories	Dual Magnetic Loop Detector ,Flashing Light
4	PVC CURTAIN	RAL 5010
5	Door Guide & Buttom	Aluminium

Note:-
1. All Dimension are in mm
2. Side guide & Bottom Off-white Colour
3. Zebra Crossing Stickers on Bottom Profile

Sr	Clear Width (CW)	Clear Height (CH)	QTY
1	3350	2800	1

This drawing & design is the property of NIHVA TECHNOLOGIES. Not to be sold or copied to any other concern.

		NAME	SIGN	DATE
TITLE	SELF REPAIRABLE HIGH SPEED DOOR WITH GA DRAWING			
DRAWN		S.J		24.07.2024
CHECK		B.B		24.07.2024
APPRD.		V.T		

NIHVA TECHNOLOGIES PVT. LTD.
NIHVA TECHNOLOGIES PVT. LTD. PUNE
Tel : 020 66304033
Email:- info@nihva.com
Website:- www.nihva.com

CLIENT -

PROJECT - HIGH SPEED DOOR

FORMAT NO - NIHVA-DD-F-03

If any queries contact : projectsupport@nihva.com

DWG. NO. : NIHVA/24-25/00XX

REV- R03

ALL DIMENSION ARE IN mm

SCALE: NTS

WT:

SHEET: