ASSA ABLOY

RECHNUNG/INVOICE

Kopie/Copy

ASSA ABLOY Entrance Systems - Am Mondschein 25 - D-59557 Lippstadt

NIHVA Technologies PVT LTD
27 8/1 Coromant Housing Society
411044 Pune, Nigdi Pradhikar
India

Rechnung/Invoice	90657963
Datum/Date	2017-12-12
Lieferschein-Nr./delivery note	80367791
Auftrags-Nr./Order No.	30644613
Referenz/Reference	Mr. Dange

Kunden-Nr./Customer No.	Innendienst/Internal department	Versandart/Way of delivery	
1059669	Tatjana Rerich	Forwarder (W)	Sea freight
Ihre Ust-ID Nr./Your TAX No	**Ihre Bestell-Nr./Your Order**	**Versandbedingungen/Terms of delivery**	**Lieferdatum/Delivery date**
	NVA- 335	FCA Lippstadt	2017-12-12

Lieferadresse/Delivery address	Nr. Lieferadresse/Delivery address No.	Zahlungsbedingungen/Terms of payment	Fälligkeit/Due date
NIHVA Technologies PVT LTD 27 8/1 Coromant Housing Society 411044 Pune, Nigdi Pradhikar India	1059669	Due Net 60	2018-02-10

Pos. Item	Produkt Product	Beschreibung Description	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

FCL Container delivery

AD_RR300_PLUS	**Albany RR300_plus**		**1.000**	**ST**	**5,235.00**	**5,235.00**
Serien-Nr. 1300009933						
Door type	High speed roller door RapidRoll 300 Plus					
Daylight width	3 000 mm					
Daylight height	3 500 mm					
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit					
Max. Opening Speed	2,2 m/s					
Max. Closing Speed	0,9 m/s					
Control box position	Mounted next to the drive unit					
Motor Position	Right					
Wind class	1					
Side frame version	Aluminium					
Bottom plate	Bottom plates included					
Bottom profile	Aluminium					
Safety contact edge	Electrical safety edge at the bottom profile					
Connection for safety edge	With cable chain, integrated in side frame					
Photocell	With photocell					
Manual egress (brake release)	Release handle with encapsulated cable on the front side					
Brake type	Door equipped with fail safe brake. When the brake is released by the door opens partially supported by the balancing system.					
Egress height	When the brake is released doors up to daylight height of 2300mm open up					

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Register court Paderborn: HR B 61 06

Management:
Juan Vargues
Per Hansson

64 300 006 15/12 DE

Pos. item	Produkt Product	Beschreibung Description	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

	to 75% of the daylight height. Doors with daylight height > 2300mm open approx. 2m
Top roll material	Aluminum
Door curtain	PVC material - transparent with vertical coloured stripes
Door curtain colour	Red, similar to RAL 3002
MCC type	Standard version
MCC-display position	Mounted on the side frame, drive side
MCC display type	Standard display with push buttons
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Mains connection cable length	4 500 mm
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	4000X480X400
Dimension packing 2 LxWxH	800X600X580
Commodity code: 39252000	
Country of origin: CZ	

Dimension packing 1 LxWxH	**4000x530x430**
Dimension packing 2 LxWxH	**800x600x580**
Net Weight	**246,000 KG**
Gross Weight	**246,000 KG**

AD_RR300_PLUS **Albany RR300_plus** **1.000** **ST** **5,235.00** **5,235.00**
Serien-Nr. 1300009934

Door type	High speed roller door RapidRoll 300 Plus
Daylight width	3 000 mm
Daylight height	3 500 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	2,2 m/s
Max. Closing Speed	0,9 m/s
Control box position	Mounted next to the drive unit
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Bottom plates included
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Connection for safety edge	With cable chain, integrated in side frame
Photocell	With photocell
Manual egress (brake release)	Release handle with encapsulated cable on the front side
Brake type	Door equipped with fail safe brake. When the brake is released by the door opens partially supported by the balancing system.
Egress height	When the brake is released doors up to daylight height of 2300mm open up to 75% of the daylight height. Doors with daylight height > 2300mm

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Register court Paderborn: HR B 61 06

Management:
Juan Vargues
Per Hansson

64 300 006 15/12 DE

Pos. item	Produkt Product	Beschreibung Description	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

	open approx. 2m
Top roll material	Aluminum
Door curtain	PVC material - transparent with vertical coloured stripes
Door curtain colour	Red, similar to RAL 3002
MCC type	Standard version
MCC-display position	Mounted on the side frame, drive side
MCC display type	Standard display with push buttons
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Mains connection cable length	4 500 mm
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	4000X480X400
Dimension packing 2 LxWxH	800X600X580

Commodity code: 39252000
Country of origin: CZ

Dimension packing 1 LxWxH	**4000x530x430**
Dimension packing 2 LxWxH	**800x600x580**
Net Weight	**248,000 KG**
Gross Weight	**248,000 KG**

AD_RR300_PLUS **Albany RR300_plus** **1.000** **ST** **5,235.00** **5,235.00**
Serien-Nr. 1300009935

Door type	High speed roller door RapidRoll 300 Plus
Daylight width	3 000 mm
Daylight height	3 500 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	2,2 m/s
Max. Closing Speed	0,9 m/s
Control box position	Mounted next to the drive unit
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Bottom plates included
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Connection for safety edge	With cable chain, integrated in side frame
Photocell	With photocell
Manual egress (brake release)	Release handle with encapsulated cable on the front side
Brake type	Door equipped with fail safe brake. When the brake is released by the door opens partially supported by the balancing system.
Egress height	When the brake is released doors up to daylight height of 2300mm open up to 75% of the daylight height. Doors with daylight height > 2300mm open approx. 2m
Top roll material	Aluminum

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Register court Paderborn: HR B 61 06

Management:
Juan Vargues
Per Hansson

64 300 006 15|12 DE

Pos. item	Produkt Product	Beschreibung Description	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

Door curtain	PVC material - transparent with vertical coloured stripes
Door curtain colour	Red, similar to RAL 3002
MCC type	Standard version
MCC-display position	Mounted on the side frame, drive side
MCC display type	Standard display with push buttons
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Mains connection cable length	4 500 mm
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	4000X480X400
Dimension packing 2 LxWxH	800X600X580

Commodity code: 39252000
Country of origin: CZ

Dimension packing 1 LxWxH	**4000x530x430**
Dimension packing 2 LxWxH	**800x600x580**
Net Weight	**244,000 KG**
Gross Weight	**244,000 KG**

AD_RR300_PLUS **Albany RR300_plus** **1.000** **ST** **5,150.00** **5,150.00**
Serien-Nr. 1300009936

Door type	High speed roller door RapidRoll 300 Plus
Daylight width	3 000 mm
Daylight height	3 000 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	2,2 m/s
Max. Closing Speed	0,9 m/s
Control box position	Mounted next to the drive unit
Motor Position	Left
Wind class	1
Side frame version	Aluminium
Bottom plate	Bottom plates included
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Connection for safety edge	With cable chain, integrated in side frame
Photocell	With photocell
Manual egress (brake release)	Release handle with encapsulated cable on the front side
Brake type	Door equipped with fail safe brake. When the brake is released by the door opens partially supported by the balancing system.
Egress height	When the brake is released doors up to daylight height of 2300mm open up to 75% of the daylight height. Doors with daylight height > 2300mm open approx. 2m
Top roll material	Aluminum
Door curtain	PVC material - transparent with vertical coloured stripes
Door curtain colour	Red, similar to RAL 3002

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Register court Paderborn: HR B 61 06

Management:
Juan Vargues
Per Hansson

64 300 006 15|12 DE

Pos. / Item	Produkt / Product	Beschreibung / Description	Anzahl / QTY	Einheit / Unit	Preis/Einh. / Price/Unit	Preis / Price

MCC type	Standard version
MCC-display position	Mounted on the side frame, drive side
MCC display type	Standard display with push buttons
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Mains connection cable length	3 000 mm
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	3500X480X400
Dimension packing 2 LxWxH	800X600X580

Commodity code: 39252000
Country of origin: CZ

Dimension packing 1 LxWxH	**3500x530x430**
Dimension packing 2 LxWxH	**800x600x580**
Net Weight	**206,000 KG**
Gross Weight	**206,000 KG**

AD_RR300_PLUS **Albany RR300_plus** **1.000** **ST** **4,880.00** **4,880.00**
Serien-Nr. 1300009937

Door type	High speed roller door RapidRoll 300 Plus
Daylight width	2 000 mm
Daylight height	3 000 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	2,2 m/s
Max. Closing Speed	0,9 m/s
Control box position	Mounted next to the drive unit
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Bottom plates included
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Connection for safety edge	With cable chain, integrated in side frame
Photocell	With photocell
Manual egress (brake release)	Release handle with encapsulated cable on the front side
Brake type	Door equipped with fail safe brake. When the brake is released by the door opens partially supported by the balancing system.
Egress height	When the brake is released doors up to daylight height of 2300mm open up to 75% of the daylight height. Doors with daylight height > 2300mm open approx. 2m
Top roll material	Aluminum
Door curtain	PVC material - transparent with vertical coloured stripes
Door curtain colour	Red, similar to RAL 3002
MCC type	Standard version
MCC-display position	Mounted on the side frame, drive side

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Register court Paderborn: HR B 61 06

Management:
Juan Vargues
Per Hansson

64 300 006 15/12 DE

Pos. / Item	Produkt / Product	Beschreibung / Description	Anzahl / QTY	Einheit / Unit	Preis/Einh. / Price/Unit	Preis / Price

MCC display type	Standard display with push buttons
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Mains connection cable length	3 000 mm
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	3500X480X400
Dimension packing 2 LxWxH	800X600X580

Commodity code: 39252000
Country of origin: CZ

Dimension packing 1 LxWxH	**3500x530x430**
Dimension packing 2 LxWxH	**800x600x580**
Net Weight	**229,000 KG**
Gross Weight	**229,000 KG**

AD_RR300_PLUS **Albany RR300_plus** **1.000** **ST** **5,090.00** **5,090.00**
Serien-Nr. 1300009938

Door type	High speed roller door RapidRoll 300 Plus
Daylight width	2 450 mm
Daylight height	3 500 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	2,2 m/s
Max. Closing Speed	0,9 m/s
Control box position	Mounted next to the drive unit
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Bottom plates included
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Connection for safety edge	With cable chain, integrated in side frame
Photocell	With photocell
Manual egress (brake release)	Release handle with encapsulated cable on the front side
Brake type	Door equipped with fail safe brake. When the brake is released by the door opens partially supported by the balancing system.
Egress height	When the brake is released doors up to daylight height of 2300mm open up to 75% of the daylight height. Doors with daylight height > 2300mm open approx. 2m
Top roll material	Aluminum
Door curtain	PVC material - transparent with vertical coloured stripes
Door curtain colour	Red, similar to RAL 3002
MCC type	Standard version
MCC-display position	Mounted on the side frame, drive side
MCC display type	Standard display with push buttons
Power supply	400 V, 3-phase

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Register court Paderborn: HR B 61 06

Management:
Juan Vargues
Per Hansson

64 300 006 15/12 DE

Pos. item	Produkt Product	Beschreibung Description	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

Frequency	50 Hz
Main switch	With main switch
Mains connection cable length	4 500 mm
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	4000X480X400
Dimension packing 2 LxWxH	800X600X580
Commodity code: 39252000	
Country of origin: CZ	

Dimension packing 1 LxWxH	**4000x530x430**
Dimension packing 2 LxWxH	**800x600x300**
Net Weight	**218,000 KG**
Gross Weight	**218,000 KG**

AD_RR300_PLUS **Albany RR300_plus** **1.000** **ST** **5,090.00** **5,090.00**

Serien-Nr. 1300009939

Door type	High speed roller door RapidRoll 300 Plus
Daylight width	2 500 mm
Daylight height	3 500 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	2,2 m/s
Max. Closing Speed	0,9 m/s
Control box position	Mounted next to the drive unit
Motor Position	Left
Wind class	1
Side frame version	Aluminium
Bottom plate	Bottom plates included
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Connection for safety edge	With cable chain, integrated in side frame
Photocell	With photocell
Manual egress (brake release)	Release handle with encapsulated cable on the front side
Brake type	Door equipped with fail safe brake. When the brake is released by the door opens partially supported by the balancing system.
Egress height	When the brake is released doors up to daylight height of 2300mm open up to 75% of the daylight height. Doors with daylight height > 2300mm open approx. 2m
Top roll material	Aluminum
Door curtain	PVC material - transparent with vertical coloured stripes
Door curtain colour	Red, similar to RAL 3002
MCC type	Standard version
MCC-display position	Mounted on the side frame, drive side
MCC display type	Standard display with push buttons
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Register court Paderborn: HR B 61 06

Management:
Juan Vargues
Per Hansson

64 300 006 15/12 DE

Pos. item	Produkt Product	Beschreibung Description	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

Mains connection cable length	4 500 mm
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	4000X480X400
Dimension packing 2 LxWxH	800X600X580

Commodity code: 39252000
Country of origin: CZ

Dimension packing 1 LxWxH	**4000x530x430**
Dimension packing 2 LxWxH	**800x600x580**
Net Weight	**192,000 KG**
Gross Weight	**192,000 KG**

AD_RR5000 **Albany RR3000 ISO** **1.000** **ST** **11,170.00** **11,170.00**

Serien-Nr. 2701001511

Door type	RapidRoll 3000 ISO_
Daylight width	3 000 mm
Daylight height	3 500 mm
Side frame extension X-Level	0 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	2,1 m/s
Max. Closing Speed	0,7 m/s
Control box position	Mounted next to the drive unit
Motor Position	Right
Wind class	3
Side frame version	Galvanised steel
Manual egress (brake release)	Release handle with encapsulated cable on the front side
Top roll material	Top roll made of steel
Door curtain	Lamella type AI
MCC type	Standard version
MCC-display position	Mounted on the side frame, drive side
MCC display type	Standard display with push buttons
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Mains connection cable length	4 500 mm
Light curtain	With light curtain integrated in the side frames
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
Qty. window lamella	4
Window level	1 335 mm
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	3880X800X1150

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Register court Paderborn: HR B 61 06

Management:
Juan Vargues
Per Hansson

64 300 006 15/12 DE

Pos. item	Produkt Product	Beschreibung Description	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

Dimension packing 2 LxWxH 4500X800X600
Commodity code: 73083000
Country of origin: CZ

Dimension packing 1 LxWxH 4000x920x1160
Dimension packing 2 LxWxH 4500x750x750
Net Weight 830,000 KG
Gross Weight 830,000 KG

AD_RR5000 Albany RR3000 ISO **1.000 ST 11,170.00 11,170.00**
Serien-Nr. 2701001512

Door type	RapidRoll 3000 ISO_
Daylight width	3 000 mm
Daylight height	3 500 mm
Side frame extension X-Level	0 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	2,1 m/s
Max. Closing Speed	0,7 m/s
Control box position	Mounted next to the drive unit
Motor Position	Right
Wind class	3
Side frame version	Galvanised steel
Manual egress (brake release)	Release handle with encapsulated cable on the front side
Top roll material	Top roll made of steel
Door curtain	Lamella type AI
MCC type	Standard version
MCC-display position	Mounted on the side frame, drive side
MCC display type	Standard display with push buttons
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Mains connection cable length	4 500 mm
Light curtain	With light curtain integrated in the side frames
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
Qty. window lamella	4
Window level	1 335 mm
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	3880X800X1150
Dimension packing 2 LxWxH	4500X800X600
Commodity code: 73083000	
Country of origin: CZ	

Dimension packing 1 LxWxH 4000x870x1110
Dimension packing 2 LxWxH 4500x750x750
Net Weight 812,000 KG
Gross Weight 812,000 KG

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Register court Paderborn: HR B 61 06

Management:
Juan Vargues
Per Hansson

64 300 006 15/12 DE

Warenwert/Value of goods		**58,255.00**
Mwst/VAT	**0.00 %**	**0.00**
Summe/Total	**EUR**	**58,255.00**

Goods delivered outside the European Community are tax free according to § 4 No. 1a UStG

ASSA ABLOY Entrance Systems
High Performance Door Solutions

Albany Door Systems GmbH
Am Mondschein 25
DE - 59557 Lippstadt
Tel.: 02941 / 766-0
www.albanydoors.com

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Register court Paderborn: HR B 61 06

Management:
Juan Vargues
Per Hansson

64 300 006 15/12 DE