Motorized Single Skin Rolling Shutter - Indirect Drive- 8000 CW X 8150 CH mm

Sr .No.	Specification	Motorized Single Skin Rolling Shutter - Indirect Drive
1	**Description:**	Motorised Rolling Shutter with GI Slats with thickness of 1.2 mm.
2	**Mounting Location area**	Inside area
3	**Mounting Surface**	Side Brackets Steel & Side
4	**Curtain Panel**	The panel made of 1.2mm thick GI.
5	**Curtain panel size**	75mm wide
6	**Curtain Profile**	Curved with 3 meter Grill at height of 1500 mm from bottom.
7	**Bottom Profile**	M. S. Plate 100 mm x 2 mm thick with angle stiffener
8	**Side Guide Profile**	M.S." T" Shaped profile 65 mm -150 mm x 2 mm thick. (Not mentioned Actual required)
9	**Roller Shaft**	M.S. Tubular Pipe with Flange & machined shaft at the ends Pipe Día -100 to 300 mm as per w x h (Not mentioned Actual required)
10	**Side Brackets**	MS Plate 3 mm to 10 mm thick, as per the opening dimension. (Not mentioned actual required)
11	**Hood Cover**	Made of GI Sheet Thickness 0.9 mm (Actual 0.8)
12	**Surface finish**	Powder coated (Not mentioned RAL Code)
13	**Drive Unit & Mounting Type**	Electric Motor - Indirect Mounting - Sprocket chain arrangement – IP54 Protection
15	**Safety Catch & Windlock**	Included

NIHVA

PRE DISPATCH INSPECTION REPORT

NIHVA - QA - F - 07

Client Name : - Glatt

Report No : - PDIR-Glatt-01

Project Name :- Glatt

Location :- NIHVA Shop

Date :- 07-07-2023

Product Name :- Automatic Rolling Shutter (8000W×8150H)

Sr.No.	Part Name	Drawing No.	Dimesion in mm	Qty per product	Observation		Remarks
					1	2	
1	Solid Slat (H×W×T)	NIHVA/23-24/VDR/0153	8150W x 1.2	212	8150WX1.2	8150X1.2	Acceptable
2	Honey Comb Grill (WxH)	NIHVA/23-24/VDR/0153	8150W x 1500H	2	8150WX1500H	8150X1500	Acceptable
3	PIPE Shaft (L×D)	NIHVA/23-24/VDR/0153	8250 X 164	2	8250X165	8250X165	Acceptable
4	Hood Cover (L×W×T)	NIHVA/23-24/VDR/0153	8650 X 535 X 0.8	2	8650X535X0.8	8650X535X0.8	Acceptable
5	M.S. Bottom (L×W×T)	NIHVA/23-24/VDR/0153	8150Lx 2T	2	8150LX2X130W	8150X2X130W	Acceptable
6	Guide (H×W×T)	NIHVA/23-24/VDR/0153	8150 H X 115 W X 2 T	4	8150HX115W X95X2	8150X115X 95X2	150mm short (Not Acceptable)
7	Side Bracket (L×W×T)	NIHVA/23-24/VDR/0153	535L X 535W X 5T	4	530X530X5	530X530X5	Acceptable
8	Motor Cover (L×W×H×T)	NIHVA/23-24/VDR/0153	600L X 400W X 350H	2	600X400X400	600X400X400	Not Acceptable.

Remark : All the dimensionally ~~accepted~~ observations are found ok, except Guide height 150mm short as per required. But riveting of hood cover is extra visible, it should be cleared before powder coating.

Rohit Pawar

Inspected By

Rohit Pawar

Checked By

07/07/2023