NIHVA

Opening doors
to business and life

ASSA ABLOY

ASSA ABLOY Entrance Systems

The global leader in
door opening solutions

Project	**Rajasthan Hangar**
Location	
Application	**Civil Aviation**
Our ref.no.	**219-028**
Calculated	2019-09-24 09:27
Notes	45°C ambient temperature applied.

System summary

Calc by	Mats Brännström
Version	V 2019-09-03 15:12:16 4730
Revision	A
Identical doors	2
Total weight	10234 kg
Shipping weight	11874 kg
Shipping volume	76,77 m³
Overall clear width	38760 mm
Environment	Megadoor Standard
Nominal current	25,0 A
Total power	11,5 kW
Hoist peak current	52,6 A
Voltage/Frequency	400 V 50 Hz
Control panel base	A1 Door Cabinet, 500x600x250
Control panel	A10x Door/Mullion Cabinet, 500x600x250 (9A nom.)
Control panel	A10x Door Cabinet, 500x600x250 (9A nom.)
Control panel	A10x Door/Mullion Cabinet, 500x600x250 (9A nom.)

Options selected

Back-up power switch
Audible and visual alarm
Beam clamps

Door 1 options selected

Metal trim both sides
Floor/site-built door leaf
Colored clamp strip on inside
Colored clamp strip on outside

Door 1

CW	12518 mm
CH	7700 mm
Depth	290 mm
Differential pressure	1 kPa (20,9 psf)
Leaf height	9004 mm
Total height	9474 mm
Total width	12758 mm
Number of splices	1
Guide shoe load	10,0 kN
Leaf fabric outside	Standard fabric, Colour TBC
Leaf fabric inside	Standard fabric, Colour TBC
Header box	1 hoist
Hoist	1 * SK 973.1Z-100LA/4
Open time	42 sec
Moving weight	1687 kg
Total weight	2661 kg
Bottom seal	EPDM Grey 644 mm

Mullion 1

Mullion	VKR400x200x6,3 355
Clear under mullion	7000 mm

Building deflection down	61 mm
Building deflection up	61 mm
Mullion swing time	45 sec
Mullion floor pit lenght	1700 mm
Mullion hoist load	675 kg
Mullion weight	1175 kg

Door 2 options selected

- Metal trim both sides
- Floor/site-built door leaf
- Colored clamp strip on inside
- Colored clamp strip on outside

Door 2

CW	12518 mm
CH	7700 mm
Depth	290 mm
Differential pressure	1 kPa (20,9 psf)
Leaf height	9004 mm
Total height	9474 mm
Total width	12758 mm
Number of splices	1
Guide shoe load	10,0 kN
Leaf fabric outside	Standard fabric, Colour TBC
Leaf fabric inside	Standard fabric, Colour TBC
Header box	1 hoist
Hoist	1 * SK 973.1Z-100LA/4
Open time	42 sec
Moving weight	1687 kg
Total weight	2573 kg
Bottom seal	EPDM Grey 644 mm

Mullion 23

Mullion	VKR400x200x6,3 355
Clear under mullion	7000 mm
Building deflection down	61 mm
Building deflection up	61 mm
Mullion swing time	45 sec
Mullion floor pit lenght	1700 mm
Mullion hoist load	675 kg
Mullion weight	1175 kg

Door 3 options selected

- Metal trim both sides
- Floor/site-built door leaf
- Colored clamp strip on inside
- Colored clamp strip on outside

Door 3

CW	12518 mm
CH	7700 mm
Depth	290 mm
Differential pressure	1 kPa (20,9 psf)
Leaf height	9004 mm
Total height	9474 mm
Total width	12758 mm
Number of splices	1
Guide shoe load	10,0 kN
Leaf fabric outside	Standard fabric, Colour TBC
Leaf fabric inside	Standard fabric, Colour TBC
Header box	1 hoist
Hoist	1 * SK 973.1Z-100LA/4
Open time	42 sec
Moving weight	1687 kg
Total weight	2650 kg
Bottom seal	EPDM Grey 644 mm