S.No	Specification		Remarks
1	Type of gate:	4 leaf telescopic gates	
2	Movement of each leaf:	Motorized	
3	Gate structure:	MS heavy duty tubular box section	
4	Leaf dimensions (Height):	1000 mm (minimum)	
5	Gate leaf width:	To be designed suitably with tail gap of minimum 250mm tail on drive gate.	
6	Channel section of column support:	100x100x3mm (MS) or suitable	
7	Gaps between tracks:	40mm (approx.)	
8	Suitable concrete support for mounting of the sliding track and support post and motor		
9	Distance between the side tracks:	60 mm (Approx.)or suitable	
10	Gate height:	50mm spacing under the gate or suitable	
11	Gap between gap and support post:	75mm (Approx.)	
12	Overlap between the gate leaf:	75mm (Approx.)	
13	Guide rail:	40x20mm. welded 10mm below the top of the rail on inside face of the fate	
14	Top rail section:	50x50mm 3mm thick(Alternate Section dimension and design are acceptable meeting thickness requirement)	
15	Internal fillings:	Vertical slats of 40mm gap of 2mm thickness	
16	Sliding Mechanism:	Specially designed Telescopic Mechanism	
17	Rollers:	Bottom Wheel with both side bearings Track	
18	Polished bright bar with I-beam support.		
19	Nylon Rollers with bearings. Mounted on column for support & smooth movement of sliding gate		
20	Full height Column: Heavy Duty Box Section Support column.		
21	Partial opening should be achievable		
22	Available with hinged side for pedestrian use.		
23	Electromechanical gear motors to be designed with factor of safety		
24	Gate should be able to be operated manually in case of power failure.		
25	Sand blasting, hot deep galvanizing process, painting should be provided all materials.		
26	Should be provided with remote control with receiver		
27	Motor should be IP 65 or better		
28	Additional push button for operation		
29	Motor should withstand 3T.		