


Abbrevation's:
WOW-Wall Opening Width
WOH-Wall Opening Height
FFL-Finished Floor Level



Inside Elevation



Top View



Detail view of Section A

ASSESORIES DETALES

(a) HINGES: SS Ball bearing butt hinges 4"x3"x3mm(MAKE DORMA)

(b) LOCK : Panic bar(IR-BRITON 378 E) with external trim(IR-BRITON 1413E).

(c) DOOR CLOSER: RYOBI.

(d) GLASS : 5mm Thk. Vision Glass of size 200x300mm.

(e) AUTO DROP DOWN SEAL

Shutter thickness : 46 mm
Frame Sheet thick : 1.5mm
Shutter sheet thick : 1.2mm
Fixing : On Solid Brick plasterd wall with Anchors

NOTE:- *All Dimensions are in mm.
*Tolerance:-All Linear Dimensions ±3mm,Others ±0.5mm.
*The Drawing Is For Location of Hardware only. Drawing Does Not Represent The Hardware For More Clarity, Please Go Through Hardware Broucher.

FIRE RATED EXIT DOOR

SR. NO.	WOW	WOH	TYPE 1 (LH)	TYPE 2 (RH)	TYPE 3 (LHR)	TYPE 4 (RHR)	QUANTITY
01	1200	2500			01	01	02 NOS

COLOR -
SIGNAL RED (RAL 3001)

This drawing & design is the property of NIHVA TECHNOLOGIES. Not be sold or copy to any other concern.

TITLE:-
FIRE RATED EXIT DOOR

	NAME	DATE	SIGN.
DRAWN	OMKAR	30/12/17	
CHECK	SHEKHAR	30/12/17	
APPRD.	SHEKHAR	30/12/17	

If any queries contact :design@nihva.com

ALL DIMENSION ARE IN mm

NIHVA TECHNOLOGIES PVT. LTD.
NIHVA TECHNOLOGY PVT. LTD. PUNE
Tel : 020 66304033
Email:- info@nihva.com
Website:-www.nihva.com

CLIENT -
PROJECT -
SITE -
DWG. NO. - NIHVA/17-18/VDR/0196 REV. : 0
SCALE: 01 WT: SHEET: 01 OF 01