NIHVA
NIHVA TECHNOLOGIES PVT. LTD.

Supply & Installtion of Telescopic belt conveyor		**Supplier Name**	**NIHVA Technologies**
Technical Specifcations - Telescopic Belt conveyor		**Contact No**	**Vijay 8551093333**
DOC REF	**E-BQ-R0-RFP-TELESCOPIC BELT CONVEYOR**	**Address**	**Pune Maharashtra**
DRG NO	**LT000025**	**Manufacturer Name**	**NIHVA Technologies**
LOGIC DOC	**NA**		

DEVIATION TEMPLATE- SUGGESTED BY SUPPLIER

	Sl No.	Technical Specifications	Customer Specifications		Supplier Spec
			UOM	Spec.	
	PLEASE MENTION THE SL NO. OF THE SPECIFICATION	**PLEASE MENTION THE EXACT SPECIFICATION THAT HAS BEEN MENTIONED IN THE SPEC SHEET**	**SAME AS SPECIFICATION SHEET**	**SAME AS SPECIFICATION SHEET**	
		Type of Drive System	Geared Motor (Non Worm Type)		worm type
		Nominal width	mm	E2-T1,000	800 mm belt width we connsidered
		Overall Height (Max) Exc Guide	mm	450-500	850 mm total height from ground to belt top .
		Type of Drive System	Typ	Geared Motor (Non Worm Type)	Helical -worm type
		Bed Type	Typ	Slider Bed with Prepainted/Coated Galvalume	We use skid plate below the belt with powder coated
		Slider Bed - Length b/w Lap Joints (Nom)	mm	E2-T2,400	As per design
		Max Angle of Inclination	Degree	Upto 7 Degree Adjustable	4 degree of inclination is ok ,
		Annual Maintenance Contract Offered	yes/no	Vendor to provide	This AMC is only considered beyond Warranty Period. Scope of Work included & the Current Rate for such a contract need to be specified -(Ok but AMC charges extra)
		Nearest Service Location	Location	Vendor to provide	Please specify the Base Location of Trained & Experienced (Min. 1Yr) Service Personnel-- Based on your installation site
			SPARE ANNEXURE (Related to Pt.no.1)		
		MOTORS+GEARBOX	1 nos per motor type		We will provide after PO approval
		CHAIN	Min length as installed in a TBC		
		ROLLERS / SHAFTS	2 nos per roller type		
		BEARINGS	5% of total installed quantities (min qty 1 nos)		
		BELT	1 nos belt per type. If same type of belt with different lengths are		
		PANEL ITEMS	1 nos all the panel components including but not limited to current		
		FIELD DEVICES	5% of total installed quantities (sensors, reflecting plates or stickers,		
		EHS points			
		Fixed guards shall be mounted for all sprockets, chains rollers, belts			For exposed sprocket and moving parts we will provide gaurds.
		LOTO provision shall be ensured on the isolation switches. Energy			Ok , For each motor you need at near to motor or in control panel only please confirm
		E-stop shall be provisioned at every 15 m intervals at both sides of the			Either 0 or 1 category can be used

NOTE

1. Deviations mentioned in this sheet shall be allowed SUBJECT to Client / Consultant Approval in writing

2. Please note that Deviations not mentioned in this sheet will not be accepted at any stage