The contents of this catalogue (pictures, technical descriptions, illustrations) are the exclusive property of BFT s.p.a. Reproduction forbidden in any form or medium. All rights reserved copyright 2011.
The data in this publication are to be considered as indicative. BFT reserves the right to make any changes whatsoever without prior notice.

D832510 00203

Bft Spa
Via Lago di Vico, 44
36015 Schio (VI)
T +39 0445 69 65 11
F +39 0445 69 65 22

→ www.bft.it

Accessories

Radius B lta

Blinker with built-in antenna for 24V or 230V motors.



230 V D113748 00002
24 V D113748 00003

Ipnos B ltb

Blinker with built-in antenna for 24V motors. LED Technology.



24 V D113783

Mitto B Rcb

Two and four-channel 433 MHz rolling code transmitter



2 Channels D111904
4 Channels D111906

Kleio B Rca

Two and four-channel 433 MHz rolling code transmitter. "Soft touch" finish



2 Channels D111888
4 Channels D111890

Mitto B Rcb Replay



2 Channels D111905
4 Channels D111907

Two and four-channel 433 MHz copyable with rolling code transmitter

Cellula 130



P111273

Set of self-aligning wall-mount photocells (range 24 m) Power supply 24V ac/dc.

Cellula 180



P111452

Set of wall-mount adjustable (180° horiz./20° vert.) photocells (range 30 m). Power supply 24V ac/dc.

Tango cover



P111454

Anodised aluminium vandal-proof cover for Tango and Cellula 180 photocell.

Kits

Kit Deimos 300 bt

Up to 300 kg - Voltage 24V



R925247 00002

The KIT includes:

→ 1 Deimos 300 bt operator, with built-in control unit and rolling code receiver.
→ 2 Mitto B Rcb 4 12V, four-channel rolling code transmitter.
→ 1 Cellula 130, set of photocells.
→1 Radius B lta, 24V blinker with built-in antenna.

Kit Deimos bt

Up to 500 kg - Voltage 24V



R925229 00002

The KIT includes:

→ 1 Deimos bt operator, with built-in control unit and rolling code receiver.
→ 2 Mitto B Rcb 4 12V, four-channel rolling code transmitter.
→ 1 Cellula 130, set of photocells.
→1 Radius B lta, 24V blinker with built-in antenna.

Kit Deimos

Up to 500 kg - Voltage 230V



R925227 00002

The KIT includes:

→ 1 Deimos operator, with built-in control board and rolling code receiver.
→ 2 Mitto B Rcb 4 12V, four-channel rolling code transmitter.
→ 1 Cellula 130 set of photocells..
→ 1 Radius B lta, 230 V blinker with built-in antenna.

Kit Deimos 700

Up to 700 kg - Voltage 230V



R925243 00002

The KIT includes:

→ 1 Deimos 700 operator, with built-in control unit and rolling code receiver.
→ 2 Mitto B Rcb 4 12V, four-channel rolling code transmitter.
→ 1 Cellula 130, set of photocells.
→ 1 Radius B lta, 230V blinker with built-in antenna.

Kit Ares 1000

Up to 1000 kg - Voltage 24V



R925273 00001

The KIT includes:

→ 1 Ares 1000 operator, with built-in control unit and rolling code receiver.
→ 2 Mitto B Rcb 4 12V, four-channel rolling code transmitter.
→ 1 Cellula 130, set of photocells.
→ 1 Radius B lta, 24V blinker with built-in antenna.

*See specific illustrative brochure for information on the Fast-Net Easy Bus and Aliseo lines.

SLIDING GATES

Sliding gate automation systems



tuned to you

RESIDENTIAL USE

Deimos

Sliding gate electromechanical operators



- 230V electromechanical operators for residential use for gates up to 800 kg.
- Electromechanical spring-loaded or proximity limit switches (Prox).
- Control unit (ALPHA) with built-in receiver.

DESCRIPTION	VOLTAGE	GATE MAX WEIGHT	CONTROL UNIT	OPENING SPEED	IMPACT REACTION	USE
	(V)	(Kg)		(m/min)		
Deimos P925197 00001	230	500	Alpha (built-in)	8.5	mechanical clutch	semi-intensive
Deimos prox P925197 00003	230	500	Alpha (built-in)	8.5	mechanical clutch	semi-intensive
Deimos 700 P925196 00001	230	700	Alpha (built-in)	8.5	mechanical clutch	semi-intensive
Deimos 800 f P925200 00002	230	800	Alpha (built-in)	8.5	mechanical clutch	semi-intensive

RESIDENTIAL USE

Deimos bt

Sliding gate electromechanical operators



- 24V electromechanical operator for intensive use for gates up to 500 kg.
- Electromechanical spring-loaded, inductive (Prox), encoder (300) limit switches and electronic slowdown system.
- Control unit with D-Track torque control system and built-in receiver.

DESCRIPTION	VOLTAGE	GATE MAX WEIGHT	CONTROL UNIT	OPENING SPEED	IMPACT REACTION	USE
	(V)	(Kg)		(m/min)		
Deimos 300 bt P925209 00002	24	300	HQSC-300 (built-in)	13	D-track	intensive
Deimos bt P925178 00005	24	500	HQSC-D (built-in)	12	D-track	intensive
Deimos bt prox P925178 00006	24	500	HQSC-D (built-in)	12	D-track	intensive

RESIDENTIAL, LIGHT COMMERCIAL, COMMERCIAL AND INDUSTRIAL USE

Ares

Sliding gate electromechanical operators



- 24V electromechanical operator for intensive use, for gates up to 1500 kg.
- Electromechanical spring-loaded or proximity limit switches (Prox.) and electronic slowdown system.
- Control unit (Hqsc-d ARES) with D-Track torque control system and built-in receiver.

DESCRIPTION	VOLTAGE	GATE MAX WEIGHT	CONTROL UNIT	OPENING SPEED	IMPACT REACTION	USE
	(V)	(Kg)		(m/min)		
Ares 1000 P926183 00002	24	1000	HQSC-D ARES (built-in)	9	D-track	Intensive
Ares 1000 prox P926183 00004	24	1000	HQSC-D ARES (built-in)	9	D-track	Intensive
Ares 1500 P926182 00002	24	1500	HQSC-D ARES (built-in)	9	D-track	Intensive
Ares 1500 prox P926182 00004	24	1500	HQSC-D ARES (built-in)	9	D-track	Intensive

RESIDENTIAL, LIGHT COMMERCIAL, COMMERCIAL AND INDUSTRIAL USE

Icaro n

Sliding gate electromechanical operators



- 230V electromechanical operator for very intensive use, for gates up to 2000 kg (1000 kg Icaro n V).
- Electromechanical spring-loaded or proximity limit switches (Prox.) and electronic slowdown system.
- Control unit (Leo b cbb) with D-Track torque control system and encoder and built-in receiver.

DESCRIPTION	VOLTAGE	GATE MAX WEIGHT	CONTROL UNIT	OPENING SPEED	IMPACT REACTION	USE
	(V)	(Kg)		(m/min)		
Icaro n P925211 00002	230	2000	Leo b cbb (built-in)	9	D-TRACK	Very intensive
Icaro n prox P925213 00002	230	2000	Leo b cbb (built-in)	9	D-TRACK	Very intensive
Icaro n V P925212 00002	230	1000	Leo b cbb (built-in)	12	D-TRACK	Very intensive

INDUSTRIAL USE

Sp3500

Sliding gate electromechanical operators



- 400/230 V 3 ph electromechanical operator for very intensive use, for gates up to 3500 kg.
- Electromechanical lever operated limit switches and Sirio Tel control unit.
- New release system with ball bearing on pinion for maximum ease of operation.

DESCRIPTION	VOLTAGE	GATE MAX WEIGHT	CONTROL UNIT	OPENING SPEED	USE
	(V)	(Kg)		(m/min)	
Sp3500 P925207 00002	230 3 ph	3500	Sirio tel (built-in)	10.5	Very intensive
Sp3500 P925207 00001	400 3 ph	3500	Sirio tel (built-in)	10.5	Very intensive

tuned to you



www.bft.it

Bft and me, always in harmony.

tuned to you