NIHVA
NIHVA TECHNOLOGIES PVT. LTD.

Product- Acoustic sliding folding panel
Size- Opening width 14.5meter X Opening Height 4.5 meter
No of Panel- 12
Noise control – 50DB

Product Description

Track and Rollers: Top hung system with track and heavy duty roller system. Supplied with necessary track plates, track strips, threaded rods, nuts and washers, alignment pins etc. Tracks are supported by adjustable steel hanger brackets connected to structural support pairs of 12mm diameter threaded rods. Brackets supports the load bearing surface of the track. Track consists of natural architectural-grade aluminum alloy capable to bear the per panel load of 800 Kgs. The transfer areas are provided with aluminum junctions, switches and curves to ensure smooth transition of panels in the parking. The trolley is made of steel and provided with stainless steel rollers to ensure durability and smooth operation held with the 16mm bolt connected to the frame.

Suspension System: The ceiling track is to be fixed with an adjustable steel suspension of threaded rods. This steel suspension should be adjustable to ensure absorbtion of the eventual deflection of the ceiling. The threaded rods should be protected against corrosion.

Wall Panels: 110mm thick standard panels, filled with sound insulation materials are provided with MDF cover boards. The panels are interconnected by means of a concave / convex interlocking aluminum anodized profiles provided with an integrated EPDM magnetic strip and a vinyl acoustic seal running along the height of the interlocking profile. The skeletal frame of each element is constructed of a non-deflecting zinc coated steel tube with the aluminum anodized edge protecting profiles on both sides of the steel frame, bolted together. The cover boards are of 16mm thick MDF board, held in acoustic free suspension with the skeletal frame and within the side profiles. Each panel to have top and bottom operable EPDM pressure seals operated by a crank handle to ensure optimum contact pressure of 1500N. The system is equipped with an adjusting panel at one end of the wall. This panel normally at the closing end of the wall has a telescopic adjusting panel built with the same materials as the other panels and is operated, together with the top and bottom seals, by an internal three-way spindle mechanism. The telescopic sliding element stroke is 120 mm. There are aluminum profiles provided on both sides of the walls for better acoustics. In case of a provision of a door within the wall, the door frame jambs is provided with retractable seals for complete and tight closure of the door panel to the floor. In case of a provision of double door within the wall, there is a provision of active and inactive leaves for the door. Rrecessed door handles in

satin stainless steel finish are provided for the doors.

MANUAL OPERATION: Each element has a spindle mechanism driven manually with the help of a bayonet connected crank handle mechanism to operate top and bottom retractable seals simultaneously.

Sonic Barrier above main track line consists of one layer of gypsum board on both sides dully filled in with 48-50 density of Rockwool.

Certification: The wall is provided with an acoustic certificate for the required sound insulation by an internationally accredited standard third party laboratory. The certification is in accordance with ISO 140-3 or EN20140.