NIHVA
NIHVA TECHNOLOGIES PVT. LTD.

Technical Specification: - RP300 Albany German Make (100% Imported)

Door type	High-speed roller door Rapid Protect 300
Daylight width	1500 mm
Daylight height	2500 mm
Qty	1 Nos
Door control system	MCC Vector Control - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	2,4 m/s
Max. Closing Speed	1,7 m/s
Control box position	Mounted next to the drive unit
Control system position	Right
Motor Position	Right
Wind class	1
Side frame version	Aluminum
Bottom Plate	Delivered without bottom plates
Bottom profile	Aluminum
Safety contact edge	Pre running photocell at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Plus
Door curtain color	Blue, similar to RAL 5002
Silicone free	Silicone free
Window type	Window 700X500 mm, type anti UV
Window Quantity	1
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminum
MCC type	Standard version
MCC-display position	Inside side frame, drive side
MCC display type	Display delivered separately, not mounted
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Dry contact	Dry contacts for signal door open / closed and door in operation
Interface card	Interface card
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
Cable marking	Including cable and component marking
CE – Sign	Yes
Warranty	1 Year