Motorized Single Leaf Sliding gate (Grill & Spike) with inbuilt wicket gate

Sr .No.	Specification	Motorized Single Leaf Sliding gate (Grill & Spike) with inbuilt wicket gate
1	**Door type**	Motorized Single Leaf Sliding gate (Grill & Spike) with inbuilt wicket gate
2	**Clear Opening gate dimension**	(W) 4550 mm X (H) 2470 mm
3	**Master Leaf Size**	5650 X 2470 mm
4	**Opening Direction**	Horizontal (inside) - from left to right
5	**Mounting Location area**	Inside area
6	**Design Pattern**	Standard Tubular Design Pattern
7	**Outer Frame Tube Sizes**	60 x 60 x 2.6 mm MS Sq Tube
8	**Internal Vertical Tube Sizes**	40 x 40 x 2.6 mm MS Sq Tube
9	**For Safety Post tube sizes**	60 x 60 x 2.6 mm MS Sq Tube
10	**No of Safety Post**	04 Nos of Safety post with Nylon Roller
11	**Bottom Rail on ground**	dia 20 mm round bright bar with heavy duty support ISMB 100 X 50 Beams
12	**Bottom Rollers**	Heavy Duty Bottom Wheel With both side Bearings
13	**Guide Rollers supporter during Gate movement**	Nylon Rollers with Bearings both side mounted on column for support smooth movement of gate
14	**Painting**	PU paint
15	**Control Panel**	1 No Operating Station.
16	**Operation**	By Electric Motor - Rack and Pinion Mechanisam
17	**Included Accessories**	1. Limit Switch for Cut out when Gate is fully Closed
		2. Flashing Light
		3. Remote - 02 Nos
		4. Photocell
17	**Cladding**	One Side 12 mm thk shera board (Inside) & 1.2 mm MS Sheet on outside - Horizontal
18	**Grill Area**	500 mm Height
19	**Spike**	On the top of the gate -as per reference drawing

Kindly note that there should be provision for manual lock inside/outside, in case the automation is non-functional