# Preventive Maintenance Manufacturer's Specification

ASSA ABLOY

ASSA ABLOY Entrance Systems

The global leader in door opening solutions

## Enhance the durability of your High Performance Door Albany RR600

Key benefit

Safety

Cost-Savings

Just as a car's tires and oil must be changed regularly, your Albany High Performance Doors have key components that periodically need replacing. Whether it's a spring or a sprocket, changing them before they break is an integral part of Pro-Active Care.

We at ASSA ABLOY Entrance Systems believe in Pro-Active Care. Letting us replace components before they fail keeps your warranty valid and your equipment compliant with regulations. Even more importantly, it ensures the safety and functionality of your equipment, so that you can avoid accidents and losses in productivity.



***Instructions for table usage:***

**Qualified person**
The manufacturer's recommendation for exchange of components is subject to the findings of a qualified person. We strongly recommend that inspections are performed by a qualified person within the recommended service intervals (according to the user manual of the door).

**Recommendations for exchange**
The manufacturer's recommendations are based on a door with average size, installed under regular environmental conditions. Doors dimensioned close to maximum size of the door type or doors installed in harsh environmental conditions, need particular observation by a qualified person as the recommended intervals might be shorter.

Components specified as wear and tear related do not have a recommended exchange interval, indications for exchange or wear can be derived from the corresponding fact sheets.

Subject to technical modifications without notice. Errors and omissions excepted.

ASSA ABLOY ENTRANCE SYSTEMS
Maintenance & Modernization

# Preventive Maintenance
# Manufacturer's Specification

ASSA ABLOY

## Albany RR600

| Product group | Description | 100.000 cycles | 200.000 cycles | 300.000 cycles | 500.000 cycles | 1.000.000 cycles | 5 years | 10 years | wear / tear related |
|---|---|---|---|---|---|---|---|---|---|
| **Actuators** | Photocell receiver re / tr | | | | | | | ● | |
| | Safety photocell re / tr | | | | | | | ● | |
| **Brush** | Brush strip (front & back) | | | | ● | | | | |
| **Sealing** | Top roll sealing | | | | ● | | | | |
| **Cable chain** | Cable chain, complete with cable and bracket | | | | ● | | | | |
| **Counterbalancing** | Cable pulley with bearings complete | | ● | | | | | | |
| | Spring A - E, M/N | | | | ● | | | | |
| | Steel cable, w/o automatic crash | | ● | | | | | | |
| | Steel cable, with automatic crash | ● | | | | | | | |
| **Curtain tension** | Deflection spring | | ● | | | | | | |
| | Rope for curtain tension | | ● | | | | | | |
| | Rope pulley | | ● | | | | | | |
| | Spring d=5mm | | ● | | | | | | |
| **Curtain** | Curtain | | | | | | | | ● |
| | Set of wind tabs | | | | ● | | | | |
| **Top roll** | Bearing d 30 | | | | ● | | | | |
| | Top roll | | | | ● | | | | |
| **Bottom profile** | Rubber profile with contact strip | | | | | | ● | | |
| | Spiral cable | | | ● | | | | | |
| **Crash** | Proximity switch | | | | | | | ● | |
| | Wheel break-away | | | | ● | | | | |
| **Sliding/Guiding** | Bell mouth front/back | | | | ● | | | | |
| | Rubber damper | | | | | | ● | | |
| **Switch** | Proximity switch | | | | | | | ● | |
| **Drive unit** | Drive unit - frequency converter | | | | | ● | | | |
| | Junction box | | | | | | | ● | |
| | Limit switch | | | | | | | ● | |
| **Brake** | Brake - frequency converter | | | | | ● | | | |
| **Damper** | Vibration absorber | | | | ● | | | | |
| **BBS** | Pulley wheel for rope BBS | | | | | | | | |
| | Rope white, d=5 mm, L=14 M | | | | ● | | | | |
| | Rubber, bottom beam stop | | | | | | ● | | |
| | Steel cable, BBS | | | | ● | | | | |
| **Electronic / PCB** | Display unit compl,ete, MCC display | | | | | | ● | | |
| | Foilkey, MCC display | | | | | | ● | | |

≤150.000 cycles: ±10.000 cycles; >150.000 cycles: ±20.000 cycles
≤5 years: ±6 months; >5 years: ±1 year

Technical data subject to change without notice

© ASSA ABLOY Entrance Systems AB PL.MAN/RR600/DEU.EN-1.1/1504 / 64 100 483

ASSA ABLOY ENTRANCE SYSTEMS
Maintenance & Modernization