NIHVA

Fire Door



We Make Possible



COMMERCIAL DOORS



Doors For Fire Applications :

1. Doors as per IS standards (CBRI) :
   - Stability & Integrity : 60 & 120 minutes
   - Stability, Integrity & Insulation : 60* & 120* minutes
2. Doors as per ANSI standards

*The fire rating to be 45, 60, 90, 120 and 180 minutes.



Doors For Clean Room Applications :

- Doors with flush view glass
- Aluminum doors
- GRP doors
- Sliding doors (Manual / Auto)
- Glazed windows (Single / Double glazed)

Doors For General Applications :

- Flush doors
- Doors with view glass
- Doors with louvers



Products For Special Applications :

1. Access doors (Fire / Non fire rated)
2. Fully glazed doors (Fire / Non fire rated)
3. Double acting doors
4. Double egress doors
5. Dutch doors
6. Sliding doors (Manual / Auto)
7. Foldable doors
8. Sliding folding doors
9. Heavy duty double doors for industrial applications (With / Without man door)
10. Acoustic doors
11. Transom doors
12. Aluminum profile doors
13. Hollow metal door frames
14. Toilet partitions

*Under Testing

DOORS FOR FIRE APPLICATIONS







SPECIFICATIONS

- **Door Skin Material**
  Galvanized steel as per IS 277 / Stainless steel 304 grade, No.4 finish.
- **Door Skin Thickness**
  0.8mm / 1.2 mm / 1.6 mm.
- **Frame Material**
  Galvanized material as per IS 277 / Stainless steel 304 grade, No.4 finish.
- **Frame Sheet Thickness**
  1.2mm / 1.6mm / 2.0 mm.
- **Infill Materials**
  Honeycomb / Mineral wool / Steel stiffened.
- **Door Thickness**
  Minimum 47 mm.
- **View Glass**
  Single glazed with glass trim / bead. Size shall be minimum 150 mm to 450 mm in width, minimum 150 mm to 750 mm in height. However, the standard sizes are 150 x 750 mm, 200 x 300 mm, 300 x 300 mm, 350 x 750 mm, 450 x 750 mm. The glasses shall be fire rated.
- **Packing**
  The frame and shutters shall be wrapped with protective film and put into corrugated boxes. The boxes shall be crated or palletized depending on the quantity and mode of transport.
- **Frame Profile (Standard)**
  Single rebated frame shall be 100 x 58 mm and double rebated profile 150 mm x 58 mm. The frames are manufactured with mitre joints as a standard and in knock down condition.
- **Non Standard Frame Profiles**
  Non standard frame profiles can be manufactured on demand. The depth shall vary from 100 mm to 450 mm for single and double rebated frames.
- **Finish**
  Pure polyester powder coated to any RAL shade / wood stained to withstand 300 hours of salt spray.

Additional Features On Demand : Welded frames | Seamless shutters | Integral astragal

DOORS FOR GENERAL APPLICATIONS







SPECIFICATIONS

- **Door Skin Material**
  Galvanized steel as per IS 277 / Stainless steel 304 grade, No.4 finish.
- **Door Skin Thickness**
  0.8mm / 1.2 mm / 1.6 mm.
- **Frame Material**
  Galvanized material as per IS 277 / stainless steel 304 grade, No.4 finish.
- **Frame Sheet Thickness**
  1.2mm / 1.6mm / 2.0 mm.
- **Infill Materials**
  Honeycomb / Polyurethane foam / Mineral wool / Steel stiffened.
- **Door Thickness**
  Minimum 47 mm.
- **Finish**
  Pure polyester powder coated to any RAL shade / wood stained to withstand 300 hours of salt spray.
- **View Glass**
  Single glazed with glass trim / bead. Size shall be minimum 150 mm to 750 mm in width, minimum 150 mm to 1600 mm in height. However, the standard sizes are 150 x 750 mm, 200 x 300 mm, 300 x 300 mm, 350 x 750 mm, 450 x 750 mm.
- **Packing**
  The frame and shutters shall be wrapped with protective film and put into corrugated boxes. The boxes shall be crated or palletized depending on the quantity and mode of transport.
- **Frame Profile (Standard)**
  Single rebated frame shall be 100 x 58 mm and double rebated profile 150 mm x 58 mm. The frames are manufactured with mitre joints as a standard and in knock down condition.
- **Non Standard Frame Profiles**
  Non standard frame profiles can be manufactured on demand. The depth shall vary from 80 mm to 450 mm for single and double rebated frames.

Additional Features On Demand :

Welded frames | Seamless shutters | Integral astragal

SHADES / FINISHES

RAL 9016 Traffic White	RAL 5010 Gentian Blue	DL12CE
RAL 7035 Light Grey	RAL 3001 Signal Red	DL89CE

Door Type	Products		Door Opening Size - MM			
			Width		Height	
			Min.	Max.	Min.	Max.
Commercial Doors	Doors For General Applications	Single Shutter Door	450	1200	750	3000
		Double Shutter Door	800	2400	750	3000
	Doors For Clean Room Applications	Single Shutter Door	450	1200	750	3000
		Double Shutter Door	800	2400	750	3000
	Doors For Fire Applications (IS)	Single Shutter Door	450	1200	750	3000
		Double Shutter Door	800	2400	750	3000
	Doors For Fire Applications (ANSI)	Single Shutter Door	450	1200	750	3000
		Double Shutter Door	800	2400	750	3000

IRONMONGERY
























NIHVA

We Make Possible

Automation Solutions	Material Handling Equipments	Door Automation
Pick & Place Machines	Dock Levellers	High speed doors / Sectional doors
Manipulator /Air Balancer	Scissor lifts / Mobile ramp	Sliding doors / Folding Doors
Wireless Automation (M2M)	Dock Shelters / Dock Seals / Dock House	Fire rated - Mot. Rolling shutters / Sliding doors
SPM	Goods Lift	Hanger Doors / Extra large opening doors
Automation Softwares	Spiral Conveyors / Belt Conveyors	Boom barriers / Turnstiles / Bollards
Grease / Oil Separator	Telescopic Conveyors	Sliding / Cantilever Gates

International Business Partners

ALBANY ASSA ABLOY | MEGADOOR ASSA ABLOY | Crawford ASSA ABLOY | besam ASSA ABLOY | ACO

Head Office: G-Block, 1st Floor, Thermax Chowk, MIDC, Above Renault Showroom, Chinchwad, Pune - 411019

NIHVA

NIHVA Technologies Pvt. Ltd.

+91 2066 3040 33 +91 85 51091 333 sales@nihva.com www.nihva.com

NETWORKS

WEST	NORTH	SOUTH	EAST
Pune I Mumbai I Nashik I Nagpur Indore I Ahmedabad I Surat I Vadodara	Delhi I Chandigarh	Chennai I Hyderabad I Bengaluru	Kolkata I Bhubaneshwar