Product:

NIHVA - AssAabloy SL500 - Sliding Doors

Green Environmental Certification	ENVIRONMENTAL PRODUCT DECLARATION as per ISO 14025 and EN 15804
Complies with the following directives:	2014/30/EU Electro Magnetic Compatibility Directive (EMCD) & 2006/42/EC Machinery Directive (MD)
Harmonized European standards which have been applied:	EN 61000-6-2:2005 EN 61000-6-3:2007+A1 EN ISO 13849-1:2008 EN 16005:2012 EN 60335-1:2012 EN 60335-2-103 2003+A1:2009
Other standards or technical specifications, which have been applied:	> BBR -IEC 60335-2-103 ed.2 1:2011 > BVL - IEC 60335-1 ed.5:2010 > FCC 47 CFR Part 15 B DIN 18650-1/-2:2010 > UL 325
Operator dimensions (h) 150 mm x (d) 123 mm	Height x Depth
Power supply 100-240 VAC ±10% 50/60 Hz	100-240 VAC ±10% 50/60 Hz
Power consumption max.	250 W
Recommended maximum door weight	
Besam SL500-2 without break-out	200 kg/door leaf
Besam SL500-2 with break-out	100 kg/door leaf
Besam SL500-1 without break-out	240 kg
Besam SL500-1 with break-out	100 kg
Clear opening width (COW)	
Besam SL500-2	1000 – 3000 mm (bi-parting)
Besam SL500-1	800 – 3000 mm (single slide)
Open and closing speed Variable	up to 1.7 m/s (2 leaves)
Hold-open time	0 – 60 s
Ambient temperature	-20°C to +50°C
Relative humidity (noncondensing)	max 85%

Standard equipment	> Cover: clear anodized aluminium > Support beam with transmission > Electronic control unit with plug-in connections and > power supply
Accessories and options at extra	> Cover: Other anodizing options or painted in RAL colours > Door adaptor for doors up to 65 mm thick from other suppliers >Traffic-controlled opening width Synchronizing of two operators > Operation mode selectors > Electronic emergency opening or closing unit > Break-out doors > Emergency button > NIHVA-ASSA ABLOY motion and presence sensors > Electrical locking devices > Interlocking between operators > Key switch > Besam automatic door systems
Security - various Optiontins at extra	> Choose your security level by adding different features. > Unwanted guests are not an issue for the Besam SL500 through the use of different locking devices. > The operation mode selector can be set to meet your security needs during and outside business opening hours. > Interlocking facilities further enhance the security level.
different solutions as:	> additional sealing (Besam Tight Seal), > sustainable drive mode, > intelligent opening width depending on traffic, > inner- and outer door air locking, > timer settings and more.