Sr. No	Description	Albany make Machine Protection Door RP300
1	**Door version:**	Vertical Rapid Roller Door for machine protection.
2	**Daylight width**	2000mm
3	**Daylight Height**	2070mm
4	**Side Frames:**	Aluminum anodized two parts, to have easy access to switches and service.
6	**Door blade:**	Rolltex Plus Curtain (RAL 2009)
7	**Bottom beam**	Aluminium anodized.
8	**Drive unit:**	Drive unit IP 55, Motor on RH, with control cable (standard length = height of door)
9	**Opening / closing speed:**	Approx. max. 2,4 / 1,7 m/s
10	**Control system:**	MCC Frequency converterVector Control for opening/closing speed up to 2,4 / 1,4 m/s for door with safety contact edge, protection IP 55. Without display, interface card delivered separately, including power- and interface cable, with main switch in separate box.
11	**Power suppy:**	3L(N)PE 380/400/415/440/460 and 480 V, 50/60 Hz
12	**Safety features:**	Safety edge with cable chain integrated in side frames, door line photocell (Transmitter / Receiver) inside side frames, emergency crank and mechanical drop-down protection.
13	**Safety limit switch:**	1 Schmersal safety limit switch PL e EN ISO 13849-1, SIL 3 EN 62061 on drive side integrated in the side frame to save space.
14	**Window Type**	700 x 500 mm Anti UV Type
15	**Window Qty**	1 Nos for each door
16	**Accessories**	Remote Control
17	**Display**	Display "Up-Stop-Down"
18	**Motor Position**	Left Hand Side
19	**Interface Card**	MCC without display unit, with combibox in plastic (175x250x150 mm) with interface card and main switch included in combibox, including power- and interface cable.
20	**Top Roll material**	Aluminum
21	**Top Roll Cover**	Made of aluminum
22	**Motor Cover**	powder coated standard
23	**Packing**	Box, Heat Treated
24	**warranty**	1 Year
25	**CE Sign**	Yes
26	**Documentation language**	English
27	**Documentation Control System**	English
28	**MCC Display Language**	English