CONTROL UNITS
TECHNICAL SPECIFICATIONS







Model	ROBODOR MR380	ROBODOR DMC24	ROBODOR MR220
Use	Constant Speed Application Control Unit for Internal / External Doors	Adjustable Speed control of high-speed PVC and sectional for Internal / External Doors	Frequency converter technology control of high-speed PVC and sectional Internal / External Doors
Drive output	Drives up to 1 kW, Three Phase Asynchronous Motor	Drives up to 0.6 kW, Brushed DC Motor	Drives up to 1.5 kW, Three Phase Asynchronous Motor
Language	English\German\Turkish	English\German\Turkish	English\Turkish
Position Encoder	Absolute Digital Encoder\ Limit Switches	Absolute Digital Encoder	Absolute Digital Encoder
Operation	Automatic Opening and Closing LCD display provides information about door functions	Intelligent Crash Control Function Automatic Opening and Closing LCD Display to provide information on door functions	Automatic Opening and Closing LCD Display to provide information on door functions
Function	Automatic Timer Safety Edge Photo Eye Door Opening Count Information Interlocking System of Two Doors Door Position Detection	Membrane Open-Stop-Close Button Door Opening Count Information Integrated Power Factor Control Unit Programmable Relay (x3) Flashing/Traffic Light Automatic Timer Safety Edge Photo Eye Intelligent Battery Pack Unit Interlocking System of Two Doors	Membrane Open-Stop-Close Button Automatic Timer Safety Edge Photo Eye Programmable Relay (x3) Flashing/Traffic Light Door Opening Count Information Interlocking System of Two Doors Door Position Detection
Control Inputs	Membrane Open-Stop-Close Button External Open-Stop-Close, Push Button Pull Switch Microwave Radar Mushroom Push Button Radar Detector Induction Loop Detector Remote Control	Membrane Open-Stop-Close Button External Open-Stop-Close, Push Button Pull Switch Microwave Radar Mushroom Push Button Radar Detector Induction Loop Detector Remote Control	Membrane Open-Stop-Close Button External Open-Stop-Close, Push Button Pull Switch Microwave Radar Mushroom Push Button Radar Detector Induction Loop Detector Remote Control
Housing Dimensions	212 mm x 146 mm x 55 mm or 250 mm x 330 mm x 130 mm	250 mm x 330 mm x 130 mm	250 mm x 330 mm x 130 mm
Temperature Range	In operation : -10°C to +60°C In storage : -25°C to +70°C	In operation : -10°C to +50°C In storage : -25°C to +70°C	In operation : -10°C to +50°C In storage : -25°C to +70°C
Protection Grade	IP 54	IP 54	IP 54
Weight	Approx. 700 gr	Approx. 3150 gr	Approx. 2600 gr
Installation	Vertically on the wall, minimum height of 1100 mm	Vertically on the wall, minimum height of 1100 mm	Vertically on the wall, minimum height of 1100 mm