Nice IDOOR


Catalogue 2019 – industrial door operators + accessories



Nice IDOOR

Catalogue 2019 – industrial door operators + accessories

FOR SECTIONAL DOORS - SW/SD INDUSTRIAL DRIVES

						
	Power supply	**Limit switch type**	**Description** **Type - Nm - Rpm - Hollow shaft**	**Hand crank (KU)** **Code**	**Light chain (KE)** **Code**	**Manual release (E)** **Code**
Sectional drives	3 x 400 Vac	Encoder - 15 turns	SDN 70 Nm 24 rpm Ø25.4 mm	on demand	NDCMB054	on demand
			SD 100 Nm 24 rpm Ø25.4 mm	NDCM0006	NDCM0199	NDCM0074
			SD 120 Nm 20 rpm Ø25.4 mm	NDCM0111	NDCM0077	NDCM0046
			SD 140 Nm 20 rpm Ø25.4 mm	NDCM0211	NDCM0102	NDCM0158
			SD 140 Nm 20 rpm Ø31.75 mm	NDCM0007	NDCM0051	NDCM0081
		Mechanical - 15 turns	SDN 70 Nm 20 rpm Ø25.4 mm	on demand	NDCMB053	on demand
			SD 100 Nm 24 rpm Ø25.4 mm	NDCM0073	NDCM0022	NDCM0040
			SD 120 Nm 20 rpm Ø25.4 mm	NDCM0147	NDCM0301	NDCM0082
			SD 140 Nm 20 rpm Ø25.4 mm	NDCM0266	NDCM0296	On Demand
			SD 140 Nm 20 rpm Ø31.75 mm	NDCM0128	NDCM0120	On Demand
	1 x 230 Vac	Encoder - 15 turns	SWN 70 Nm 20 rpm Ø25.4 mm	on demand	NDCMB064	on demand
		Mechanical - 15 turns	SWN 70 Nm 20 rpm Ø25.4 mm	on demand	on demand	on demand

Nice IDOOR

Catalogue 2019 – industrial door operators + accessories

FOR SECTIONAL DOORS - SW/SD INDUSTRIAL DRIVES

TECHNICAL DATA

type	SWN-70-20	SDN-70-24	SD-100-24	SD-120-20	SD-140-20
shaft Ø (mm)	25.4				25.4/31.75
max. torque (Nm)	70		100	120	140
rated torque (Nm)	60		80	100	120
static safety torque (Nm)	450			600	
weight lifted *(kg)	250		300		550
speed (rpm)	20	24		20	
absorbed power (kW)	0,37				0,55
working voltage (V)	1~230	3~230/3~400			
frquency (Hz)	50				
cycles per hour	5	6	7	5	6
connection cable (no. Xmm²)	4x1.5mm² - 6x0.75mm² - 2x0.75mm²				
nominal currrent (A)	2,3	1,8	3,18	2,6	3,45
limit capacity (max. turns hollow shaft)	15				
operating temperature (°C)	-5 ÷ +40				
noise [db(A)]	<70				
protection class (IP)	54				
weight (kg)	13,2		11,1	11	12

*for balanced door with 1-4 compensation springs with a rope 160mm rope drum, obsere the permitted cables forces, tha danger warnings and the general rules of safety!

Nice IDOOR

Catalogue 2019 – industrial door operators + accessories

FOR ROLLING SHUTTERS - RDF INDUSTRIAL DRIVES

						
	Power supply	Limit switch type	Description		Hand crank (KU)	Light chain (KE)
			Type - Nm - Rpm - Hollow shaft		Code	Code
Rolling shutter drives	3 x 400 Vac	Encoder - 15 turns	RDF 140 Nm 20 rpm Ø30 mm		NDCM1074	NDCM0206
		Encoder - 10 turns	RDF 220 Nm 15 rpm Ø30 mm		NDCM1076	NDCM0205
			RDF 290 Nm 15 rpm Ø30 mm		NDCM1071	NDCM1069
			RDF 380 Nm 15 rpm Ø40 mm		NDCM1072	NDCM1077
			RDF 450 Nm 15 rpm Ø40 mm		NDCM1073	NDCM1068
			RDF 550 Nm 12 rpm Ø40 mm		NDCM1075	NDCM0208
		Encoder - 40 turns	RDF 750 Nm 9.5 rpm Ø40 mm + BRAKE		NDCM1042	NDCM1041
		Encoder - 10 turns	RDF 850 Nm 10 rpm Ø55 mm + BRAKE		NDCM1045	NDCM0200
			RDF 1100 Nm 10 rpm Ø55 mm + BRAKE		NDCM1019	NDCM1018
			RDF 1400 Nm 7 rpm Ø55 mm + BRAKE		NDCM1032	NDCM1031
		Mechanical - 15 turns	RDF 140 Nm 20 rpm Ø30 mm		On demand	NDCM1078
		Mechanical - 10 turns	RDF 220 Nm 15 rpm Ø30 mm		On demand	NDCM0306
			RDF 290 Nm 15 rpm Ø30 mm		NDCM1086	NDCM1054
			RDF 380 Nm 15 rpm Ø40 mm		NDCM0129	NDCM0107
			RDF 450 Nm 15 rpm Ø40 mm		On demand	NDCM1053
			RDF 550 Nm 12 rpm Ø40 mm		NDCM0005	NDCM0039
		Mechanical- 40 turns	RDF 750 Nm 9.5 rpm Ø40 mm + BRAKE		NDCM1044	NDCM1043
		Mechanical - 10 turns	RDF 850 Nm 10 rpm Ø55 mm + BRAKE		NDCM1049	NDCM1048
			RDF 1100 Nm 10 rpm Ø55 mm + BRAKE		NDCM1085	NDCM1022
			RDF 1400 Nm 7 rpm Ø55 mm + BRAKE		NDCM1036	NDCM1035

Nice Industrial Doors

Catalogue 2019 – industrial door operators + accessories

FOR ROLLING SHUTTERS - RDF INDUSTRIAL DRIVES

					
	Power supply	Limit switch type	Description	Hand crank (KU)	Light chain (KE)
			Type - Nm - Rpm - Hollow shaft	Code	Code
Rolling shutter fast drives 24 rpm	3 x 400 Vac	Encoder - 15 turns	RDF 140 Nm 20 rpm Ø30 mm	NDCM1074	NDCM0206
		Encoder - 40 turns	RDF 250 Nm 24 rpm Ø 40 mm with brake	NDCM0198	NDCM0297
			RDF 350 Nm 24 rpm Ø 40 mm with brake	On demand	NDCM1009
			RDF 500 Nm 24 rpm Ø 40 mm with brake	NDCM1011	NDCM1010
			RDF 750 Nm 24 rpm Ø 55 mm with brake	NDCM1070	NDCM1039
			RDF 950 Nm 24 rpm Ø 55 mm with brake	NDCM0193	NDCM1083
			RDF 1250 Nm 24 rpm Ø 55 mm with brake	On demand	NDCM1084
			RDF 1400 Nm 24 rpm Ø 55 mm with brake	On demand	On demand
		Mechanical - 15 turns	RDF 140 Nm 20 rpm Ø30 mm	On demand	NDCM1078
		Mechanical - 40 turns	RDF 250 Nm 24 rpm Ø 40 mm with brake	On demand	On demand
			RDF 350 Nm 24 rpm Ø 40 mm with brake	NDCM0227	On demand
			RDF 500 Nm 24 rpm Ø 40 mm with brake	On demand	On demand
			RDF 750 Nm 24 rpm Ø 55 mm with brake	NDCM1040	On demand
			RDF 950 Nm 24 rpm Ø 55 mm with brake	NDCM1052	On demand
			RDF 1250 Nm 24 rpm Ø 55 mm with brake	On demand	On demand
			RDF 1400 Nm 24 rpm Ø 55 mm with brake	On demand	On demand

Nice IDOOR

Catalogue 2019 – industrial door operators + accessories

FOR ROLLING SHUTTERS - RDF INDUSTRIAL DRIVES

Max. shutter weight (kg):

Gearmotor		Steel pipe EN 10220 (mm)										
	RDF series	**101,6 x 3,6**	**108,0 x 3,6**	**133,0 x 4**	**159,0 x 4,5**	**177,8 x 5**	**193,7 x 5,4**	**219,1 x 5,9**	**244,5 x 6,3**	**273,0 x 6,3**	**298,5 x 7,1**	**323,9 x 7,1**
	RDF-140-20	125	122	115	106	99	94	85	77	69	64	59
	RDF 180-15	166	163	153	141	133	126	113	102	92	85	79
	RDF-220-15	208	204	192	177	166	157	142	128	115	106	98
	RDF-290-15	260	255	240	221	207	197	177	160	144	133	123
	RDF-380-15	375	368	335	319	299	284	255	231	208	192	177
	RDF-450-15	416	408	383	354	332	315	284	256	231	213	197
	RDF-550-12	468	460	431	399	373	355	319	289	260	240	222
	RDF-250-24	239	235	220	203	190	181	163	147	133	122	113
	RDF-350-24	322	316	297	274	257	244	220	199	179	165	153
	RDF-500-24	468	460	431	399	373	355	319	289	260	240	222
	RDF-750-24	677	664	623	576	539	513	461	417	376	346	321
	RDF-950-24	885	868	815	753	705	671	603	545	492	453	419
	RDF-750-9.5	781	715	671	620	581	552	497	449	405	373	345
	RDF-1250-24	1145	1124	1055	975	913	869	781	706	637	586	543
	RDF-1400-24	1354	1324	1247	1152	1079	1026	923	835	753	693	642
	RDF-850-10	-	-	-	664	622	592	532	481	434	400	370
	RDF-1100-10	-	-	-	842	788	750	675	610	550	506	469
	RDF-1400-7	-	-	-	1063	1038	987	888	770	724	666	617

The table applies only to section bars with a single wall (thickness 20 mm). The dimensions must be taken into account for the winding if section bars with double wall, with greater thickness or higher are used.

In this case higher torque applies after 1-2 turns.
A 20% friction loss is considered for the normal rolling shutters in the table.

It is generally advisable to check the door proportions when there are coverings, section bars with double wall, doors higher than normal or in the case of particular entry situations that could require other force ratios or cause additional friction losses (e.g. doors that are wider than the height), for example.

Nice IDOOR

Catalogue 2019 – industrial door operators + accessories

FOR ROLLING SHUTTERS - RDF INDUSTRIAL DRIVES

Technical data

Model RDF-	140-20	220-15	290-15	380-15	450-15	550-12	750-9,5
Shaft Ø (mm)	30			40			
Max. torque (Nm)	140	220	290	380	450	550	750
Rated torque (Nm)	120	200	250	360	400	450	700
Output rpm	20	15	15	15	15	12	9,5
Motor power (kW)	0,55	1,1	1,1	1,5	1,5	1,5	1,5
Limit switch rpm	15	10-20	10-20	10-20	10-20	10	40
Working voltage (V/Hz)	3x230 V / 3x400 V 50 Hz						
Duty Cycle	S 3 - 60%						
Connection cable (no. x mm²)	5 x 1,5						
Operating temperature (°C)	-5 ÷ +40						
Noise dB(A)	<70						
Protection rating (IP)	IP 54						
Weight (kg)	12,4	22	24	28,9	27,7	27,7	35

Model RDF-	850-10	1100-10	1400-7	250-24	350-24	500-24	750-24	950-24	1250-24	1400-24
Shaft Ø (mm)	55			40			55			
Max. torque (Nm)	850	1100	1400	250	350	500	750	950	1250	1400
Rated torque (Nm)	700	950	1250	230	310	450	650	850	1100	1250
Output rpm	10	10	7	24	24	24	24	24	24	24
Motor power (kW)	2,2	2,2	2,2	1,1	1,5	2,2	2,2	3	4	5,5
Limit switch rpm	10-40	10-40	10-40	10-40	10-40	10-40	10-40	10-40	10-40	10-40
Working voltage (V/Hz)	3x230 V / 3x400 V 50 Hz									
Duty Cycle	S 3 - 60%									
Connection cable (no. x mm²)	5 x 1,5									
Operating temperature (°C)	-5 ÷ +40									
Noise dB(A)	<70									
Protection rating (IP)	IP 54									
Weight (kg)	51,7	51,9	58	24,1	29,2	32,7	51,9	61	63	65

Gearmotors with integrated anti-fallback device, independent of speed and position.

Nice IDOOR

Catalogue 2019 – industrial door operators + accessories

FOR HIGH SPEED DOORS - HDF/HDFI Industrial drives without frequency-inverter



	Power supply	Limit switch type	Description Type - Nm - Rpm - Hollow shaft	Hand crank (KU) Code
High speed drives	3 x 400 Vac	Encoder - 15 turns	HDF 30 Nm 120 rpm Ø30 mm with brake	NDCM0272
			HDF 45 Nm 95 rpm Ø30 mm with brake	NDCM0247
		Encoder - 20 turns	HDF 70 Nm 135 rpm Ø40 mm with brake	On demand
			HDF 95 Nm 95 rpm Ø40 mm with brake	NDCM0148
		Encoder - 15 turns	HDF 120 Nm 70 rpm Ø40 mm with brake	On demand
		Encoder - 10 turns	HDF 135 Nm 135 rpm Ø40 mm with brake	On demand
		Encoder - 20 turns	HDF 180 Nm 95 rpm Ø40 mm with brake	NDCM0057
		Encoder - 10 turns	HDF 190 Nm 45 rpm Ø40 mm with brake	On demand
			HDF 230 Nm 70 rpm Ø40 mm with brake	On demand
		Encoder - 40 turns	HDF 350 Nm 45 rpm Ø40 mm with brake	On demand
		Mechanical - 15 turns	HDF 30 Nm 120 rpm Ø30 mm with brake	NDCM0052
			HDF 45 Nm 95 rpm Ø30 mm with brake	NDCM0098
		Mechanical - 20 turns	HDF 70 Nm 135 rpm Ø40 mm with brake	On demand
			HDF 95 Nm 95 rpm Ø40 mm with brake	NDCM0099
		Mechanical - 15 turns	HDF 120 Nm 70 rpm Ø40 mm with brake	On demand
		Mechanical - 10 turns	HDF 135 Nm 135 rpm Ø40 mm with brake	NDCM0055
		Mechanical - 20 turns	HDF 180 Nm 95 rpm Ø40 mm with brake	NDCM0167
		Mechanical - 10 turns	HDF 190 Nm 45 rpm Ø40 mm with brake	On demand
			HDF 230 Nm 70 rpm Ø40 mm with brake	On demand
		Mechanical - 40 turns	HDF 350 Nm 45 rpm Ø40 mm with brake	NDCM0030

Nice IDOOR

Catalogue 2019 – industrial door operators + accessories

FOR HIGH SPEED DOORS - HDF/HDFI Industrial drives with frequency-inverter



Power supply	Limit switch type	Description Type - Nm - Rpm - Hollow shaft	Hand crank (KU) Code
1 x 230 Vac	Encoder - 15 turns	HDFI 30 Nm 120 rpm Ø30 mm with brake	NDCM0186
		HDFI 45 Nm 95 rpm Ø30 mm with brake	NDCM0259
	Encoder - 20 turns	HDFI 70 Nm 135 rpm Ø40 mm with brake	NDCM0260
		HDFI 95 Nm 95 rpm Ø40 mm with brake	NDCM0187
	Encoder - 15 turns	HDFI 120 Nm 70 rpm Ø40 mm with brake	On demand
	Encoder - 10 turns	HDFI 135 Nm 135 rpm Ø40 mm with brake	On demand
	Encoder - 20 turns	HDFI 180 Nm 95 rpm Ø40 mm with brake	NDCM0261
	Encoder - 10 turns	HDFI 190 Nm 45 rpm Ø40 mm with brake	On demand
		HDFI 230 Nm 70 rpm Ø40 mm with brake	On demand
	Encoder - 40 turns	HDFI 350 Nm 45 rpm Ø40 mm with brake	NDCM0250

Nice IDOOR

Catalogue 2019 – industrial door operators + accessories

FOR HIGH SPEED DOORS - HDF/HDFI Industrial drives

Selection guide of the acceptable maximum weights according to the model and winding pipe with inverter at 50 Hz

Steel pipe EN 10220 (mm)	HDF series											
	45-95	120-95	30-120	90-120	190-45	360-45	120-70	230-70	95-95	180-95	70-135	135-135
108,0 x 3,6	46	46	31	93	187	280	93	187	98	187	612	820
133,0 x 4,0	37	37	25	76	152	228	76	152	80	152	499	668
159,0 x 4,5	31	31	21	64	128	191	64	128	67	128	418	560
177,8 x 5,0	28	28	19	57	114	171	57	114	60	114	375	502
193,7 x 5,4	26	26	18	53	105	158	53	105	55	105	344	461
219,1 x 5,9	23	23	15	46	93	139	46	93	49	93	305	405

The weight table is based on a friction value of 20%, with a sheet thickness of 2 mm.
For frequencies greater than 50 Hz the maximum weight is reduced by 5% for each frequency increase of 10%; the values shown in the table are calculated for operation with max. 80 Hz.

Please note:
If gearmotor operation without inverter is planned, it must be clearly indicated in the order because in this case it may be necessary to equip the gearmotors with a more powerful brake.

Nice IDOOR

Catalogue 2019 – industrial door operators + accessories

FOR HIGH SPEED DOORS - HDF/HDFI Industrial drives

Technical data

Type	HDF-45-95	HDF-120-95	HDF-30-120	HDF-90-120	HDF-190-45	HDF-350-45
Shaft Ø (mm)	25/30	25/30	25/30	25/30	40	40
Max. torque (Nm)	45	120	33	90	190	350
Rated torque (Nm)	36	100	30	80	170	300
Speed at 50 Hz (rpm)	95	95	120	120	45	45
Motor power (kW)	0,75	1,1	0,75	1,1	1,5	2,2
Limit switch rpm	15	15	15	15	10-20	10-20
Working voltage (V/Hz)	3x230 V / 3x400 V 50 Hz					
Duty Cycle	S 3 - 60%					
Connection cable (no. x mm²)	5 x 1,5					
Operating temperature (°C)	-5 ÷ +40					
Noise dB(A)	<70					
Protection rating (IP)	IP 54					
Weight (kg)	16,9	16,9	15,8	15,8	30,5	34

Type	HDF-120-70	HDF-230-70	HDF-95-95	HDF-180-95	HDF-70-135	HDF-135-135
Shaft Ø (mm)	40	40	30/40	30/40	30/40	30/40
Max. torque (Nm)	120	230	95	180	70	135
Rated torque (Nm)	100	200	90	150	55	100
Speed at 50 Hz (rpm)	70	70	95	95	135	135
Motor power (kW)	1,5	2,2	1,5	2,2	1,5	2,2
Limit switch rpm	10-20	10-20	10-20	10-20	10-20	10-20
Working voltage (V/Hz)	3x230 V / 3x400 V 50 Hz					
Duty Cycle	S 3 - 60%					
Connection cable (no. x mm²)	5 x 1,5					
Operating temperature (°C)	-5 ÷ +40					
Noise dB(A)	<70					
Protection rating (IP)	IP 54					
Weight (kg)	30,5	34	30,5	34	30,5	34

Nice IDOOR

Catalogue 2019 – industrial door operators + accessories

INDUSTRIAL CONTROL UNITS AND CABLES

THE STRENGTH OF THE NEW
NICE SOLUTIONS

RELIABLE AND VERSATILE CONTROL UNITS FOR INDUSTRIAL AND COMMERCIAL DOORS.
Numerous functions at your fingertips!



D-PRO
ACTION

The basic functions
in the easiest way.

D-PRO
AUTOMATIC

The most advanced
and versatile
on the market.



Nice IDOOR

Catalogue 2019 – industrial door operators + accessories

INDUSTRIAL CONTROL UNITS AND CABLES

D-PRO ACTION CONTROL UNITS

Control units for **motors with mechanical limit stop or electronic limit switch**,
both **automatic and deadman operation**.
Suitable for all types of motor, single phase without integrated inverter
and three-phase, with 2.2 kW maximum power.

Easy programming and 2 LEDs for diagnostics.

High performance, with possibility of adding a dedicated module for optional potential free outputs.
Compatible with all types of sensitive edges, including wireless.

User-friendly: thanks to the O-View programmer with multifunction display for connection through the IBT4N interface (both optional).

Safe: protected by a plastic shell, to avoid any risk of electrical shock.

Radio receiver: dedicated slot to connect a Nice SMXI or OXI plug-in receiver.

Smart: the maintenance service warning can be programmed according to the number of manoeuvers required.



Nice IDOOR

Catalogue 2019 – industrial door operators + accessories

INDUSTRIAL CONTROL UNITS AND CABLES

D-PRO AUTOMATIC CONTROL UNITS



The most advanced and versatile control units for motors with mechanical limit stop or electronic limit switch, both automatic and deadman operation.
In compliance with all European norms and certified by TÜV.

Suitable for almost all industrial motors on the market, single phase with or without integrated inverter and three-phase, with 2.2 kW maximum power.

Easy programming and immediate diagnostics.

High performance with possibility of adding dedicated modules for additional functions such as traffic lights and loop detectors and to connect external transmitters.
Compatible with all types of sensitive edges, including wireless.

The ideal solution for interlocking doors: thanks to the dedicated function, the control unit can be used to operate a number of doors in succession, to restrict or control entry to and from areas that need to be secured against two or more doors being open simultaneously.



Safe: protected by a plastic shell, to avoid any risk of electrical shock.

Radio receiver: dedicated slot to connect a Nice SMXI or OXI plug-in receiver.

Smart: the maintenance service warning can be programmed according to the number of manoeuvers required.

Customizable: further button configurations are available on request, such as emergency stop switch.

The TÜV certification and compliance with EN 12453:2014 mean safety in all situations.

Nice IDOOR

Catalogue 2019 – industrial door operators + accessories




INDUSTRIAL CONTROL UNITS AND CABLES

D-PRO CONTROL UNITS		
Code	**Picture**	**Description**
NDCC2000		Control unit D-PRO Action 3-400 Max.Power 2,2 kW IP65 CEE Plug
NDCC2100		Control unit D-PRO Action 3-400 Max.Power 2,2 kW IP65 CEE Plug + brake/boost capacitor control board
NDCC2200		Control unit D-PRO Action 1-230 Max.Power 2,2 kW IP65 Schuko Plug + brake/boost capacitor control board
NDCC1000		Control unit D-PRO Automatic 3-400 Max.Power 2,2 kW IP65 CEE Plug
NDCC1100		Control unit D-PRO Automatic 1-230 Max.Power 2,2 kW IP65 Schuko Plug - for drives with frequency converter
NDCC1200		Control unit D-PRO Automatic 1-230 Max.Power 2,2 kW IP65 Schuko Plug

Nice IDOOR

Catalogue 2019 – industrial door operators + accessories

INDUSTRIAL CONTROL UNITS AND CABLES

Additional versions D-PRO control units		
On Demand		Control unit D-PRO Action 3-400 Max.Power 2,2 kW IP65 CEE Plug + MAIN SWITCH
On Demand		Control unit D-PRO Action 3-400 Max.Power 2,2 kW IP65 CEE Plug + brake/boost capacitor control board + MAIN SWITCH
On Demand		Control unit D-PRO Action 1-230 Max.Power 2,2 kW IP65 Schuko Plug + brake/boost capacitor control board + MAIN SWITCH
On Demand		Control unit D-PRO Action 3-400 Max.Power 2,2 kW IP65 CEE Plug + EMERGENCY MUSHROOM
On Demand		Control unit D-PRO Action 3-400 Max.Power 2,2 kW IP65 CEE Plug + brake/boost capacitor control board + EMERGENCY MUSHROOM
On Demand		Control unit D-PRO Action 1-230 Max.Power 2,2 kW IP65 Schuko Plug + brake/boost capacitor control board + EMERGENCY MUSHROOM
NDCC1002		Control unit D-PRO Automatic 3-400 Max.Power 2,2 kW IP65 CEE Plug + MAIN SWITCH
On Demand		Control unit D-PRO Automatic 1-230 Max.Power 2,2 kW IP65 Schuko Plug - for drives with frequency converter + MAIN SWITCH
On Demand		Control unit D-PRO Automatic 1-230 Max.Power 2,2 kW IP65 Schuko Plug + MAIN SWITCH
NDCC1001		Control unit D-PRO Automatic 3-400 Max.Power 2,2 kW IP65 CEE Plug + EMERGENCY MUSHROOM
NDCC1101		Control unit D-PRO Automatic 1-230 Max.Power 2,2 kW IP65 Schuko Plug - for drives with frequency converter + EMERGENCY MUSHROOM
NDCC1201		Control unit D-PRO Automatic 1-230 Max.Power 2,2 kW IP65 Schuko Plug + EMERGENCY MUSHROOM

Nice IDOOR

Catalogue 2019 – industrial door operators + accessories

INDUSTRIAL CONTROL UNITS AND CABLES

CABLES FOR D-PRO CONTROL UNITS	
Code	**Description**
For electronic limit switch	
CA0154A00/CA0174A00	Motor-control unit connection cable for SD+SW/SDN+SWN, unshielded. For small motors with electronic limit switch, length 5 m
CA0155A00/CA0175A00	Motor-control unit connection cablefor SD+SW/SDN+SWN, unshielded. For small motors with electronic limit switch, length 7 m
CA0156A00/CA0176A00	Motor-control unit connection cablefor SD+SW/SDN+SWN, unshielded. For small motors with electronic limit switch, length 11 m
CA0177A00	Motor-control unit connection cable, unshielded. For medium/big motors with electronic limit switch, length 5 m
CA0178A00	Motor-control unit connection cable, unshielded. For medium/big motors with electronic limit switch, length 7 m
CA0179A00	Motor-control unit connection cable, unshielded. For medium/big motors with electronic limit switch, length 11 m
For mechanical limit switch	
CA0157A00	Motor-control unit connection cable, unshielded. For small motors with mechanical limit switch, length 5 m
CA0158A00	Motor-control unit connection cable, unshielded. For small motors with mechanical limit switch, length 7 m
CA0159A00	Motor-control unit connection cable, unshielded. For small motors with mechanical limit switch, length 11 m
CA0177B00	Motor-control unit connection cable, unshielded. For medium/big motors with mechanical limit switch, length 5 m
CA0178B00	Motor-control unit connection cable, unshielded. For medium/big motors with mechanical limit switch, length 7 m
CA0179B00	Motor-control unit connection cable, unshielded. For medium/big motors with mechanical limit switch, length 11 m

Nice IDOOR

Catalogue 2019 – industrial door operators + accessories

MECHANICAL ACCESSORIES

Code	Picture	Description
NDA500		Adapter from 31,75 to 25,4 mm shaft
NDA501		Adapter from 40 to 25,4 mm shaft
NDA502		Adapter from 40 to 30 mm shaft
NDA503		Adapter from 40 to 31,75 mm shaft
NDA504		Adapter from 55 to 40 mm shaft
NDA505		Adapter from 30 to 25.4 mm shaft
NDA506		Adapter from 30 to 25 mm shaft
NDA507		Adapter from 40 to 25 mm shaft
CRA9		Adapter for diameter 31.75 (1.1/4”), 35and 40mm shafts

Code		Description
900029000050		Additional chain, 5 m length
100031010000		Additional chain, in rolls of 100 m, per meter
100031010001		Link for additional chain

Nice IDOOR

Catalogue 2019 – industrial door operators + accessories



MECHANICAL ACCESSORIES

Code		Description
NDSP0001		Emergency handchain system for SD cast bevel gear (low cost)
NDSP0009		Emergency handchain system for SD steel bevel gear
NDSP0004		Emergency handchain system for RDF140
NDSP0006		Emergency handchain system for RDF-220/350
NDSP0002		Emergency handchain system for RDF-380/750-9,5
NDSP0007		Emergency handchain system for RDF750-24/850Nm and above

Nice IDOOR

Catalogue 2019 – industrial door operators + accessories

MECHANICAL ACCESSORIES

Code		Description
NDA540		Kit with shafts Ø 30 mm (motor side with key + opposite side)
NDA541		Kit with shafts Ø 40 mm (motor side with key + opposite side)
NDA542		Kit with shafts Ø 55 mm (motor side with key + opposite side)
910510000300		Shaft bearing Ø 30 mm
910510000400		Shaft bearing Ø 40 mm
910510000550		Shaft bearing Ø 55 mm
133003201 / 910410000300		Shaft bearing, wall mounted Ø 30 mm
133055601 / 910410000400		Shaft bearing, wall mounted Ø 40 mm
910310003000		Triangular bracket for horizontal mounting, up to 300 kg
910310005300		Triangular bracket for horizontal mounting, up to 530 kg
910310013000		Triangular bracket for horizontal mounting, up to 1300 kg
910310025000		Triangular bracket for horizontal mounting, up to 2500 kg
NDA544		Backet to fix SD/SW-motors to Alpha sectional doors

Nice IDOOR

Catalogue 2019 – industrial door operators + accessories

MECHANICAL ACCESSORIES

Accessories for rolling shutters*		
Code		**Description**
131176001 / 910110093631		Disk for Shaft Ø 30, to suit tube Ø 98 x 2; 100 x 3 e 101,6 x 3,6 mm
141103201 / 910110012463		Disk for Shaft Ø 30, to suit tube Ø 133 x 4 mm
131176101		Disk for Shaft Ø 30, to suit tube Ø 133 x 2 mm
131176201		Disk for Shaft Ø 30, to suit tube Ø 159 x 4,5 mm
141105401		Disk for Shaft Ø 30, to suit tube Ø 168,3 x 4,5 mm
141109501		Disk for Shaft Ø 30, to suit tube Ø 193,7 x 5,4 mm
131046101 / 910110012464		Disk for Shaft Ø 40, to suit tube Ø 133 x 4 mm
131025701		Disk for Shaft Ø 40, to suit tube Ø 159 x 4,5 mm
131026201		Disk for Shaft Ø 40, to suit tube Ø 168,3 x 4,5 mm
141026201 / 910110018184		Disk for Shaft Ø 40, to suit tube Ø 193,7 x 5,4 mm
141106101		Disk for Shaft Ø 40, to suit tube Ø 219,1 x 5,9 mm
141106201		Disk for Shaft Ø 40, to suit tube Ø 244,5 x 6,3 mm

Nice IDOOR

Catalogue 2019 – industrial door operators + accessories

MECHANICAL ACCESSORIES

Accessories for chain-driven rolling shutters with RD motors (*)		
Code		**Description**
NDA520		Chain Reduction Kit 3/4",2:1,Shaft Ø30mm, Pignion 12 + 24 Tooth, 2m Roller Chain
NDA521		Chain Reduction Kit 1",2:1,Shaft Ø40mm, Pignion 12 + 24 Tooth, 2m Roller Chain
NDA522		Chain Reduction Kit 1"1/4, 2:1,Shaft Ø55mm, Pignion 12 + 24 Tooth, 2m Roller Chain
NDA523		Chain Reduction Kit 3/4",3:1,Shaft Ø30mm, Pignion 12 + 36 Tooth, 2.5m Roller Chain
NDA524		Chain Reduction Kit 1",3:1,Shaft Ø40mm, Pignion 12 + 36 Tooth, 2.5m Roller Chain
NDA525		Chain Reduction Kit 1"1/4, 3:1,Shaft Ø55mm, Pignion 12 + 36 Tooth, 2.5m Roller Chain
NDA526 / 100710000011		Chain Reduction Kit 1:1 for SD, tension bracket, Shaft Ø25,4mm, Pignion 12 + 12 Tooth, 1,5m Roller Chain
900210012000		Small motors foot bracket for chain reduction system
900210035000		Medium motors foot bracket for chain reduction system
900210069000		Big motors foot bracket for chain reduction system
245520003		Safety Bearing TA 1/2 RD .Max Torque 332 Nm
245530003		Safety Bearing TA 2/3 RD Max. Torque 552 Nm
245300001		Safety Bearing TA 4 RD Max. Torque 1063 Nm
245310001		Safety Baering TA 5 RD con Max. Torque 1943 Nm

Nice IDOOR

Catalogue 2019 – industrial door operators + accessories


ELECTRICAL ACCESSORIES

Code	Picture	Description
OXI/OXIFM		Pluggable receiver, 433MHz/868MHz
OX2/OX2FM		External receiver, 433MHz/868MHz
Era INTI		The colourful new line of 1 and 2 channel miniaturised transmitters, 433MHz, available in six colours.
Era ONE/ONEFM		The system includes 1, 2, 4 and 9 channel transmitters 433´MHz/868MHz
Era FLOR		1, 2 and 4 channel transmitters with a new stylish design 433MHz

Nice IDOOR

Catalogue 2019 – industrial door operators + accessories



ELECTRICAL ACCESSORIES

Code	Picture	Description
NDA006		K60 D-PRO Monitoring Module
NDA008		D-PRO Repeater Module K65
NDA030		D-PRO Automatic Relays and traffic light extension module
NDA070		D-PRO Automatic Induction loop module - 2 channels

Nice IDOOR

Catalogue 2019 – industrial door operators + accessories

NICE APPS

Code	Picture	Description
NDA004		Programming and installation bluetooth module for D-Pro Automatic to be used with Nice-Industrial App
	   	
IT4WIFI		Wifi-module to use D-PRO Action with Nice App
	 	

Nice IDOOR

Catalogue 2019 – industrial door operators + accessories

ELECTRICAL ACCESSORIES

Additional elements		
720000001100		Cable 1m with Plug Red 380-CEE
CA8.5320		Cable 2m with Schuko plug 90 degres
730000001023		Main Switch Group (Button-3 Black Cable-3 Brown Cable)
730000001030		Mushroom head emergency stop push-pull button switch N/C
920512000730		External push buttons, 2 NA buttons + 1 ND stop button + 7 m long cable
920512000731		External push buttons, 2 NA buttons + 1 ND stop emeregency button + 7 m long cable

Nice IDOOR

Catalogue 2019 – industrial door operators + accessories

ELECTRICAL ACCESSORIES

Safety Elements		
920132111001		Optosensors with Diagnosis function(10.5 m long cable)
920081155516		Spiralcable 5 x 0,5 qmm, 0,8m spiraled/ 1,6m stretched
920081155550		Spiralcable 5 x 0,5 qmm, 0,8m spiraled/ 5m stretched
920821000010		Safety switch against possible cable breaks or slackering
920811000010		Slack Rope Cylindrical Switch Rope Brake against cable breaks
NDA010		Junction Box with integrated pneumatic switch for pneumatic safety edge
NDA011		Junction Box black, with board, plugable with hole Ø16m
NDA012		Junction Box black, with board, plugable with hole Ø16m incl. SBA-Sensor for autom. Floor Level Regulation
NDA013		Junction Box black, with board, plugable without hole
920091100085		Connecting Cable for 2 junction boxes, lenght 8,5m

Nice IDOOR


Catalogue 2019 – industrial door operators + accessories

ELECTRICAL ACCESSORIES

Safety Elements	
TCLS	Light curtain protected length 2.430mm, total length 2.555mm, type CEDES
TCLSW	Light curtain protected length 2.430mm, total length 2.555mm, type Witt
TCLS1	Light curtain protected length 1.890mm, total length 2.015mm, type CEDES
TCLS1W	Light curtain protected length 1.890mm, total length 2.015mm, type Witt








Nice IDOOR

Catalogue 2019 – industrial door operators + accessories

ELECTRICAL ACCESSORIES

Safety Elements		
920540100041		Roller Lever Switch
920670000020		Wicked Door Contact
920630000110		Pass Through Photocell with Reflector
920141000010		Rubber Profile 1m
920320228100		C-rail, Aluminium 28mm x 10mm, in 2m-pcs.

Nice IDOOR

Catalogue 2019– industrial door operators + accessories

Frequency converters

Frequency converters	
EG059B00	inverter 2.2kW with 7mtrs cable
EG059E00	inverter 2.2kW with 11mtrs cable
EG059A00	inverter 1.1kW with 7mtrs cable
EG059C00	inverter 1.1kW with 5mtrs cable
EG059F00	inverter 1.1kW with 11mtrs cable

Nice IDOOR

Catalogue 2019 – industrial door operators + accessories

notes

Nice IDOOR

Catalogue 2019 – industrial door operators + accessories

notes

Nice IDOOR

Catalogue 2019 – industrial door operators + accessories

CONTACTS

Nice Deutschland GmbH
Friethöfer Kamp 23
48727 Billerbeck

Tel. +49 (0) 2543 2389 0
Fax. +49 (0) 2543 2389 23
E-Mail infode@niceforyou.com

www.niceforyou.com