TENDER SPECIFICATION

FOR

MOTORIZED SLIDING GATE

Doc. No. 323-MD-024
Rev. 2, Date 1–Nov-2014

Rev.	Date	Description
2	01/Nov/14	Generally Revised
1	11/Sep/14	Revised as per site discussion
0	09/Sep/14	First Issue

1. INTRODUCTION

JSW MI is setting up sitting & cut to length line project at Khed City Dist.-Pune (M.S.), India. The project site is near to Pune city. For this project, the items as per enclosed sheet/ drawings are required.

2. SITE CONDITION

Climatic conditions

Max. ambient air temperature	45°C
Max. relative humidity	87% (In rainy season)
Max. annual rainfall	1000 mm
Max. wind pressure	140.4 Km/hr
Altitude above mean sea level	700 m
Seismic zone	III

Working conditions

Input power supply	3 phase, 415 ±10% V, 50 ± 3% Hz
Temperature	10 – 50 °C
Relative humidity	87%

3. SCOPE OF THE WORK (supply & services)

The scope of work includes design, engineering, supply, testing, erection and commissioning (as may be applicable for the scope) of motorized sliding gate as per the details given along with this document.

The bidder to submit the offer along with all relevant details, drawings, reference list and relevant documents as below:

- Intended deviations (if any) from the specified requirements / specifications.
- Design / drawing (wherever applicable).
- Standard catalogue (wherever applicable).
- Time schedule & delivery period.
- Make of standard bought out items.
- References of similar jobs done.
- Period and terms & conditions.
- List of inclusions / exclusions.
- Guarantee / warrantee.

4. PRICE

The price to be submitted including all expenses and towards the following

1. Designing, Engineering, manufacturing and supply including packing, forwarding, loading, freight & insurance charges for the delivery of all materials & services up to project site
2. Erection & commissioning (wherever applicable) including all expenses for air / train / taxi fare from the place of departure to project site, lodging & boarding, local transport and

any other expenses during stay of bidder`s representative at project site for required duration.

3. Taxes and duties as applicable.

5. SPECIAL NOTE

The scope of supply shall not be limited to the services / equipments mentioned in this document. If any additional equipments / services deemed to be required to complete the system / equipment / services then the same to be included in the offer.

6. TECHNICAL SPECIFICATION FOR MOTORIZED SLIDING GATE

Sr. No.	Particulars	Description
1.	Type	See through Stainless Steel Motorized Single Sliding Gate with push button, Wicket gates and fencing
2.	Qty.	02 nos. sliding gate (01 no SG1 & 01 SG2) 02 nos. wicket gate (01 no. WC1 & 01 no. WC2) Fixed grill (FG) (length given in point 7 & 8)
3.	Material	Stainless Steel SS304 , rest standard construction
4.	Sliding gate dimensions	Length SG1 - 10000 mm SG2 – 6000 mm Height - 1800 mm (refer attached dwg no 323-A-020 Sheet 1 of 2 Rev.C & 2 of 2 Rev.0)
5.	Wicket gate	Length WC1 - 1500 mmm WC2 - 1900 mm Height - 1800 mm (Design same as the sliding gate)
6.	Stainless steel fix grill	Length FG1 - 2500 mm Height - 1800 mm (refer attached dwg no 323-A-020 Sheet 1 of 2 Rev.C & 2 of 2 Rev.0)
7.	Fence above boundary wall (MS and SS 304 both to be quoted separately)	Length FG2 19650 mm (straight) FG3 19600 mm (straight) FG4 7500 mm (arch length) Height 1000 mm (refer attached dwg no 323-A-020 Sheet 1 of 2 Rev.C & 2 of 2 Rev.0)
8.	Gate guide way	Vendor to furnish details
9.	Speed	Vendor to specify
10.	Motor	Vendor to specify
11.	Power required	Vendor to specify
12.	Gate Weight	Vendor to specify
	Standard Accessories/ Features:	
1.	Electrical equipment suitable for 3 phase 415 ± 10 % V / single phase 230 V/50 Hz AC supply.	
2.	Robust fabricated structure.	
3.	Hard chrome plated wheel.	
4.	Galvanised adjustable upper guide brackets with guide posts duly painted with nylon rollers.	
5.	MS end of run limit stop and MS post with rubber safety strike rail.	
6.	Guide way rail along with its suitable clamping arrangement.	
7.	Manual operation in case of power failure.	
8.	Foundation bolts, guide ways, roller etc. to be provided by supplier	

9.	Highly compact dimensions & extremely silent operation.
10.	Motor protected by internal thermal switch.
11.	Advance electronic control unit permits/allows operation time adjustment, partial opening, automatic closing, step by step control, stop safety, reverse safety.
12.	All equipment shall be dust and vermin proof and also capable to work in dusty environment.
13.	Electromechanical actuator consisting of a suitable drive unit with suitable rack & electronic system for opening and closing of sliding gate using push button with mechanical over-ride facility.
14.	Flashing light indicator shall be installed on posts.
15.	Photocell shall be provided to stop the gate in case the traffic is not clear.
16.	Necessary GA drawings to be provided.
17.	2 Sets of operational & maintenance manual.
18.	Set of spares for 2 years normal operation as per supplier`s recommendation.
19.	Supply, installation, erection and commissioning shall be in supplier’s scope.
20.	Above dimensions may vary as per actual layout designing.
21.	All hinges with aldrop with key & lock facility and necessary fittings for the wicket gates to be provided.