Motorized Single Leaf Sliding Gate with Wicket Gate (1500 X 2200 mm)

Sr .No.	Specification	Motorized Single Leaf Sliding Gate W) 10250 X (H)2200MM with Wicket Gate (1500 X 2200 mm)
1	**Door type**	Motorized Sliding Gate (1.2MM MS SHEET _ Cladding)
2	**Opening Direction**	Horizontal - from left to right or reverse
3	**Mounting Location area**	Inside area
4	**Design Pattern**	Standard Tubular Design Pattern
5	**Outer Tube**	100 x 100 x 4mm MS SQ. TUBE
6	**For Post**	100 x 100 x 4mm MS SQ. TUBE
7	**Inner Tube**	40 x 40 x 3.2 mm MS SQ. TUBE
8	**Gap Between Tubes**	1000MM APPROX
9	**Bottom Rail on ground**	dia 20 mm round bright bar with heavy duty support ISMB 100 X 50 Beams
10	**Bottom Rollers**	Heavy Duty Bottom Wheel With both side Bearings (chorme plated)
11	**Guide Rollers supporter during Gate movement**	Nylon Rollers with Bearings both side mounted on column for support smooth movement of gate
12	**Painting**	QD Paint & QD Primer
13	**El motor make**	(100% imported)
14	**Emergency Operation**	Manual after turn the switch
15	**Operating Switch**	Push Button from inside
16	**Safety**	Photocells, Flashing Light
17	**Civil work**	Client scope – client need to grout the I beam in concrete to create track for sliding gate

Manual Single Leaf Sliding Gate

Sr .No.	Specification	Manual Single Leaf Sliding Gate (W) 9300 X (H)2000MM
1	**Door type**	Manual Single Leaf Sliding Gate (1.2MM MS SHEET _ Cladding)
2	**Opening Direction**	Horizontal - from left to right or reverse
3	**Mounting Location area**	Inside area
4	**Design Pattern**	Standard Tubular Design Pattern
5	**Outer Tube**	100 x 100 x 4mm MS SQ. TUBE
6	**For Post**	100 x 100 x 4mm MS SQ. TUBE
7	**Inner Tube**	40 x 40 x 3.2 mm MS SQ. TUBE
8	**Gap Between Tubes**	1000MM APPROX
9	**Bottom Rail on ground**	dia 20 mm round bright bar with heavy duty support ISMB 100 X 50 Beams
10	**Bottom Rollers**	Heavy Duty Bottom Wheel With both side Bearings (chorme plated)
11	**Guide Rollers supporter during Gate movement**	Nylon Rollers with Bearings both side mounted on column for support smooth movement of gate
12	**Painting**	QD Paint & QD Primer
13	**Civil work**	Client scope – client need to grout the I beam in concrete to create track for sliding gate

Motorised Three Leaf Telescopic Sliding Gate

Sr .No.	Specification	Motorised Three Leaf Telescopic Sliding Gate
1	**Door type**	Motorised Three Leaf Telescopic Sliding Gate (1.2MM MS SHEET _ Cladding)
2	**Clear Opening gate dimension**	(W) 9900 mm X (H) 2500 mm & (W) 12800 mm x (H) 2000mm
3	**Master Leaf Size**	4565 X 2500 mm & 5535 X 2000 mm
4	**1 ST Leaf Size**	3815 X 2500 mm & 4785 X 2000 mm
5	**2 ND Leaf Size**	3815 X 2500 mm & 4785 X 2000 mm
6	**Opening Direction**	Horizontal - from left to right or reverse
7	**Mounting Location area**	Inside area
8	**Design Pattern**	Standard Tubular Design Pattern
9	**Outer Frame Tube Sizes**	100 x 100 x 4mm MS SQ. TUBE
10	**Internal Vertical Tube Sizes**	40 x 40 x 3.2 mm MS SQ. TUBE
11	**For Post**	100 x 100 x 4mm MS SQ. TUBE
12	**Bottom Rail on ground**	dia 20 mm round bright bar with heavy duty support ISMB 100 X 50 Beams
13	**Bottom Rollers**	Heavy Duty Bottom Wheel With both side Bearings
14	**Guide Rollers supporter during Gate movement**	Nylon Rollers with Bearings both side mounted on column for support smooth movement of gate
15	**Painting**	QD Paint & QD Primer
16	**Control Panel**	1 No Operating Station.
17	**Operation**	By Telescopic Mechanism
18	**Accessories**	1. Limit Switch for Cut out when Gate is fully Closed
		2. Flashing Light
		3. Remote
		4. Hooter
		5. Photocell
19	**Civil work**	Client scope – client need to grout the I beam in concrete to create track for sliding gate