Motorized Rolling Sutter

Door type	Single Wall Motorized Rolling Sutter
Clear Opening dimension (w) -- x (h) --	RS-1:(W) 4000 mm x (H) 5000 mm RS-2:(W) 5000 mm x (H) 6000 mm RS-3:(W) 4000 mm x (H) 5000 mm RS-4:(W) 3500 mm x (H) 5000 mm RS-5:(W) 2500 mm x (H) 2700 mm
Opening Direction	Vertical - from bottom to Top
Mounting Location area	Inside area / Outside area
Mounting Surface	Side Brackets: Optional = On Concrete /Steel & Side Guides: Not required for height below 3000mm
Opening/Closing Speed	0.1 m/sec
Door Material	
Curtain material	GI
Curtain Panel	The panel made of 1.0mm thick CRCA steel
Curtain panel size	75mm wide
Curtain Profile	Corrugation
Slat Thickness	0.9 mm to 1.2 mm (As per IS 6248)
Bottom Profile	M. S. Plate 100 mm x 2.5 mm thick with angle stiffener
Side Guide Profile	M.S." U" Shaped profile 65 mm -150 mm x 3 mm thick (as per the opening width dimension)
Roller Shaft	M.S. Tubular Pipe with Flange & machined shaft at the ends Pipe Día -100 to 300 mm as per w x h
Side Brackets	MS Plate 3 mm to 10 mm thick, as per the opening dimension
Hood Cover	Made of GI Sheet Thickness 0.8 mm with 25x25x3mm angle stiffener
Surface finish	
Painting	2 Coats (each coat of 35 microns DFT) of EPOXY polyamide-based enamel finish of approved color and make over a Coat (each one coat 25 microns DFT) of EPOXY polyamide based red oxide zinc phosphate primer
Automation	
Drive Unit & Mounting Type	Direct Drive (European Make)
Emergency Operation	Manual Rope Driven
Operating Switch	Push Button from inside & Outside also
Accessories	Flashing Light / Door line Safety Photocell
Installation Constraint any	Need to be check = space requirements + substructure + Mounting access + Access in the event of power cut