High Speed Door RR3000ISO

Sr. No	Description	High Speed Door RR3000ISO
1	**Door construction:**	consists of highly thermally insulated sandwich lamellas consisting of foam (thickness 50 mm) covered by metal sheet trays in silver (RAL 9006). A doubled sealing system links the lamellas ensuring excellent wind and water tightness and a smooth run of the door
2	**Side Frames**	Made up with Galvanised Steel Profiles
3	**Thermal transmittance:**	Door blade 1,4 W/m^2K Complete door min 1,5 W/m^2K
4	**Wind resistance:**	class 2-3 (EN 12424) DW ≤ 5000 mm: class 3 DW > 5000 mm: class 2
5	**Contactless Winding :**	The innovative Disc Drive technology used in the Albany RR3000 ISO supports the door curtain movement thereby ensuring a long service life. The slats are wound onto windling discs without contact. Using this technology, the door can be opened and closed very quickly and with no wear.
6	**Drive Unit :**	Gear motor 1,1 KW. Chain drive to reduce mounting space to the side
7	**Temperature range :**	-20°C to +40°C (mounting side)
8	**Protection :**	IP55
9	**Control system:**	Albany MCC, with vector control technology and boost function at start-up. Graphic display and foil keypad for easy guided operation. Easy access to all important information for operation and service
10	**Control Voltage**	24 V DC
11	**Power supply:**	3/N/PE 380/400/415/440/480 V; 50/60 Hz.
12	**Speed:**	Opening / closing up to 2,1 / 0,7 m/s.
13	**Safety device:**	Door line photo-cell, drop down protection by integrated balancing system
14	**Manual activation :**	by releasing the brake at ground level. Partly opening by means of the pre-stressed tension springs.
15	**Heat transfer coefficient :**	Door blade 1,4 W/m^2K
16	**Window slats**	Lamellas with transparency window slats
17	**Top Cover & Motor Cover**	Included