TECHNICAL SPECIFICATION – TRANSPARENT GREENHOUSE/POLYHOUSE FILM			
TECHNICAL SPECIFICATIONS	**REQUIREMENT**	**UNIT**	**TEST STANDARD / REFERENCE**
PRODUCT	Transparent UV-stabilized greenhouse/polyhouse film	—	Manufacturer's specification
MATERIAL	UV-stabilized polyethylene (PE)	—	Manufacturer's specification
TYPE OF FILM	Transparent multilayer greenhouse film	—	Manufacturer's specification
THICKNESS	200 minimum	micron	ISO 4593 / Manufacturer's test certificate
TOTAL WEIGHT	Approx. 180–200	g/m²	EN ISO 2286-2 / Manufacturer's test certificate
LIGHT TRANSMISSION	≥ 85% (90% preferred)	%	ASTM D1003 / Manufacturer's test certificate
COLOUR	Transparent / clear	—	Visual inspection
UV STABILIZATION	Required; suitable for outdoor exposure	—	Manufacturer's certification
ANTI-DRIP	Required	—	Manufacturer's specification
ANTI-FOG	Preferred	—	Manufacturer's specification
ANTI-DUST	Preferred	—	Manufacturer's specification
WATER TIGHTNESS	Waterproof; no leakage under normal service conditions	—	Manufacturer's test certificate
TENSILE STRENGTH	≥ 20	MPa	ISO 527 / Manufacturer's test certificate
TEAR RESISTANCE	To be declared by manufacturer; suitable for outdoor roofing	N	ISO 6383 / equivalent
ELONGATION AT BREAK	To be declared by manufacturer	%	ISO 527
SERVICE LIFE	Minimum 3 years under outdoor exposure	years	Manufacturer's warranty/certificate
OPERATING TEMPERATURE	Suitable for local ambient temperature and solar exposure	°C	Manufacturer's specification
ROLL WIDTH	Approx. 4.0 m minimum; wider rolls preferred where available	m	Manufacturer's specification
ROLL LENGTH	15–30 m or as required; continuous rolls preferred	m	Manufacturer's specification
JOINTING	Manufacturer-approved heat welding / compatible joining system	—	Manufacturer's installation procedure
FIXING SYSTEM	Mechanical clamping/fixing suitable for wind uplift; supplier to provide details	—	Manufacturer's installation procedure
WIND RESISTANCE	Supplier to declare maximum permissible wind speed and support spacing	—	Manufacturer's technical data
APPLICATION	Temporary outdoor roof covering for cricket pitch to permit use during rainy season	—	Project requirement
UV / WEATHER WARRANTY	Minimum 3 years preferred	years	Manufacturer's warranty