MS Motorised Single Skin Rolling Shutter - Indirect Drive

Sr .No.	Specification	MS Motorized Rolling Shutter
1	**Description:**	Motorised Rolling Shutter with MS Slats with thickness of 1 mm.
2	**Mounting Location area**	Inside area
3	**Mounting Surface**	MS Structutre (client scope)
4	**Curtain Panel**	The panel made of 1.0mm thick MS.
5	**Curtain panel size**	75mm wide
6	**Curtain Profile**	Curved
7	**Bottom Profile**	M. S. Plate 100 mm x 2.5 mm thick with angle stiffener
8	**Side Guide Profile**	M.S." U" Shaped profile 65 mm -150 mm x 3 mm thick.
9	**Side Guide Profile**	T shape Guide Required for W 5000 mm X H 7200 mm , W 7000 mm X H 5000 mm, W 5000 mm X H 6000 mm
10	**Wind Lock**	W 5000 mm X H 7200 mm, W 7000 mm X H 5000 mm, W 5000 mm X H 6000 mm
11	**Roller Shaft**	M.S. Tubular Pipe with Flange & machined shaft at the ends Pipe Día -100 to 300 mm as per w x h
12	**Side Brackets**	MS Plate 3 mm to 10 mm thick, as per the opening dimension.
13	**Hood Cover**	Made of GI Sheet Thickness 0.9 mm
14	**Surface finish**	Powder Coating
15	**Drive Unit & Mounting Type**	Electric Motor - Indirect Mounting - Sprocket chain arrangement – IP54 Protection
16	**Safety Catch**	**Included in size W5000 mm X H7200 mm with " T " shape Side Guide profile.**