



DOCK LEVELER SIZE	WIDTH (W)	LENGTH (L)	HEIGHT (H)	LIP (C) LENGTH	BUFFER SIZE (OPTIONAL)
	2200	2925	480	400	200X300X100


PIT DIMENSION	WIDTH (W 1)	LENGTH (L 1)	DEPTH (D)	ALL DIMENSIONS ARE IN mm
	2250	2985	485	











NOTE: -

1. PROPER DRAINAGE SHOULD BE DONE
2. TRENCH AS SHOWN SHOULD BE MADE BY DECIDING THE POWER PACK POSITION (SUPPLY CABLE LENGTH STD. 7000 MM)
3. LEVEL OF THE PIT SHOULD BE PLAIN AND SHOULD TAKE AT LEAST 12000 KGB FLOOR LOADING
4. MOUNTING ARRANGEMENT FOR BUFFERS SHOULD BE MADE AS PER BUFFER DRAWING (IF ORDERED)
5. FABRICATION TOLERANCE FOR PLATFROM SIZE WILL BE +-15 MM

DOCK LEVELER- 6 TON CAPACITY - DOUBLE CYLINDER

CLIENT APPORVAL-		NIHVA TECHNOLOGIES PVT. LTD.	NIHVA TECHNOLOGY PVT. LTD. PUNE Tel : 020 66304623 Email:- info@nihva.com Website:- www.nihva.com
DRAWN :- A. KUMAR	DATE : - 30/12/2014	CLIENT - TAKENAKA INDIA PVT LTD.	
		PROJECT - TS TECH	
ALL DIMENSION ARE IN mm		SITE - MANDAL , GUJARAT	
If any queries contact : projects@nihva.com		DWG. NO. - NVA/TAKENAKA/NDL/01.	