NIHVA MAKE - High Speed Door - (ALU Speed Door)

- Ideal solution in areas with high demand for logistics efficiency and heavy traffic
- Automatic super fast opening and closing
- Reduces leakage of heat and air, heat preservation
- Moveable shaft system
- No torsion spring, less need for spareparts, minimum cost
- Patented rubber drive method

Sr. No	Description	Specifications
1	**Use**	Internal / External Door
2	**Speed**	Inverter Motion system to adjust different speeds, with progressive control of acceleration & deceleration during braking
3	**Opening speed**	upto 2 m/s
4	**Closing speed**	0.7 m/s
5	**Security Features**	EN 13241-1 Standard
6	**Resistance to wind load**	EN12424 upto class 1
7	**Curtain**	Aluminium 19.0 mm
8	**Door Leaf Material / Surface**	Polyurethane filled RAL 9006 aluminium lamella
9	**Hood Cover**	Included
10	**Motor Cover**	Included
11	**Guide Material / Surface**	Aluminium Anodized , Painting in any RAL9006 lamalla colour
12	**Operator & Control**	German Make Motor
13	**Connecting Voltage**	220V , 1Ph , N
14	**Open-Stop-Close Button**	Standard
15	**Protection Category**	IP 54
16	**Power Consumption**	0.75 kw Motor
17	**Emergency Off Button**	Standard
18	**Closing Zone Monitoring**	Optical Safety edge, bottom edge sensor
19	**External Route Monitoring**	Photocell
20	**Emergency Opening**	Crank Handle
21	**Window**	one row of window