High-Speed Door Design Dimensions & Guide

1. Door Dimensions (Example)

- Door Width (W): 3000 mm
- Door Height (H): 3500 mm
- Opening Speed: 1.5 m/s
- Curtain Area: 10.5 m²
- Opening Time: ~2.33 sec

2. Curtain Material

- Type: Reinforced PVC Fabric
- Thickness: 1.5 mm
- Tensile Strength: ~2500 N/50 mm (warp), ~2200 N/50 mm (weft)

3. Structural Frame

- Side Frame: 100x50x3 mm Mild Steel Rectangular Tube
- Top Header: 150x75x4 mm Mild Steel
- Curtain Guide: U-section with brush seals
- Bottom Bar: 50x50x3 mm with rubber sealing strip

4. Drive System

- Motor: 1.5 kW, 3-Phase Induction Motor with VFD
- Gearbox: Helical Inline Gear Reducer
- Roller Shaft: Ø76 mm seamless pipe with end bearings
- Operation Speed: Adjustable via VFD (soft start/stop)

5. Safety and Sensors

- Photoelectric Safety Sensors (2 pcs)
- Bottom Edge Soft Sensor (auto-reverse)
- Manual Override System (chain or crank)

6. Additional Notes

- Allow 200 mm side clearance for guide and service
- Use IP55 rated motor for outdoor or washdown areas
- Provide control panel access at 1.2-1.4 m height