Annexure A with refer to PO – NVA 432

Technical Specification: - RP300 Albany German Make (100% Imported)

AD_RP300 ASSA ABLOY RP300

Door type High-speed roller door RapidProtect 300
Daylight width- 1.200 mm
Daylight height- 1.800 mm
Door control system MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed 2,3 m/s
Max. Closing Speed 1,7 m/s
Control box position Mounted next to the drive unit
Control system position Right
Motor Position - Right
Wind class - 1
Side frame version - Aluminium
Bottom plate - Delivered without bottom plates
Bottom profile - Aluminium
Safety contact edge - Pre running photocell at the bottom profile
Photocell - With photocell
Crank - With crank for manual operation
Top roll material - Aluminium
Door curtain - RollTex Plus
Door curtain colour - Grey, similar to RAL 7001
Silicone free -- Silicone free
Window type -- Window 700X500 mm, type anti UV
Window Quantity - 1
Height:bott.edge to bott.prof. 1.200 mm
Motor cover - Motor cover powder coated standard
Top roll cover - Top roll cover made of aluminium
MCC type - Standard version
Field bus - Field bus connection Ethernet/IP 2 -port, mounted in MCC extension box
1 x D4920R0057 EtherNet/IP 2-port bus module
1 x D4920R0049 PROFINET cable 0,5m RJ45/M12 fem
MCC display type - Display delivered separately, not mounted
Power supply - 400 V, 3-phase
Frequency - 50 Hz
Main switch - With main switch
Mains connection cable length 3.000 mm
Safety limit switch (MP) Schmersal on 1 side with relay for cat. 4
Cable marking Including cable and component marking