NIHVA - ASSA ABLOY – High Performance Door - RR392

(100% Imported – made in Germany)

Size –

1. **(W) 4000 mm X (H) 4500 mm**
2. **(W) 3600 mm X (H) 4500 mm**
3. **(W) 2500 mm X (H) 2500 mm**

Description:

Flexible High-Performance Door, opening in vertical direction, for interior and exterior use
Self-supporting side frames made of galvanized steel

Door curtain

Transparent PVC with vertically applied side reinforcement stripes, ultramarine (similar to RAL 5002) or red (similar RAL 3002).

Top roll: made of anodized aluminum.

Wind protection: Through wind taps on the door curtain.

Wind resistance: Class 2 (EN 12424)

Bottom profile: anodized aluminum.

Drive unit: Gear motor.

Protection: IP 55

Safety devices:
Electrical safety contact edge, stationary safety photocell, and drop down protection by integrated balancing system.

Covers

Top roll cover made of galvanized steel

Motor cover made of plastic, colour grey (similar RAL 7040

91 8551096333 ☎ +91 20 66304033

Email: Arjun.patil@nihva.com

Control system:
Frequency converter control system

MCCVectorControl, based on vector control system including boost function for start-up,

(Open/close) up to max. 2.2/0.9 m/s,

Supply voltage 3L(N)PE/380/400/415/440/480V;50/60Hz,

Transformer necessary for 220/230/500V; 50/60 Hz