WORK ORDER

Client		PO Number:	4700064951	W. O. no-	SO/20-21/076
SEZ Biotech Services Pvt Ltd		PO Dated :	04-Nov-20	W. O. Date	24-Dec-20
Address:		PO Received Date:	04-Nov-20	Sales Co ordinator	Smita Khare
Manjari Bk., Tal. Haveli, Pune 412207 (India)		Ref. Quotation:	SQT.20.21.2717R3	Front Sales Person	Arjun

Dispatch Address:

SEZ Biotech Services Pvt Ltd, Manjari Bk., Tal. Haveli, Pune 412207 (India)

Sr. No	Description of Goods	Technical Details	UOM	Qty.	Rate	Supply	Installation	Total Amount	Dwg. Approval
1	**Automatic Biparting Sliding Glass Door**	**Size : (W)2000 x (H)2530 mm**	**NO**	**1**				-	
2	**Automatic Telescopic Sliding Glass Door**	**Size : (W)2070 x (H)2400 mm**	**NO**	**2**				-	

Sr .No.	Specification	Description
1	Motor	High performance and heavy duty DC motor with integrated encoder and gearbox
2	Power Supply	170-260 V AC 50-60 Hz
3	Power Consumption	170 W
4	Protection Class	IP 22
5	Carrying Capacity	170 Kg for single leaf, 240 Kg for double leaves
6	Operator	Hafele Make - 100% Imported
7	Operator Chassis Size	125 x 168 mm , Aluminium
8	Carrier Assembly	Two carrier assembly for each leaf, (2 main and 1 balancing wheel for each carrier assembly)
9	Trigger Belt	Special trigger belt design for maximum safety and endurance and minimum noise level
10	Working Temperature	- 20* C + 50* C
11	Position Selector	Digital , 6 user positions, LCD touch screen
12	User Modes	Auto , Open , In , Out , Locked , Partial Opening
13	Installer Settings	Opening Speed, Closing Speed, Hold Open Time, Half Opening Distance, Opening, Direction, Installer Password, User Password
14	Obstacle Detection	Permanent obstacle detection in both opening and closing cycles.
15	Energy Saving	Short braking distance during opening and closing cycle for energy saving
16	Interlocking	2 doors can be operated using interlocking mode
17	Resetting	Can be performed using digital position selector without opening operator cover
18	Compatibility	Compatible with fire alarm and access control systems
19	Fault Monitoring	Error codes are shown on the digital position selector screen.
20	Safety	3D infrared curtain photocell
21	Opening Sensor	Radar
22	Combiner (Opening + Safety) Sensor	Opening radar with integrated 3D infrared curtain photocell, Energy saving, EN16006
23	Door Leaf	Frameless With 2 point fittings per door panel
24	Glass	12mm thick Glass
25	Operator Mounting	On glass panel provided by others

A) Commerical Terms

1)	**Payment Terms:**	Supply : 100% Against Delivery & Installation : 100% After Installation
2)	**Delivery Date as per PO:**	8-9 weeks as per our offer
3)	**Transportation:**	Inclusive
4)	**P&F Charges:**	NA
5)	**Loading:**	NIHVA
6)	**Unloading:**	Client Scope
7)	**Lifting Equipments:**	Scaffholding/ Forklift - NIHVA
8)	**Warranty:**	12 Months from date of Supply
9)	**Height arrangement:**	Client Scope
10)	**Electricity Supply:**	Client Scope
11)	**GST:**	Due to SEZ
12)	**Installation Scope:**	NIHVA
13)	**Mode of import:**	NA
14)	**HSS:**	NA
15	**Supprt Structure**	NIHVA
15)	**Documentation Required:**	Standard Handover Documents

Certified that the above work order finalised in presence of:

AGM	SALES	PROJECT		PPC	DESIGN	Date & Time
A. K.	A.P					