QUALITY PLAN AND INSPECTION REPORT

M/S NIHVA TECHNOLOGIES PVT.LTD

CYLINDER DESCRIPTION:-Ø50XØ25X140MM STROKE (ROD EYE & REAR EYE)

SUPPLIER NAME:-**DUTTA CONTROL**	INVOICE QUANTITY :-04 NO.	INVOICE DATE:- 20-08-2018.
PART NO:- 12-03-002-50-140-R1	INVOICE NO. :-00	INSP. SAMPLING CRITERIA :- 100%
PART NAME:-SINGLE ACTING HYDRAULIC CYL.	CHECKED QUANTITY :-04 NO.	
DRG .REV. NO:-DLP1002_006.	P.O. NO :-	P.O DATE:-

SR. NO-	PARAMETER	SPCIFICATION	INSTRUMENT	SUPPLIER OBSERVETION				
				1	2	3	4	
1	TOTAL LENGTH(CLOSE)	400(+/- 2)	MEASURING SCALE	401	399	402	400	
2	STROKE	140(+/- 1)	MEASURING SCALE	140	139	141	141	
3	CTC DISTANCE	350(+/- 0.5)	MEASURING SCALE	351	349	352	351	
4	REAR & ROD EYE BORE	28(H7)	BORE GAUGE	28.02	28.03	28.02	28.025	
5	INLET PORT	1/8"BSP	PLUG GAUGE	OK	OK	OK	OK	
6	OUTLET PORT	3/8" BSP	PLUG GAUGE	OK	OK	OK	OK	
7	PLATING THICK	35+µ	PLATING THICK GAUGE	44	39	40	37	
8	LEAKAGE	SHOULD NOT	VISUAL	NO LEAKAGE	NO LEAKAGE	NO LEAKAGE	NO LEAKAGE	
9	MAX WORKING PRE.	160 BAR	PRESSURE GAUGE	OK	OK	OK	OK	

SPECIAL CASE:-CYL TESTED DURING 10 MINUTES AT 210 BAR PRESSURE.

REMARKS:-

INSPECTED BY SIGNATURE / DATE :- Jayante 20.08.18

APPROVED BY:-

DUTTA CONTROL ★ JYOTIBANAGAR ★ TALAWADE PUNE - 62.

Note :- All Dimensions are in MM.

QUALITY PLAN AND INSPECTION REPORT

M/S NIHVA TECHNOLOGIES PVT.LTD

CYLINDER DESCRIPTION:-Ø50XØ35X426MM STROKE (ROD EYE & REAR EYE)

SUPPLIER NAME:-**DUTTA CONTROL**	INVOICE QUANTITY :-08 NO.	INVOICE DATE:- 20-08-2018.
PART NO:- 02-06-002-50-426.	INVOICE NO. :-00	INSP. SAMPLING CRITERIA :- 100%
PART NAME:-SINGLE ACTING HYDRAULIC CYL.	CHECKED QUANTITY :-08 NO.	
DRG .REV. NO:-	P.O. NO :-	P.O DATE:-

SR. NO-	PARAMETER	SPCIFICATION	INSTRUMENT	SUPPLIER OBSERVETION				
				1	2	3	4	5
1	TOTAL LENGTH(CLOSE)	684(+/- 2)	MEASURING SCALE	686	684	683	684	685
2	STROKE	426(+/- 1)	MEASURING SCALE	425	426	427	425	426
3	CTC DISTANCE	634(+/- 0.5)	MEASURING SCALE	635	634	635	636	635
4	REAR & ROD EYE BORE	28 (H7)	BORE GAUGE	28.03	28.018	28.025	28.025	28.03
5	INLET PORT	1/8"BSP	PLUG GAUGE	OK	OK	OK	OK	OK
6	OUTLET PORT	3/8" BSP	PLUG GAUGE	OK	OK	OK	OK	OK
7	PLATING THICK	35+µ	PLATING THICK GAUGE	40	36	38	44	43
8	LEAKAGE	SHOULD NOT	VISUAL	NO LEAKAGE	NO LEAKAGE	NO LEAKAGE	NO LEAKAGE	NO LEAKAGE
9	MAX WORKING PRE.	160 BAR	PRESSURE GAUGE	OK	OK	OK	OK	OK

SPECIAL CASE:-CYL TESTED DURING 10 MINUTES AT 210 BAR PRESSURE.	REMARKS:-
INSPECTED BY SIGNATURE / DATE :- 20.08.18	APPROVED BY:-

Note :- All Dimensions are in MM.

★ DUTTA CONTROL ★ JOTIBANAGAR
TALAWADE
PUNE 62.

QUALITY PLAN AND INSPECTION REPORT

M/S NIHVA TECHNOLOGIES PVT.LTD

CYLINDER DESCRIPTION:-Ø50XØ35X426MM STROKE (ROD EYE & REAR EYE)

SUPPLIER NAME:-**DUTTA CONTROL**	INVOICE QUANTITY :-08 NO.	INVOICE DATE:- 20-08-2018.
PART NO:- 02-06-002-50-426.	INVOICE NO. :-00	INSP. SAMPLING CRITERIA :- 100%
PART NAME:-SINGLE ACTING HYDRAULIC CYL.	CHECKED QUANTITY :-08 NO.	
DRG .REV. NO:-	P.O. NO :-	P.O DATE:-

SR. NO-	PARAMETER	SPCIFICATION	INSTRUMENT	SUPPLIER OBSERVETION				
				7	8			
1	TOTAL LENGTH(CLOSE)	684(+/- 2)	MEASURING SCALE	685	684			
2	STROKE	426(+/- 1)	MEASURING SCALE	427	425			
3	CTC DISTANCE	634(+/- 0.5)	MEASURING SCALE	634	633			
4	REAR & ROD EYE BORE	28 (H7)	BORE GAUGE	28.02	28.022			
5	INLET PORT	1/8"BSP	PLUG GAUGE	OK	OK			
6	OUTLET PORT	3/8" BSP	PLUG GAUGE	OK	OK			
7	PLATING THICK	35+µ	PLATING THICK GAUGE	39	41			
8	LEAKAGE	SHOULD NOT	VISUAL	NO LEAKAGE	NO LEAKAGE			
9	MAX WORKING PRE.	160 BAR	PRESSURE GAUGE	OK	OK			

SPECIAL CASE:-CYL TESTED DURING 10 MINUTES AT 210 BAR PRESSURE.

REMARKS:-

INSPECTED BY SIGNATURE / DATE :- 20.08.18

APPROVED BY:-

★ DUTTA CONTROL ★ JYOTIBANAGAR
TALAWADE
PUNE - 62.

Note :- All Dimensions are in MM.