Opening doors
to business and life

ASSA ABLOY

ASSA ABLOY Entrance Systems

The global leader in door opening solutions

Project	**Hal NIHVA**
Location	**Bangalore**
Application	**Civil Aviation**
Our ref.no.	**219-080**
Calculated	**14-3-2019 16:52**
Notes	

System summary

Calc by	Henk v.d. Heijden
Version	V 11-3-2019 13:19:50 4606
Revision	
Identical doors	1
Total weight	3420 kg
Shipping weight	3936 kg
Shipping volume	27,06 m³
Environment	Megadoor Standard
Nominal current	10,2 A
Total power	5,0 kW
Hoist peak current	45,0 A
Voltage/Frequency	400 V 50 Hz
Control panel	Basic Cabinet, 500x600x250 (12A nom.)

Options selected

Back-up power switch	
Audible and visual alarm	
Beam clamps	

Door 1 options selected

No installation equipment	1 no.
Metal trim both sides	
Floor/site-built door leaf	
Colored clamp strip on inside	
Colored clamp strip on outside	

Door 1

CW	20000 mm
CH	5000 mm
Depth	290 mm
Differential pressure	0,7 kPa (14,6 psf)
Leaf height	6252 mm
Total height	6722 mm
Total width	20240 mm
Number of splices	1
Guide shoe load	10,2 kN
Leaf fabric outside	Standard fabric, Colour TBC
Leaf fabric inside	Standard fabric, Colour TBC
Hoist	1 * SK 973.1Z-112M/4
Open time	32 sec
Moving weight	2260 kg
Total weight	3420 kg
Bottom seal	EPDM Grey 600 mm