Opening doors
to business and life

ASSA ABLOY

ASSA ABLOY Entrance Systems

The global leader in
door opening solutions

Project	**Hal NIHVA**
Location	**Bangalore**
Application	**Civil Aviation**
Our ref.no.	**219-080**
Calculated	**14-3-2019 16:23**
Notes	

System summary

Calc by	Henk v.d. Heijden
Version	V 11-3-2019 13:19:50 4606
Revision	
Identical doors	1
Total weight	13701 kg
Shipping weight	16141 kg
Shipping volume	99,37 m³
Overall clear width	60000 mm
Environment	Megadoor Standard
Nominal current	54,3 A
Total power	25,7 kW
Hoist peak current	79,6 A
Voltage/Frequency	400 V 50 Hz
Control panel base	A1 Door Cabinet, 500x600x250
Control panel	A10x Door/Mullion Cabinet, 500x600x250 (20A nom.)
Control panel	A10x Door Cabinet, 500x600x250 (20A nom.)
Control panel	A10x Door/Mullion Cabinet, 500x600x250 (20A nom.)

Options selected

Make level door	
Back-up power switch	
Audible and visual alarm	
Beam clamps	

Door 1 options selected

No installation equipment	1 no.
Metal trim both sides	
Floor/site-built door leaf	
Colored clamp strip on inside	
Colored clamp strip on outside	

Door 1

CW	19706 mm
CH	7650 mm
Depth	290 mm
Differential pressure	0,7 kPa (14,6 psf)
Leaf height	9081 mm
Total height	9551 mm
Total width	19946 mm
Number of splices	1
Guide shoe load	9,5 kN
Leaf fabric outside	Standard fabric, Colour TBC
Leaf fabric inside	Standard fabric, Colour TBC
Hoist	1 * SK 73F-132S/4 OD440
Open time	49 sec
Moving weight	2482 kg
Total weight	3803 kg
Bottom seal	EPDM Grey 748 mm

Mullion 12

Mullion	VKR400x200x6,3 355
Clear under mullion	7000 mm
Building deflection down	87 mm
Building deflection up	87 mm
Mullion swing time	59 sec
Mullion floor pit lenght	2000 mm
Mullion hoist load	535 kg
Mullion weight	1188 kg

Door 2 options selected

Metal trim both sides
Floor/site-built door leaf
Colored clamp strip on inside
Colored clamp strip on outside

Door 2

CW	19706 mm
CH	7650 mm
Depth	290 mm
Differential pressure	0,7 kPa (14,6 psf)
Leaf height	9081 mm
Total height	9551 mm
Total width	19946 mm
Number of splices	1
Guide shoe load	9,5 kN
Leaf fabric outside	Standard fabric, Colour TBC
Leaf fabric inside	Standard fabric, Colour TBC
Hoist	1 * SK 73F-132S/4 OD440
Open time	49 sec
Moving weight	2482 kg
Total weight	3720 kg
Bottom seal	EPDM Grey 748 mm

Mullion 23

Mullion	VKR400x200x6,3 355
Clear under mullion	7000 mm
Building deflection down	87 mm
Building deflection up	87 mm
Mullion swing time	59 sec
Mullion floor pit lenght	2000 mm
Mullion hoist load	535 kg
Mullion weight	1188 kg

Door 3 options selected

Metal trim both sides
Floor/site-built door leaf
Colored clamp strip on inside
Colored clamp strip on outside

Door 3

CW	19706 mm
CH	7650 mm
Depth	290 mm
Differential pressure	0,7 kPa (14,6 psf)
Leaf height	9081 mm
Total height	9551 mm
Total width	19946 mm
Number of splices	1
Guide shoe load	9,5 kN
Leaf fabric outside	Standard fabric, Colour TBC
Leaf fabric inside	Standard fabric, Colour TBC
Hoist	1 * SK 73F-132S/4 OD440
Open time	49 sec
Moving weight	2482 kg
Total weight	3803 kg
Bottom seal	EPDM Grey 748 mm