1.2 mm GI Motorised Single Skin Rolling Shutter - Indirect Drive

Sr .No.	Specification	1.2 mm GI Motorised Single Skin Rolling Shutter - Indirect Drive
1	**Description:**	Motorised Rolling Shutter with GI Slats with thickness of 1.2 mm.
2	**Mounting Location area**	Inside area / Outside area
3	**Mounting Surface**	Side Brackets: Optional = On Concrete /Steel & Side
4	**Curtain Panel**	The panel made of 1.2mm thick GI.
5	**Curtain panel size**	75mm wide
6	**Curtain Profile**	Curved with 600mm grill at a height 1200mm from bottom
7	**Bottom Profile**	M. S. Plate 100 mm x 2.5 mm thick with angle stiffener
8	**Side Guide Profile**	M.S."U" Shaped profile 65 mm -150 mm x 3 mm thick.
9	**Roller Shaft**	M.S. Tubular Pipe with Flange & machined shaft at the ends Pipe Día -100 to 300 mm as per w x h
10	**Side Brackets**	MS Plate 3 mm to 10 mm thick, as per the opening dimension.
11	**Hood Cover**	Made of GI Sheet Thickness 0.9 mm
12	**Surface finish**	PU paint or Powder coated
13	**Drive Unit & Mounting Type**	Electric Motor - Indirect Mounting - Sprocket chain arrangement – IP54 Protection

WORK ORDER

NIHVA TECHNOLOGIES PVT. LTD.

Client:		PO Number:	SQA.23.24.0297	W. O. No-	SO/23-24/053
REL CONSTROTECH LLP		PO Dated :	28.11.2023	W. O. Date	01-12-2023
Address:		PO Received Date:	01.12.2023	Sales Co ordinator	Shilpa
		Ref. Quotation:	SQA.23.24.0297	Front Sales Person	Santosh

Contact Details		Billing Address:	Dispatch Address:
Contact Person:			
Email ID of contact Person:			
Mobile No:			

A Technical Terms:

Sr. No	Description of Goods	UOM	Qty.	Supply Rate	Installation Rate	Total Amount	Dwg. Approval Status
1	Motorized Rolling Shutter with Galvanized Steel Slats 1.2 mm Thick, Grill and Indirect Drive 3 Phase Electric Motor Size: (W) 4000 mm X (H) 6000 mm (Supply & Installation) Grill DimensionsFFL to Grill Bottom - 4.5 Feet FFL to Grill Top - 6.5 Feet, Grill Height - 2 Feet	Nos	3	-	-	-	Pending
2	Motorized Rolling Shutter with Galvanized Steel Slats 1.2 mm Thick, Grill and Indirect Drive 3 Phase Electric Motor Size: (W) 3000 mm X (H) 4000 mm (Supply & Installation) Grill DimensionsFFL to Grill Bottom - 4.5 Feet FFL to Grill Top - 6.5 Feet Grill Height - 2 Feet	Nos	1	-	-	-	Pending
					Total		-

Non standard items/extra requirement, if any:

B Commerical Terms:

1	Payment Terms:	40% Advance along with Purchase Order, 40% Payment immediately on Delivery and Balance 20% on Installation		
2A	Delivery Date as per PO:	2 weeks from approval of Drawings	2B. Required Delivery Date:	
3A	Transportation Scope:	In Client Scope	3B. Transportation Charges:	
4	P&F Charges:	Nil		
5A	Loading Scope:	NIHVA Scope	5B. Loading Charges:	
6A	Unloading Scope:	In Client Scope	6B. Unloading Charges:	
7A	Lifting Equipments Scope:	In Client Scope	7B. Available Lifting Equipments:	
8	Warranty:	12 months from the date of supply.		
9A	Height arrangement Scope:	In Client Scope	9B. Available Equipments for working at Site:	
10	Electricity Supply:	In Client Scope		
11	GST:	18%		
12A	Installation Scope:	NIHVA Scope	12B. Installation required date:	
13	Mode of import:	NA		
14	HSS:	NA		
15	Documentation Required:	Standard Handover Documents		
16A	Total site visits required:		16B. Site visit charges:	

Certified that the above work order finalised in presence of:

GM	AGM	SALES		Operation	PROJECT	DESIGN	Date & Time